


ENSTO

EMERGENCY LIGHTING

Safety during power failure



EMERGENCY LIGHTING

Safety during power failure

Emergency lighting is required in public buildings to ensure that exit routes are lit in the event of a power failure. To support our current product range, we have developed emergency luminaire versions for our JONO and AVR320/400 product ranges.

Emergency luminaires as part of regular lighting

The product range was selected based on the luminaires most commonly used in public buildings, allowing the emergency luminaires to be used as part of general lighting.


Emergency lighting utilises a power input independent of that of regular lighting, allowing the lights to remain on during power failures thanks to luminaire-specific batteries. The job of emergency luminaires is to ensure the safe exit of people from the

premises, and that fire extinguishing and safety equipment can be located and used without unnecessary effort. These luminaires are meant for the emergency lighting of exit routes and open areas.



JONO EMERGENCY LUMINAIRES

AVR66 emergency luminaire



Continuous-operation unit emergency luminaire for dry and humid spaces, mounted on walls or the ceiling. The frame of the luminaire is manufactured from aluminium profile painted white. The ends and the dome are manufactured from shock-proof polycarbonate.

| TYPE* | EAN-CODE | LIGHT SOURCE | BATTERY | BLF |
|---------------|-------------------|--------------|-------------|------|
| AVR66.036E/3M | 64 186 77 618 123 | T8-36W | NiCd 5x1,2V | 0,15 |
| AVR66.058E/3M | 64 186 77 618 130 | T8-58W | NiCd 5x1,2V | 0,10 |
| AVR66.021E/3M | 64 186 77 618 147 | T5-21W | NiCd 5x1,2V | 0,25 |
| AVR66.028E/3M | 64 186 77 618 154 | T5-28W | NiCd 6x1,2V | 0,11 |
| AVR66.035E/3M | 64 186 77 618 161 | T5-35W | NiCd 6x1,2V | 0,10 |



AVR400 AND AVR320 EMERGENCY LUMINAIRES

AVR400 and AVR320 unit emergency luminaires



AVR400 and AVR320 emergency luminaires equipped with luminaire-specific batteries for dry and humid spaces. Suitable for surface and recessed mounting on both walls and the ceiling. Compatible with the décor rings of standard luminaires.

| TYPE* | EAN-CODE | LIGHT SOURCE | BATTERY | BLF |
|-----------------|-------------------|--------------|-------------|------|
| AVR400.128H/3M | 64 186 77 618 178 | TC-DD28W | NiCd 5x1,2V | 0,21 |
| AVR400.218E/3SM | 64 186 77 618 185 | 2xTC-L18W | NiCd 5x1,2V | 0,18 |
| AVR320.218E/3SM | 64 186 77 618 192 | 2xTC-DE18W | NiCd 5x1,2V | 0,28 |

* M = Continuous-operation emergency luminaire; S = Emergency luminaire combo; 3 = Operating time (hours)
BLF = Ballast Lumen Factor, the ratio of light output in emergency lighting compared with normal lighting



AVR320 emergency luminaire with a black décor ring AVL45.1



ENSTO ELECTRIC OY
P.O. Box 110
06101 PORVUO, FINLAND
TEL. +358 (0) 204 76 21
FAX +358 (0) 204 76 2753
ELECTRIC@ENSTO.COM
WWW.ENSTO.COM