

Switching Power Supply



Feature

- Compact design, small size and light weight
- Internal EMI filter
- Remote Control Function
- Short-circuit protection and over-load protection
- High efficiency and good reliability
- Power Output LED Indicator
- Over-heat Protection
- UPS Function
- Certificate : CE Certificate

Specifications

| Type | SP-05AS | SP-12AS | SP-24AS | SP-05AL | SP-12AL | SP-24AL |
|--------------------------------|--|---------|---------|------------------|---------|---------|
| Output Voltage | 5V | 12V | 24V | 5V | 12V | 24V |
| Output Current | 6A | 3A | 1.5A | 10A | 6A | 3A |
| Installation | Standard 35mm DIN (EN50022-35) | | | | | |
| Full-range Voltage Input | 100-240VAC / 140-340VDC | | | | | |
| Waving Voltage Allowance Range | 85-264VAC / 120-370VDC | | | | | |
| Input Frequency | 47-63Hz | | | | | |
| Output Voltage Stability | $\leq \pm 0.5\%$ | | | | | |
| Ripple | $\leq 150\text{mVp-p}$ | | | | | |
| Temperature | $-25\text{ }^{\circ}\text{C} \sim +70\text{ }^{\circ}\text{C}$ | | | | | |
| Insulation and Breakdown | $> 1.5\text{KV}$ | | | | | |
| Efficiency | $> 75\%$ | | | | | |
| Dimensions(L×W×H) | 71mm×106mm×65mm | | | 126mm×106mm×65mm | | |

MAXTHERMO-GITTA GROUP CORPORATION

Add: 3C25, Taipei World Trade Center, No. 5, Sec. 5, Hsin Yi Rd. Taipei Taiwan, R.O.C.

Tel: 886-2-27206601 (Rep.)

Fax: 886-2-27206603 & 886-2-23455120

E-mail: gitta@ms9.hinet.net Website: www.maxthermo.com