

■ 产品材质: A.C.F部位采用黄铜镀镍, D部位采用UL认可的尼龙PA66, B.E部位采用丁腈橡胶。

■ 螺纹规格: 公制(Metric), 德制(PG), 英制(G), 美制(NPT)。

■ 工作温度: -40℃至100℃, 瞬时耐热至120℃。




■ 产品特点: 特殊的夹紧爪与橡胶件设计, 夹紧电缆范围大, 抗拉力特强, 可防水, 防尘, 防盐, 耐酸碱, 酒精, 油脂及一般溶剂。

■ Material: Parts A, C, F are made of brass plated with nickel, part D is made of UL approved nylon PA66, parts B and E are made of nitrile butadiene rubber (NBR).

■ Thread spec.: Metric, PG, G, NPT.

■ Working temperature: -40℃ to 100℃, instantaneous heat resistance up to 120℃.

■ Characteristics: Special design of clamping die and rubber part, large range in clamping the cable, ultra-strong stretching resistance, waterproof, dustproof, and high ability to resist salt, acid, alkali, alcohol, grease and general solvent.



编号 NO.	产品型号 Model	螺纹规格 Thread Size	适用电缆 Cable Range (mm)	螺纹外径 Thread O. D. L2 (mm)	螺纹长度 Thread Length L1 (mm)	扳手直径 Spanner Size (mm)
	G1/4" -M	G1/4"	3~6.5	13.1	8	14
	G1/4" -M	G1/4"	2~5	13.1	8	14
	G3/8" -M	G3/8"	4~8	16.6	10	18
	G3/8" -M	G3/8"	2~6	16.6	10	18
	G1/2" -M	G1/2"	6~12	20.9	13	22
	G1/2" -M	G1/2"	5~9	20.9	13	22
	G3/4" -M	G3/4"	13~18	26.4	15	30
	G3/4" -M	G3/4"	9~16	26.4	15	30
	G1" -M	G1"	18~25	33.2	15	40
	G1" -M	G1"	13~20	33.2	15	40
	G1 1/4" -M	G1 1/4"	18~25	41.9	15	50
	G1 1/4" -M	G1 1/4"	13~20	41.9	15	50
	G1 1/2" -M	G1 1/2"	22~32	48	15	57
	G1 1/2" -M	G1 1/2"	20~26	48	15	57
	G2" -M	G2"	37~44	60	15	64
	G2" -M	G2"	29~34	60	15	64

