

NEW

Raychem **RPG** 

aluEiNTM

aluminium Die-cast Ex Enclosure



IP 66



(A TE - Connectivity - RPG Enterprises JV)



Raychem RPG - ATEX MARKING














0539

II 2 G Ex e IIC Gb
II 2 D Ex tb IIIC Db IP66
DEMKO 13 ATEX 1327771U
IECEX UL 13.0042U

Technical Data Sheet :

Die-cast Aluminium Enclosure

-  Material : AISi 12
-  Surface : Plain or Powder Coated
-  Lid Screw : Stainless Steel, Captive Screw
-  Tightning Torque : M4 (2 To 3) N-m, M6 (3 To 4) N-m.
-  Service Temperature : - 50°C to +135°C
-  Mechanical Strength : Accordance With 60079-0, Impact Energy 7 Nm
-  Protection Class : EN 60529, IP 66
-  Compliance Standard : IEC/EN 60079-0, IEC/EN 60079-7 and IEC/EN 60079-31.
-  Process Control System : ISO 9001:2008, IEC 80079-34: 2011
-  Standard Color : RAL 7001, 7031, 7032, 7035, 7038, Black RAL 9004, White RAL 9010
-  Internal/External Earthing : 4 mm² To 120 mm² Internal and External

Raychem Model No.	Order No.	Size			Coating		Certification / Conformity					
		Length	Width	Height	Natural	Painted	ATEX	IECEx	UL-508A	UL-50E	CE	IP66
EX-AJB586434-U	EXRJ 04	58	64	34	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB986434-U	EXRJ 02	98	64	34	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB1506434-U	EXRJ 03	150	64	34	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB758057-U	EXRJ 05	75	80	57	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB1258057-U	EXRJ 06	125	80	57	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB1758057-U	EXRJ 07	175	80	57	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB2508054-U	EXRJ 08	250	80	54	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB10010081-U	EXRJ 09	100	100	81	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB16010081-U	EXRJ 10	160	100	81	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB12212081-U	EXRJ 11	122	120	81	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB22012081-U	EXRJ 21	220	120	81	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB22012090-U	EXRJ 12	220	120	90	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB26016090-U	EXRJ 13	260	160	90	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB36016090-U	EXRJ 14	360	160	90	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB16016091-U	EXRJ 15	160	160	91	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB12212091-U	EXRJ 22	120	120	91	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB280230110-U	EXRJ 17	280	230	110	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB230200110-U	EXRJ 19	230	200	110	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB330230110-U	EXRJ 18	330	230	110	Y	Y	Y	Y	Y	Y	Y	Y
EX-AJB330230180-U	EXRJ 20	330	230	180	Y	Y	Y	Y	Y	Y	Y	Y

