因联结而喜悦!!
Delight Through Connections

町洋企業股份有限公司
DINKLE ENTERPRISE CO., LTD.

臺灣新北市五股區五權二路19號（新北產業園區）
No.19,Wuquan 2nd Road., Wugu District,
New Taipei City 24890, Taiwan
TEL:+886-2-8069-9000　7705-6900
FAX:+886-2-2290-1702（代表號）
E-mail:service@dinkle.com
Web:www.dinkle.com

町洋國際股份有限公司
DINKLE INTERNATIONAL CO., LTD.

臺灣新北市五股區五權二路19號（新北產業園區）
No.19,Wuquan 2nd Road., Wugu District,
New Taipei City 24890, Taiwan
TEL:+886-2-8069-9000　7705-6900
FAX:+886-2-2290-1702
E-mail:service@dinkle.com
Web:www.dinkle.com

奧迪克國際有限公司
OPTIKLE INTERNATIONAL CO., LTD.

香港九龍九龍灣宏冠道6號 鴻力工業中心B座1樓29室
Room 29, 1/F, Block B, Proficient Industrial Center,
No.6 Wang Kwun Road, Kowloon Bay, Kowloon,
HONG KONG
TEL:+852-2795-3840　2758-8005
FAX:+852-2753-6919
E-mail:service@dinkle.com
Web:www.dinkle.com

町洋机电(中国)有限公司
DINKLE ELECTRIC MACHINERY (CHINA) CO., LTD.

江蘇省昆山市千燈鎮石浦工商管理區興浦中路258號(215343)
No.258,Xingpu Mid RD,Shipu Business Adminstration Estate,
Qiandeng Town, Kunshan City, Jiangsu Province, China
TEL:+86-512-5708-8588
FAX:+86-512-5708-8600
E-mail:service@dinkle.com
Web:www.dinkle.com

东莞立洋电机有限公司
LIYAN ELECTRIC MACHINERY (DONGGUAN) CO., LTD.

廣東省東莞市黃江鎮鷄啼崗村金錢嶺一街2號
No.2 1st street Jinqian Ridge, Jiming gang village,
Huangjiang town, Dongguan City, Guangdong Province
TEL:+86-769-8336-4350　8336-4370
FAX:+86-769-8384-8634
E-mail:service@dinkle.com
Web:www.dinkle.com

DINKLE CORPORATION, USA

12613 Executive Drive, Suite 704, Stafford, Texas 77477
TEL:+1-832-539-4703
Toll-Free:+1-844-273-1850
FAX:+1-832-532-7226
E-mail:service@dinkle.com
Web:www.dinkle.com

DINKLE S.R.L., ITALY

Via Stabilini n°14, 23864 Malgrate (LC), Italia
TEL:+39/0341176154
E-mail:service@dinkle.com
Web:www.dinkle.com

町洋电气贸易(上海)有限公司
DINKLE ELECTRIC TRADING (SHANGHAI) CO., LTD.

上海市徐匯區虹橋路3號港匯中心二座3706單元
Unit 3706, 2 Grand Gateway, No. 3 Hongqiao Road,
Xuhui District, Shanghai City.
TEL:+86-21-6487-0636　6427-3157
FAX:+86-21-3356-2500
E-mail:service@dinkle.com
Web:www.dinkle.com

北京辦事處
北京市海澱區知春路甲48號盈都大厦C座1單元5B
TEL:+86-10-5873-4338
FAX:+86-10-5873-4337

西安辦事處
陝西省西安市雁塔區科技路209號新西藍1-1-1705室
TEL:+86-29-8885-8475
FAX:+86-21-3356-2500

E-mail : service@dinkle.com
Web : www.dinkle.com

Dinkle remains the right of product modification and engineering change of design. The catalogue is for reference only. The final product is made according to actual engineering drawing.

弊社標準品に関しては、修正や設計変更等が行われるため、カタログは参考であり、詳細仕様は図面を基準とする。

本公司對產品保有修改、設變權，目錄僅供參考，實際產品仍需依照工程圖面為準。

Mar./2019

Terminal Block

Delight Through Connections



町洋國際股份有限公司
DINKLE INTERNATIONAL CO., LTD.

DC-27.2e

Dinkle，Delight through connections

Dinkle is one of the global major manufacturers of terminal blocks and committed to meet the highest application requirements of automation industry.

We continuously improve our productivity and competitive advantages, while keeping pace with the new production techniques and the global industrial trend. We work with trading offices in over 40 countries providing products and technical support services.

The business was established in Taiwan on July 22nd, 1983, it started from manufacturing barrier type terminal blocks. The first production facilities in China were set up in 1995, with 15 sales offices in Greater China region. Dinkle facilities include an R&D center for terminal blocks in Jiangsu, two OEM product development centers in KunShan and DongGuan city, an R&D center for electronics in Taipei, a CNAS certified laboratory in Jiangsu and two main production facilities in Jiangsu and Guangdong.

Terminal blocks are widely used in six main industrial applications including Production Automation, Process Automation, Power Automation, Railway Transportation, New Energy and Equipment Manufacturing. All of our production facilities granted ISO 9001 quality control system certification and ISO 14001 environmental management system certification, and Dinkle's products have safety certifications include UL, CUL, CSA, VDE, GB. All products and materials used meet EU environmental policy of RoHS Directive and REACH regulation.

With more than 30 years of manufacturing experiences, Dinkle team is here to help to make your business successful. We provide reliable products and offer professional technical support and practical example to illustrate our solutions which are able to assist your business of improving production automation level and technical standard. No matter what your requirement is, you will find out the ideal solutions from Dinkle.



Table of Contents

PID (Push-In Design) Plug - Pluggable PCB Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
2.50	150	4	ESC250V-XXP	26	
2.54	150	5	0156-1AXX-BK	3	Screw flange
2.54	150	5	0156-1BXX-BK	3	
2.54	150	5	0156-1CXX-BK	3	Lock flange
2.54	150	5	0156-1DXX-BK	3	Release tool
3.50	150	2	0191-01XX	32	
3.50	150	2	0191-01XXC	32	With cover
3.50	150	6	0184-11XX	31	
3.50	150	6	0184-12XX	31	
3.50	150	6	0184-13XX	31	
3.50	150	6	0184-14XX	31	
3.50	150	8	0156-2AXX-BK	4	Screw flange
3.50	150	8	0156-2BXX-BK	4	
3.50	150	8	0156-2CXX-BK	4	Lock flange
3.50	150	8	0156-2DXX-BK	4	Release tool
3.50	150	8	0159-01XX	5	Screw flange
3.50	150	8	0159-03XX	5	
3.50	150	8	0159-04XX	5	Release tool
3.50	300	8	0181-A1XX	22	
3.50	300	8	0181-A3XX	22	
3.50	300	8	0191-06XX	32	
3.50	300	8	0191-06XXC	32	
3.50	300	8	0221-20XX	6	
3.50	300	8	0221-21XX	7	
3.50	300	8	0221-24XX	7	
3.50	300	8	0221-28XX	7	Screw flange
3.50	300	8	0225-01XX	12	Screw flange/light pipe
3.50	300	8	0225-02XX	12	Lock flange/light pipe
3.50	300	8	0225-03XX	12	Light pipe
3.50	300	8	0225-06XX	13	Screw flange
3.50	300	8	0225-07XX	13	Lock flange
3.50	300	8	0225-08XX	13	
3.50	300	8	ESC350V-XXP	27	
3.50	300	8	ESC350VM-XXP	27	
3.81	300	8	0221-42XX	8	
3.81	300	8	0221-43XX	8	Screw flange
3.81	300	8	0221-44XX	8	
3.81	300	8	ESC381V-XXP	27	
3.81	300	8	ESC381VK-XXP	27	Release tool
3.81	300	8	ESC381VM-XXP	27	Screw flange
5.00	300	2	0191-02XX	32	
5.00	300	2	0191-02XXC	32	
5.00	300	6	0184-31XX	31	
5.00	300	6	0184-32XX	31	
5.00	300	6	0184-33XX	31	
5.00	300	6	0184-34XX	31	
5.00	300	10	0226-01XX	14	Screw flange/light pipe
5.00	300	10	0226-02XX	14	Lock flange/light pipe
5.00	300	10	0226-03XX	14	Light pipe
5.00	300	10	0226-06XX	15	Screw flange
5.00	300	10	0226-07XX	15	Lock flange
5.00	300	10	0226-08XX	15	
5.00	300	10	5ESDS-XXP	28	
5.00	300	10	5ESDSM-XXP	29	Screw flange
5.00	300	10	5ESDSR-XXP	28	
5.00	300	10	5ESDSRM-XXP	29	Screw flange
5.00	300	10	5ESV-XXP	18	
5.00	300	10	5ESVK-XXP	18	Release tool
5.00	300	10	5ESVM-XXP	18	Screw flange
5.00	300	10	5ESR-XXP	18	
5.00	300	10	5ESRK-XXP	19	Release tool
5.00	300	10	5ESRM-XXP	18	Screw flange
5.00	300	15	0161-01XX	23	Screw flange
5.00	300	15	0161-02XX	23	Lock flange
5.00	300	15	0161-03XX	23	
5.00	300	15	0161-04XX	23	Release tool
5.00	300	15	0161-11XX	23	Screw flange/inverted contact
5.00	300	15	0161-12XX	23	Lock flange/inverted contact
5.00	300	15	0161-13XX	23	Inverted contact
5.00	300	15	0161-14XX	23	Release tool/inverted contact
5.00	300	15	0227-01XX	16	Screw flange/light pipe
5.00	300	15	0227-02XX	16	Lock flange/light pipe
5.00	300	15	0227-03XX	16	Light pipe
5.00	300	15	0227-04XX	16	Release tool/light pipe
5.00	300	15	0227-06XX	17	Screw flange
5.00	300	15	0227-07XX	17	Lock flange
5.00	300	15	0227-08XX	17	
5.00	300	15	0227-09XX	17	Release tool
5.08	300	8	0225-04XX	11	Screw flange
5.08	300	8	0225-05XX	11	Lock flange
5.08	300	8	0225-09XX	11	
5.08	300	8	0225-0AXX	11	Release tool
5.08	300	8	ESC508V-XXP	28	
5.08	300	8	ESC508VM-XXP	29	Screw flange
5.08	300	10	2ESDS-XXP	28	
5.08	300	10	2ESDSM-XXP	29	Screw flange
5.08	300	10	2ESDSR-XXP	28	
5.08	300	10	2ESDSRM-XXP	29	Screw flange
5.08	300	10	2ESDSV-XXP	18	
5.08	300	10	2ESDSVM-XXP	19	Screw flange
5.08	300	10	2ESDSVK-XXP	19	Release tool
5.08	300	10	2ESR-XXP	20	
5.08	300	10	2ESRK-XXP	20	Release tool
5.08	300	10	2ESRM-XXP	20	Screw flange
5.08	300	10	2ESV-XXP	20	
5.08	300	10	2ESVK-XXP	20	Release tool
5.08	300	10	2ESVM-XXP	20	Screw flange
5.08	300	12	2ESDB-XXP	28	
5.08	300	12	2ESDBA-XXP	28	
5.08	300	12	2ESDBAM-XXP	29	Screw flange
5.08	300	12	2ESDBM-XXP	29	Screw flange
5.08	300	15	2ESS-XXP	20	
5.08	300	15	2ESSM-XXP	20	Screw flange
5.08	300	16	0150-20XX	24	Lock flange beneath
5.08	300	16	0150-21XX	24	
6.35	600	20	0150-30XX	25	Lock flange beneath
6.35	600	20	0150-31XX	25	
7.00	300	6	0184-51XX	30	
7.00	300	6	0184-52XX	30	
7.00	300	6	0184-53XX	30	
7.00	300	6	0184-54XX	30	
7.50	600	18	0150-40XX	25	
7.62	300	10	3ESDS-XXP	30	
7.62	300	10	3ESDSM-XXP	30	Screw flange
7.62	300	10	3ESDSR-XXP	30	
7.62	300	10	3ESDSRM-XXP	30	Screw flange
10.00	300	6	0184-81XX	30	
10.00	300	6	0184-82XX	30	
10.00	300	6	0184-83XX	30	
10.00	300	6	0184-84XX	30	

Screw Connection Plug - Pluggable PCB Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
3.50	300	8	EC350F-XXP	35	
3.50	300	8	EC350FM-XXP	35	Screw flange
3.50	300	8	EC350R-XXP	34	
3.50	300	8	EC350RM-XXP	34	Screw flange
3.50	300	8	EC350RL-XXP	34	
3.50	300	8	EC350RLM-XXP	34	Screw flange
3.50	300	8	EC350V-XXP	34	
3.50	300	8	EC350VM-XXP	34	Screw flange
3.81	300	8	EC381F-XXP	35	
3.81	300	8	EC381FM-XXP	35	Screw flange
3.81	300	8	EC381R-XXP	34	
3.81	300	8	EC381RM-XXP	34	Screw flange
3.81	300	8	EC381RL-XXP	34	
3.81	300	8	EC381RLM-XXP	34	Screw flange
3.81	300	8	EC381V-XXP	34	
3.81	300	8	EC381VK-XXP	37	
3.81	300	8	EC381VM-XXP	34	Screw flange
3.81	300	8	EC381L-XXP	36	
3.81	300	8	EC381LM-XXP	36	
4.00	300	10	0162-01XX	51	
4.00	300	10	0162-A1XX	51	
5.00	300	7	ED130F-XXP	50	
5.00	300	12	ED130R-XXP	50	
5.00	300	15	5ESDA-XXP	37	
5.00	300	15	5ESDAM-XXP	38	Screw flange
5.00	300	15	5ESDF-XXP	37	
5.00	300	15	5ESDFM-XXP	37	Screw flange
5.00	300	15	5ESDP-XXP	37	
5.00	300	15	5ESDPM-XXP	38	Screw flange
5.00	300	15	5ESDPL-XXP	38	
5.00	300	15	5ESDPLM-XXP	38	Screw flange
5.00	300	15	5ESDT-XXP	38	
5.00	300	15	5ESDV-XXP	38	
5.00	300	15	5ESDVM-XXP	38	Screw flange
5.08	300	6	FDC508B-XXP	43	
5.08	300	6	FDC508B1-XXP	43	
5.08	300	6	FDC508B3-XXP	43	
5.08	300	6	FDC508BM-XXP	43	

Table of Contents

Screw Connection Plug - Pluggable PCB Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
5.08	300	10	0164-01XX	51	
5.08	300	10	0164-01XX(T)	51	
5.08	300	10	0164-A1XX	51	
5.08	300	10	0164-A1XX(T)	51	
5.08	300	12	EC508F-XXP	36	
5.08	300	12	EC508FM-XXP	36	Screw flange
5.08	300	12	EC508V-XXP	36	
5.08	300	12	EC508VM-XXP	36	Screw flange
5.08	300	15	2ESDA-XXP	39	
5.08	300	15	2ESDAM-XXP	40	Screw flange
5.08	300	15	2ESDF-XXP	39	
5.08	300	15	2ESDFM-XXP	39	Screw flange
5.08	300	15	2ESDL-XXP	40	
5.08	300	15	2ESDP-XXP	39	
5.08	300	15	2ESDPM-XXP	39	Screw flange
5.08	300	15	2ESDPL-XXP	40	
5.08	300	15	2ESDPLM-XXP	40	Screw flange
5.08	300	15	2ESDV-XXP	39	
5.08	300	15	2ESDVM-XXP	39	Screw flange
5.08	300	16	2ESDVB-XXP	40	
5.08	300	16	2ESDVBM-XXP	40	Screw flange
7.50	300	15	7ESDP-XXP	41	
7.50	300	15	7ESDPM-XXP	41	Screw flange
7.50	300	15	7ESDPL-XXP	41	
7.50	300	15	7ESDPLM-XXP	41	Screw flange
7.50	300	15	7ESDV-XXP	41	
7.50	300	15	7ESDVM-XXP	41	Screw flange
7.62	300	15	3ESDP-XXP	42	
7.62	300	15	3ESDPM-XXP	42	Screw flange
7.62	300	15	3ESDPL-XXP	42	
7.62	300	15	3ESDPLM-XXP	42	Screw flange
7.62	300	15	3ESDV-XXP	42	
7.62	300	15	3ESDVM-XXP	42	Screw flange
7.62	300	30	EC762V-XXP	46	
7.62	300	30	EC762VM-XXP	47	Screw flange
7.62	300	30	EC762VN-XXP	46	
7.62	300	30	EC762VNM-XXP	47	Screw flange
7.62	600	15	3ESNP-XXP	45	
7.62	600	18	3ESNPHL-XXP	45	
7.62	600	15	3ESNPL-XXP	45	
7.62	600	15	3ESNPLM-XXP	46	Screw flange
7.62	600	15	3ESNPLS-XXP	45	
7.62	600	15	3ESNPLSM-XXP	46	Screw flange
7.62	600	15	3ESNPM-XXP	46	Screw flange
7.62	600	15	3ESNPS-XXP	45	
7.62	600	15	3ESNPSM-XXP	46	
7.62	600	25	0183-01XX	47	
7.62	600	25	0183-01XXTXX	47	
7.62	600	40	EC762HV-XXP	46	
7.62	600	40	EC762HVN-XXP	46	
7.62	600	40	EC762HVM-XXP	47	
7.62	600	40	EC762HVNM-XXP	47	Screw flange
10.16	600	51	0187-A4XX	48	
10.16	600	51	EC116V-XXP	48	
10.16	600	51	EC116VM-XXP	48	

Accessories

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
			SDH-002	25	Wire entry tool
			SDH-003	25	Wire entry tool
			CSC-01XX	49	Jumper
			ECHK1	49	Key coding
			ECHK1L	49	Key coding, THR
			ECHK2	49	Key coding
			ESDK1	49	Key coding
			ESDK2	49	Key coding
			EHDK1	49	Key coding
			EHDK1L	49	Key coding, THR
			ECHG1	57	Light pipe
			0159K1L	5	

Screw Connection Inverted Pluggable PCB Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
3.50	150	12	CPC350-XXP	52	PCB connection
3.50	300	8	EC350CR-XXP	53	
3.50	300	8	EC350CV-XXP	53	
3.81	300	8	EC381CR-XXP	53	
3.81	300	8	EC381CV-XXP	53	
3.81	300	8	ECSH381V-XXP	52	
5.00	300	15	5ESN-XXP	54	
5.00	300	16	5ESDG-XXP	52	PCB connection
5.08	300	12	2EHDRD-XXP	54	
5.08	300	12	2EHDRDM-XXP	54	Threaded flanges
5.08	300	12	2EHDRS-XXP	54	
5.08	300	12	2EHDRSM-XXP	54	Threaded flange
5.08	300	12	2ESDCR-XXP	53	
5.08	300	12	2ESDCRM-XXP	53	Threaded flange
5.08	300	12	2ESDCV-XXP	53	
5.08	300	12	2ESDCVM-XXP	53	Threaded flange
5.08	300	12	2ESH-XXP	52	
5.08	300	12	2ESHM-XXP	52	Screw flange
7.62	300	15	3ESDHM-XXP	54	Threaded flange
7.62	300	15	3ESH-XXP	54	

Headers (Sockets) For Pluggable PCB Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
2.50	150	4	ECH250R-XXP	55	
2.50	150	4	ECH250V-XXP	55	
2.50	150	4	ECHB250R-XXP	62	
2.50	150	4	ECHB250V-XXP	62	
2.54	150	5	0156-10XX	3	
2.54	150	5	0156-10XXL	3	THR
2.54	150	5	0156-12XX	3	Threaded flange/release tool
2.54	150	5	0156-12XXL	3	THR
2.54	150	5	0156-13XX	3	Threaded flange/release tool
2.54	150	5	0156-13XXL	3	THR
2.54	150	5	0156-15XX	3	
2.54	150	5	0156-15XXL	3	THR
2.54	150	5	0156-16XX	3	Lock flange
2.54	150	5	0156-16XXL	3	THR
2.54	150	5	0156-17XX	3	Threaded flange/release tool
2.54	150	5	0156-17XXL	3	THR
2.54	150	5	0156-18XX	3	Threaded flange/release tool
2.54	150	5	0156-18XXL	3	THR
2.54	150	5	0156-19XX	3	Lock flange
2.54	150	5	0156-19XXL	3	THR
3.50	150	2	0191-11XXTH	32	PIN strip, THR
3.50	150	8	0156-20XX-BK	4	
3.50	150	8	0156-20XXL	4	THR
3.50	150	8	0156-20XX-BK-WR	71	
3.50	150	8	0156-20XXLWR	71	THR
3.50	150	8	0156-21XX-BK	4	Threaded flange/release tool
3.50	150	8	0156-21XXL	4	THR
3.50	150	8	0156-21XX-BK-WR	71	
3.50	150	8	0156-21XXLWR	71	THR
3.50	150	8	0156-24XX-BK	4	
3.50	150	8	0156-24XXL	4	THR
3.50	150	8	0156-24XX-BK-WR	71	
3.50	150	8	0156-24XXLWR	71	THR
3.50	150	8	0156-25XX-BK	4	
3.50	150	8	0156-25XXL	4	THR
3.50	150	8	0156-25XX-BK-WR	71	
3.50	150	8	0156-25XXLWR	71	THR
3.50	150	8	0156-26XX-BK	4	Threaded flange/release tool
3.50	150	8	0156-26XXL	4	THR
3.50	150	8	0156-26XX-BK-WR	71	
3.50	150	8	0156-26XXLWR	71	THR
3.50	150	8	0156-29XX-BK	4	Lock flange
3.50	150	8	0156-29XXL	4	THR
3.50	150	8	0156-29XX-BK-WR	71	
3.50	150	8	0156-29XXLWR	71	THR
3.50	150	8	0159-11XX	5	Threaded flange/release tool
3.50	150	8	0159-11XXL	5	THR
3.50	150	8	0159-11XXWR	71	
3.50	150	8	0159-11XXLWR	71	THR
3.50	150	8	0159-12XX	5	Threaded flange/release tool

Table of Contents

Headers (Sockets) For Pluggable PCB Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
3.50	150	8	0159-12XXL	5	THR
3.50	150	8	0159-12XXWR	71	
3.50	150	8	0159-12XXLWR	71	THR
3.50	150	8	0159-31XX	5	
3.50	150	8	0159-31XXL	5	THR
3.50	150	8	0159-31XXWR	71	
3.50	150	8	0159-31XXLWR	71	THR
3.50	150	8	0159-32XX	5	
3.50	150	8	0159-32XXL	5	THR
3.50	150	8	0159-32XXWR	71	
3.50	150	8	0159-32XXLWR	71	THR
3.50	300	8	0191-16XXTH	32	
3.50	300	8	0221-22XX-BK	6	
3.50	300	8	0221-22XXL	6	THR
3.50	300	8	0221-23XXL	6	THR
3.50	300	8	0221-25XX-BK	6	
3.50	300	8	0221-25XXL	6	THR
3.50	300	8	0221-26XXL	7	THR
3.50	300	8	0221-27XX-BK	7	
3.50	300	8	0221-27XXL	7	THR
3.50	300	8	0221-35XXL	7	THR
3.50	300	8	0221-36XXL	7	THR
3.50	300	8	0221-41XX-BK	6	
3.50	300	8	0221-41XXL	6	THR
3.50	300	8	0225-11XX	12	Threaded flange/light pipe
3.50	300	8	0225-12XX	12	Threaded flange/light pipe
3.50	300	8	0225-16XX	13	Threaded flange
3.50	300	8	0225-16XXL	13	THR
3.50	300	8	0225-17XX	13	Threaded flange
3.50	300	8	0225-17XXL	13	THR
3.50	300	8	0225-21XX	12	Lock flange/light pipe
3.50	300	8	0225-22XX	12	Lock flange/light pipe
3.50	300	8	0225-26XX	13	Lock flange
3.50	300	8	0225-26XXL	13	THR
3.50	300	8	0225-27XX	13	Lock flange
3.50	300	8	0225-27XXL	13	THR
3.50	300	8	0225-31XX	12	Light pipe
3.50	300	8	0225-32XX	12	Light pipe
3.50	300	8	0225-36XX	13	
3.50	300	8	0225-36XXL	13	THR
3.50	300	8	0225-37XX	13	
3.50	300	8	0225-37XXL	13	THR
3.50	300	8	ECH350H-XXP	57	
3.50	300	8	ECH350R-XXP	56	
3.50	300	8	ECH350R-XXPL	67	THR
3.50	300	8	ECH350R-XXPWR	73	
3.50	300	8	ECH350R-XXPLWR	73	
3.50	300	8	ECH350RM-XXP	57	Threaded flange
3.50	300	8	ECH350RM-XXPL	66	THR
3.50	300	8	ECH350RM-XXPWR	73	
3.50	300	8	ECH350RM-XXPLWR	73	THR
3.50	300	8	ECH350RJ-XXPL	67	
3.50	300	8	ECH350RR-XXP	57	
3.50	300	8	ECH350RR-XXPL	67	THR
3.50	300	8	ECH350RR-XXPWR	72	
3.50	300	8	ECH350RR-XXPLWR	72	THR
3.50	300	8	ECH350RRM-XXP	57	Threaded flange
3.50	300	8	ECH350RRM-XXPL	67	THR
3.50	300	8	ECH350RRM-XXPWR	72	
3.50	300	8	ECH350RRM-XXPLWR	72	THR
3.50	300	8	ECH350RT-XXPL	67	THR
3.50	300	8	ECH350RT-XXPLWR	73	THR
3.50	300	8	ECH350V-XXP	56	
3.50	300	8	ECH350V-XXPL	66	THR
3.50	300	8	ECH350V-XXPWR	72	
3.50	300	8	ECH350V-XXPLWR	72	THR
3.50	300	8	ECH350VM-XXP	56	Threaded flange
3.50	300	8	ECH350VM-XXPL	67	THR
3.50	300	8	ECH350VM-XXPWR	72	
3.50	300	8	ECH350VM-XXPLWR	72	THR
3.50	300	8	ECH350VJ-XXPL	67	THR
3.50	300	8	ECH350VT-XXPL	67	THR
3.50	300	8	ECH350VT-XXPLWR	73	THR
3.50	300	8	ECHB350R-XXP	63	
3.50	300	8	ECHB350RM-XXP	63	Threaded flange
3.50	300	8	ECHB350V-XXP	63	
3.50	300	8	ECHB350VM-XXP	63	Threaded flange
3.50	300	8	EECH350R-XXP	64	
3.50	300	8	EECH350RM-XXP	65	Threaded flange
3.50	300	8	EECH350V-XXP	64	
3.50	300	8	EECH350VM-XXP	64	Threaded flange
3.81	300	8	0221-33XX-BK	8	
3.81	300	8	0221-33XXL	8	THR
3.81	300	8	0221-39XX-BK	8	
3.81	300	8	0221-39XXL	8	THR
3.81	300	8	0221-51XX-BK	8	Threaded flange
3.81	300	8	0221-51XXL	8	THR
3.81	300	8	0221-52XX-BK	8	Threaded flange
3.81	300	8	0221-52XXL	8	THR
3.81	300	8	ECH381A-XXP	56	
3.81	300	8	ECH381AM-XXP	56	Threaded flange
3.81	300	8	ECH381H-XXP	57	
3.81	300	8	ECH381R-XXP	56	
3.81	300	8	ECH381R-XXPL	67	THR
3.81	300	8	ECH381R-XXPWR	73	
3.81	300	8	ECH381R-XXPLWR	73	THR
3.81	300	8	ECH381RM-XXP	57	Threaded flange
3.81	300	8	ECH381RM-XXPL	67	THR
3.81	300	8	ECH381RM-XXPWR	73	
3.81	300	8	ECH381RM-XXPLWR	73	THR
3.81	300	8	ECH381RJ-XXPL	66	THR
3.81	300	8	ECH381RG-XXP	57	
3.81	300	8	ECH381RR-XXP	57	
3.81	300	8	ECH381RR-XXPL	67	THR
3.81	300	8	ECH381RR-XXPWR	73	
3.81	300	8	ECH381RR-XXPLWR	73	THR
3.81	300	8	ECH381RRM-XXP	57	Threaded flange
3.81	300	8	ECH381RRM-XXPL	67	THR
3.81	300	8	ECH381RRM-XXPWR	73	
3.81	300	8	ECH381RRM-XXPLWR	73	THR
3.81	300	8	ECHP381V-XXP	56	Solder/Slip-on connection
3.81	300	8	ECH381V-XXP	56	
3.81	300	8	ECH381V-XXPL	66	THR
3.81	300	8	ECH381V-XXPWR	72	
3.81	300	8	ECH381V-XXPLWR	72	THR
3.81	300	8	ECH381VM-XXP	56	Threaded flange
3.81	300	8	ECH381VM-XXPL	66	THR
3.81	300	8	ECH381VM-XXPWR	72	
3.81	300	8	ECH381VM-XXPLWR	72	THR
3.81	300	8	ECH381VJ-XXPL	66	THR
3.81	300	8	ECHB381R-XXP	62	
3.81	300	8	ECHB381RM-XXP	63	Threaded flange
3.81	300	8	ECHB381RRD-XXP	63	
3.81	300	8	ECHB381RRM-XXP	63	Threaded flange
3.81	300	8	ECHB381V-XXP	62	
3.81	300	8	ECHB381VM-XXP	62	Threaded flange
3.81	300	8	EECH381R-XXP	64	
3.81	300	8	EECH381RM-XXP	65	Threaded flange
3.81	300	8	EECH381V-XXP	64	
3.81	300	8	EECH381VM-XXP	64	Threaded flange
4.00	300	10	0162-11XX	51	
5.00	300	2	0191-12XXTH	32	
5.00	300	7	EDH130F-XX/12.6	50	PIN strip
5.00	300	7	EDH130F-XXTH126	50	PIN strip, THR
5.00	300	10	0226-11XX	14	Threaded flange/light pipe
5.00	300	10	0226-12XX	14	Threaded flange/light pipe
5.00	300	10	0226-16XX	15	
5.00	300	10	0226-16XXL	15	THR
5.00	300	10	0226-17XX	15	
5.00	300	10	0226-17XXL	15	THR
5.00	300	10	0226-21XX	14	Lock flange/light pipe
5.00	300	10	0226-22XX	14	Lock flange/light pipe
5.00	300	10	0226-26XX	15	Lock flange
5.00	300	10	0226-26XXL	15	THR
5.00	300	10	0226-27XX	15	Lock flange
5.00	300	10	0226-27XXL	15	THR
5.00	300	10	0226-31XX	14	Light pipe
5.00	300	10	0226-32XX	14	Light pipe
5.00	300	10	0226-36XX	15	
5.00	300	10	0226-36XXL	15	THR
5.00	300	10	0226-37XX	15	
5.00	300	10	0226-37XXL	15	THR
5.00	300	12	EDH130-21XX	50	PIN strip
5.00	300	12	EDH130-21XXTHT	50	PIN strip, THR
5.00	300	15	0227-11XX	16	Threaded flange/light pipe
5.00	300	15	0227-12XX	16	Threaded flange/light pipe
5.00	300	15	0227-16XX	17	Threaded flange
5.00	300	15	0227-16XXL	17	THR
5.00	300	15	0227-17XX	17	Threaded flange
5.00	300	15	0227-17XXL	17	THR
5.00	300	15	0227-21XX	16	Lock flange/light pipe
5.00	300	15	0227-22XX	16	Lock flange/light pipe
5.00	300	15	0227-26XX	17	Lock flange
5.00	300	15	0227-26XXL	17	THR
5.00	300	15	0227-27XX	17	Lock flange
5.00	300	15	0227-27XXL	17	THR
5.00	300	15	0227-31XX	16	Release tool/light pipe
5.00	300	15	0227-32XX	16	Release tool/light pipe
5.00	300	15	0227-36XX	17	Release tool
5.00	300	15	0227-36XXL	17	THR
5.00	300	15	0227-37XX	17	Release tool
5.00	300	15	0227-37XXL	17	THR
5.00	300	15	5EEHDR-XXP	64	
5.00	300	15	5EEHDRM-XXP	64	Threaded flange
5.00	300	15	5EEHDV-XXP	64	
5.00	300	15	5EEHDVM-XXP	64	Threaded flange
5.00	300	15	5EHDBR-XXP	62	
5.00	300	15	5EHDBRM-XXP	63	Threaded flange
5.00	300	15	5EHDBV-XXP	62	
5.00	300	15	5EHDBVM-XXP	62	Threaded flange

Headers (Sockets) For Pluggable PCB Terminal Blocks

Table of Contents

Headers (Sockets) For Pluggable PCB Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
5.00	300	15	5EHDK-XXP/T	58	Lock flange
5.00	300	15	5EHDKM-XXP/T	59	Threaded flange
5.00	300	15	5EHDKPM-XXP	59	Threaded flange
5.00	300	15	5EHDR-XXP	57	
5.00	300	15	5EHDR-XXPL	69	THR
5.00	300	15	5EHDR-XXPWR	75	
5.00	300	15	5EHDR-XXPLWR	75	THR
5.00	300	15	5EHDRC-XXP	57	
5.00	300	15	5EHDRC-XXPL	69	THR
5.00	300	15	5EHDRC-XXPWR	75	
5.00	300	15	5EHDRC-XXPLWR	75	THR
5.00	300	15	5EHDRM-XXP	57	Threaded flange
5.00	300	15	5EHDRM-XXPL	69	THR
5.00	300	15	5EHDRM-XXPWR	75	
5.00	300	15	5EHDRM-XXPLWR	75	THR
5.00	300	15	5EHDRR-XXP	58	
5.00	300	15	5EHDRR-XXPL	68	THR
5.00	300	15	5EHDRR-XXPWR	74	
5.00	300	15	5EHDRR-XXPLWR	74	THR
5.00	300	15	5EHDRRC-XXP	58	
5.00	300	15	5EHDRRC-XXPL	68	THR
5.00	300	15	5EHDRRC-XXPWR	74	
5.00	300	15	5EHDRRC-XXPLWR	74	THR
5.00	300	15	5EHDRRM-XXPL	68	THR
5.00	300	15	5EHDRRM-XXPLWR	74	THR
5.00	300	15	5EHDV-XXP	56	
5.00	300	15	5EHDV-XXPL	68	THR
5.00	300	15	5EHDV-XXPWR	74	
5.00	300	15	5EHDV-XXPLWR	74	THR
5.00	300	15	5EHDVC-XXP	56	
5.00	300	15	5EHDVC-XXPL	68	THR
5.00	300	15	5EHDVC-XXPWR	74	
5.00	300	15	5EHDVC-XXPLWR	74	THR
5.00	300	15	5EHDVM-XXP	56	Threaded flange
5.00	300	15	5EHDVM-XXPL	68	THR
5.00	300	15	5EHDVM-XXPWR	74	
5.00	300	15	5EHDVM-XXPLWR	74	THR
5.08	300	6	FDCH508R-XXP	43	
5.08	300	6	FDCH508RM-XXP	43	
5.08	300	8	0225-46XX	11	Threaded flange
5.08	300	8	0225-47XX	11	Threaded flange
5.08	300	8	0225-56XX	11	Lock flange
5.08	300	8	0225-57XX	11	Lock flange
5.08	300	8	0225-66XX	11	
5.08	300	8	0225-67XX	11	
5.08	300	8	0225-76XX	11	Release tool
5.08	300	8	0225-77XX	11	Release tool
5.08	300	10	0164-11XX	51	
5.08	300	12	ECH508R-XXP	58	
5.08	300	12	ECH508RM-XXP	59	Threaded flange
5.08	300	12	ECH508V-XXP	58	
5.08	300	12	ECH508VM-XXP	58	Threaded flange
5.08	300	15	2EEHDR-XXP	64	
5.08	300	15	2EEHDRM-XXP	65	Threaded flange
5.08	300	15	2EEHDV-XXP	64	
5.08	300	15	2EEHDVM-XXP	64	Threaded flange
5.08	300	15	2EHDA-XXP	58	
5.08	300	15	2EHDAC-XXP	58	
5.08	300	15	2EHDBR-XXP	62	
5.08	300	15	2EHDBRM-XXP	63	Threaded flange
5.08	300	15	2EHDBV-XXP	62	
5.08	300	15	2EHDBVM-XXP	62	Threaded flange
5.08	300	15	2EHDP-XXP	58	Solder/Slip-on connection
5.08	300	15	2EHDR-XXP	59	
5.08	300	15	2EHDR-XXPL	69	THR
5.08	300	15	2EHDR-XXPWR	75	
5.08	300	15	2EHDR-XXPLWR	75	THR
5.08	300	15	2EHDRC-XXP	59	
5.08	300	15	2EHDRC-XXPL	69	THR
5.08	300	15	2EHDRC-XXPWR	75	
5.08	300	15	2EHDRC-XXPLWR	75	THR
5.08	300	15	2EHDRM-XXP	59	Threaded flange
5.08	300	15	2EHDRM-XXPL	69	THR
5.08	300	15	2EHDRM-XXPWR	75	
5.08	300	15	2EHDRM-XXPLWR	75	THR
5.08	300	15	2EHDRR-XXPL	68	THR
5.08	300	15	2EHDRRC-XXPL	68	THR
5.08	300	15	2EHDRRM-XXPL	68	THR
5.08	300	15	2EHDV-XXP	58	
5.08	300	15	2EHDV-XXPL	68	THR
5.08	300	15	2EHDV-XXPWR	74	
5.08	300	15	2EHDV-XXPLWR	74	THR
5.08	300	15	2EHDVC-XXP	58	
5.08	300	15	2EHDVC-XXPL	68	THR

Headers (Sockets) For Pluggable PCB Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
5.08	300	15	2EHDVC-XXPWR	74	
5.08	300	15	2EHDVC-XXPLWR	74	THR
5.08	300	15	2EHDVM-XXP	58	Threaded flange
5.08	300	15	2EHDVM-XXPL	68	THR
5.08	300	15	2EHDVM-XXPWR	74	
5.08	300	15	2EHDVM-XXPLWR	74	THR
5.08	300	16	0150-26XX	24	
6.35	600	20	0150-36XX	25	
7.50	300	18	0150-46XX	25	
7.50	300	15	7EHDR-XXP	61	
7.50	300	15	7EHDRC-XXP	61	
7.50	300	15	7EHDRM-XXP	61	Threaded flange
7.50	300	15	7EHDV-XXP	60	
7.50	300	15	7EHDVC-XXP	60	
7.50	300	15	7EHDVM-XXP	60	Threaded flange
7.62	300	15	3EHDR-XXP	61	
7.62	300	15	3EHDR-XXPWR	75	
7.62	300	15	3EHDRC-XXP	61	
7.62	300	15	3EHDRC-XXPWR	75	
7.62	300	15	3EHDRRC-XXP	61	
7.62	300	15	3EHDRM-XXP	61	Threaded flange
7.62	300	15	3EHDRM-XXPWR	75	
7.62	300	15	3EHDV-XXP	60	
7.62	300	15	3EHDV-XXPWR	74	
7.62	300	15	3EHDVC-XXP	60	
7.62	300	15	3EHDVC-XXPWR	74	
7.62	300	15	3EHDVM-XXP	60	Threaded flange
7.62	300	15	3EHDVM-XXPWR	74	
7.62	300	25	0183-11XX	47	
7.62	300	25	0183-11XXTXX	47	
7.62	300	30	ECH762R-XXP	61	
7.62	300	30	ECH762RM-XXP	61	Threaded flange
7.62	300	30	ECH762RR-XXP	60	
7.62	300	30	ECH762RRM-XXP	60	Threaded flange
7.62	300	30	ECH762RRT-XXP	60	
7.62	300	30	ECH762RTM-XXP	61	Threaded flange
7.62	300	30	ECH762V-XXP	60	
7.62	300	30	ECH762VM-XXP	60	Threaded flange
7.62	300	30	ECH762VTM-XXP	60	Threaded flange
7.62	600	40	ECH762HR-XXP	61	
7.62	600	40	ECH762HRR-XXP	61	
10.16	300	51	ECH116RM-XXP	48	
10.16	300/600	51/5	ECH116V-XXP	48	
10.16	300/600	51/5	ECH116R-XXP	49	
10.16	300/600	51/5	ECH116L-XXP	48	
10.16	600	51	ECH116HVS-XXP	49	

PID (Push-In Design) PCB Type Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
2.50	150	2	0136-11XX	77	
2.50	150	5	0188-01XXL	76	THR
2.50	150	5	0188-01XXSMD	76	THR
2.50	150	5	0188-02XXL	76	THR
2.50	150	5	0188-02XXSMD	76	THR
2.50	300	2	0136-10XX	77	
2.54	150	5	0138-10XX	77	
2.54	150	5	0138-11XX	77	
2.54	150	5	141V-XXP	77	
2.54	150	5	141R-XXP	77	
3.50	300	5	0137-40XX	78	
3.50	300	5	0137-41XX	78	
3.50	300	6	0136-20XX	77	
3.50	300	6	0136-21XX	77	
3.50	300	9	0151-01XX	78	
3.50	300	9	0151-02XX	78	
3.50	300	10	0151-01XXL	78	THR
3.50	300	10	0151-02XXL	78	THR
3.50	300	10	0177-31XX	82	
3.50	300	10	0177-33XX	82	

Table of Contents

PID (Push-In Design) PCB Type Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
3.50	300	10	0185-11XX	79	
3.50	300	10	0185-12XX	79	
3.50	300	12	0138-50XX	78	
3.50	300	12	0138-50XXL	78	THR
3.50	300	12	0138-51XX	78	
3.50	300	12	0138-51XXL	78	THR
3.81	300	10	0141-01XX	79	
3.81	300	10	0141-22XX	79	
5.00	300	10	0137-11XX	79	
5.00	300	10	0138-70XX	80	
5.00	300	10	0138-76XX	80	
5.00	300	10	0152-01XX	80	
5.00	300	10	0152-02XX	80	
5.00	300	10	0185-31XX	79	
5.00	300	10	0185-32XX	79	
5.00	300	20	0153-01XX	80	
5.00	300	20	0153-02XX	80	
5.00	300	20	0177-51XX	82	
5.00	300	20	0177-53XX	82	
5.08	300	10	0141-21XX	81	
5.08	300	10	0141-24XX	81	
5.08	300	10	142R-XXP	81	
5.08	300	10	142V-XXP	81	
5.08	300	12	0138-60XX	80	
5.08	300	12	0138-60XXL	80	
5.08	300	12	0138-61XX	80	THR
5.08	300	12	0138-61XXL	80	
6.35	600	25	0177-76XX	83	THR
6.35	600	25	0177-78XX	83	
7.50	300	20	0177-51XXP3	83	
7.50	300	20	0177-53XXP3	83	
7.50	600	36	0177-86XX	83	
7.50	600	36	0177-88XX	83	
10.00	300	10	0152-41XX	81	
10.00	600	20	0153-41XX	81	
10.00	600	66	0177-06XX	83	
10.00	600	66	0177-08XX	83	

Screw Connection PCB Type Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
2.54	150	10	EK254V-XXP	84	
3.50	300	10	EK350V-XXP	85	
3.50	300	10	EK350V4L-XXP	85	Double decked
3.81	300	10	EHK381V-XXP	84	
3.81	300	12	EK381V-XXP	85	
3.81	300	12	EK381V3L-XXP	85	Triple decked
3.81	300	12	EK381V4L-XXP	84	Double decked
3.81	300	12	EEK381V-XXP	85	
3.81	300	12	EESK381V-XXP	84	High profile
3.81	300	12	E3K381V-XXP	85	High profile
3.81	300	12	ESK381R-XXP	85	
3.81	300	12	ESK381V-XXP	85	
3.81	300	12	ESK381V4L-XXP	84	Double decked
5.00	300	13.5	ELK500S-XXP	85	Low profile
5.00	300	13.5	ELK500V-XXP	85	Low profile
5.00	300	20	E2HK500V-XXPAM	87	High profile
5.00	300	20	EHK5V3L-XXP	86	
5.00	300	20	EK500A-XXP	86	
5.00	300	20	EK500R-XXP	86	
5.00	300	20	EK500V-XXP	86	
5.00	300	20	EK500V2L-XXP	87	Double decked
5.00	300	20	EK500V3L-XXP	87	Triple decked
5.00	300	20	EK500V4L-XXP	87	
5.00	300	20	EEK500V-XXP	86	
5.00	300	20	E3K500V-XXP	86	High profile
5.00	300	20	EHK500R-XXP	87	
5.00	300	25	EHK5V-XXP	87	
5.00	300	20/26	DT-123RA-XXP	92	
5.00	300	20/26	DT-123VA-XXP	92	
5.08	300	13.5	ELK508S-XXP	87	

Screw Connection PCB Type Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
5.08	300	13.5	ELK508V-XXP	86	
5.08	300	13.5	EELK508V-XXP	86	Double decked
5.08	300	13.5	E2LK508V-XXP	87	
5.08	300	20	EK508A-XXP	86	
5.08	300	20	EK508R-XXP	87	
5.08	300	20	EK508V-XXP	87	
5.08	300	20	EK508V2L-XXP	88	Double decked
5.08	300	20	EK508V3L-XXP	88	Triple decked
5.08	300	20	EK508V4L-XXP	88	Double decked
5.08	300	20	EEK508V-XXP	89	High profile
5.08	300	20	EESK508V-XXP	88	High profile
5.08	300	20	E3K508V-XXP	89	High profile
5.08	300	20	E3SK508V-XXP	89	High profile
5.08	300	20	ESK508V3L-XXP	89	Triple decked
5.08	300	20	ESK508V4L-XXP	89	Double decked
5.08	300	23	ESK508V-XXP	88	
5.08	300	25	E2HK508V-XXPAM	89	High profile
5.08	300	25	EEHK508V-XXP	88	Double decked
5.08	300	25	EHK2V-XXP	88	
5.08	300	25	EHK508R-XXP	88	
5.08	300	25	EHK508V2L-XXP	89	Double decked
5.08	300	25	EHK508V3L-XXP	89	Triple decked
6.35	300	30	DT-2300-XXP	93	
6.35	300	30	DT-2301-XXP	93	
6.35	300	30	EKB635V-XXP	88	Double decked
6.35	300	30	ESK635V-XXP	88	
6.35	600	35	EPK635VN-XXP	89	
7.50	300	25	EHK7V-XXP	90	
7.50	300	20/26	DT-123RA-XXP3	92	
7.50	300	20/26	DT-123VA-XXP3	92	
7.50	600	20	DT-123HVR-XXP	92	
7.50	300/600	30/5	ESK750V-XXP	90	
7.62	300	25	EHK3V-XXP	91	
7.62	300	30	DT-2320-XXP	93	
7.62	300	30	DT-2321-XXP	93	
7.62	300/600	30/5	EKB762V-XXP	91	
7.62	300/600	30/5	ESK762V-XXP	90	
9.52	300/600	30/5	EK950V-XXP	91	
9.52	600	30	EK950HVN-XXP	91	
10.00	300		PDS-10A-XX	93	
10.00	300	65	PDS-10-XX	93	
10.00	300	65	PDS-10S-XXP	93	
10.00	300		PDS-10SA-XX	93	
10.16	300/600	65/5	ESK116R-XXPAM	90	
10.16	300/600	65/5	ESK116V-XXP	90	
10.16	300	65	ESKW116V-XXP	91	
10.16	600	57/65	EPK116VN-XXP	91	
15.00	600	115	ESK150V-XXP	90	
15.00	600	115	ESK150VM-XXP	90	
20.00	600	200	ESK200VM-XXP	91	

Spring Clamp Connection - PCB Type Terminal Blocks

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
2.50	300	4	WKA250A-XXP	94	
2.50	300	4	WKV250A-XXP	95	
2.54	300	4	WKA254A-XXP	95	
2.54	300	4	WKV254A-XXP	95	
5.00	300	10	WKA50B-XXP	94	
5.00	300	10	WKK500-XXP	95	
5.00	300	10	W3K500-XXP	95	
5.00	300	10	W4K500-XXP	95	
5.00	300	15	WKA500-XXP	94	
5.00	300	15	WKA500-XXPL	94	THR
5.00	300	15	WSKA500S-XXP	94	
5.08	300	15	WKA508-XXP	94	
5.08	300	10	WKK508-XXP	95	
5.08	300	10	W3K508-XXP	95	
5.08	300	10	W4K508-XXP	95	
7.50	300	30	WSKA750S-XXP	95	
10.00	300	57	WSKA100-XXP	95	

Table of Contents

PCB Terminal Blocks For Electronic Housing Applications

Pitch (mm)	Voltage (V)	Current (A)	Part number	Page	Remarks
5.00	300	10	5ES-2PL	98	
5.00	300	10	5ES-2PR	99	
5.00	300	10	5ES-3PL	98	
5.00	300	10	5ES-3PR	99	
5.00	300	10	5ES-4PL	98	
5.00	300	10	5ES-4PR	99	
5.00	300	15	5EH-2PL	98	
5.00	300	15	5EH-2PR	99	
5.00	300	15	5EH-3PL	98	
5.00	300	15	5EH-3PR	99	
5.00	300	15	5EH-4PL	98	
5.00	300	15	5EH-4PR	99	
5.00	300	20	0189-204PL	98	
5.00	300	20	0189-204PR	98	
5.08	300	8	0228-21XX	97	
5.08	300	8	0228-22XX	97	
5.08	300	8	0228-23XX	97	
7.50	300	20	7ES-3PL	98	
7.50	300	20	7ES-3PR	98	
9.00	300	8	0171-10XX	97	Light pipe
9.00	300	8	0171-11XX	97	Light pipe
9.00	300	8	0171-60XX	97	
12.50	300	15	0171-20XX	97	Light pipe
12.50	300	15	0171-21XX	97	Light pipe

Panel Feed-through Terminal Blocks

Capacity (mm^2)	Voltage (V)	Current (A)	Part number	Page	Remarks
6	300	30	PPACN-4	100	
6	300	30	PPACNV-4	100	
	300	30	PPACNVH-4	103	
16	300	65	PPACN-10	100	
16	300	65	PPACN-10AS	102	
16	300	65	PPACN-10Z	100	
16	300	65	PPACNV-10	101	
16	300	65	PPACNV-10AS	102	
16	300	65	PPACNV-10Z	101	
25	300	85	PPAC-16AS	102	
25	300	85	PPACV-16AS	102	
	300	115	PPAC-25MAS	101	
	300	115	PPAC-50MAS	101	
25	600	85	PPAC-16	101	
25	600	85	PPACV-16	101	
25	600	85	PPACV-16Z	101	
35	600	115	PPAC-25	101	
35	300/600	100	PPAC-25AS	102	
50	600	150	PPAC-50	101	
50	300/600	150/5	PPAC-50AS	102	
95	300	230	PPAC-95MAS	103	
95	600	230	PPAC-95	102	
95	600	230	PPAC-95M	102	

Connection methods

Screw connection

Spring clamp connection

Push-in design

Front screw connection

Wire protector type

Iron soldering

Wire Ferrules



Unit:mm

Part No.	Wire Range AWG	Wire Range mm^2	Dimension Unit : mm^2 D1	Dimension Unit : mm^2 D2	Dimension Unit : mm L1	Dimension Unit : mm L2	DIN Color	Package pcs/bag	Package bags/box	Tools
DN00206D	24	0.2	0.75	1.9	6	10	Light Blue	1000	10	
DN00208D					8	12				
DN00306D	22	0.34	0.8	1.9	6	10	Turouise			
DN00308D					8	12				
DN00506D	20	0.5	1	2.6	6	12	White	500	8	
DN00508D					8	14				
DN00510D					10	16				
DN00706D	18	0.75	1.2	2.8	6	12	Grey			
DN00708D					8	14				
DN00710D					10	16				
DN00712D					12	18				
DN01006D		1	1.4	3	6	12	Red		6	
DN01008D					8	14				
DN01010D					10	16				
DN01012D					12	18				
DN01508D	16	1.5	1.7	3.5	8	14	Black		4	
DN01510D					10	16				
DN01512D					12	18				
DN01518D					18	24				
DN02508D	14	2.5	2.2	4.2	8	14	Blue		3	
DN02510D					10	16				
DN02512D					12	18				
DN02518D					18	24				
DN04010D	12	4	2.8	4.8	10	17	Grey		2	
DN04012D					12	20				
DN04018D					18	26				
DN06012D	10	6	3.5	6.3	12	20	Yellow		1	
DN06018D					18	26				
DN10012D	7	10	4.5	7.6	12	22	Red	200	1	
DN10018D					18	28				
DN16012D	5	16	5.8	8.8	12	22	Blue			
DN16018D					18	28				
DN25016D	4	25	7.3	11.2	16	30	Yellow	100		
DN25018D					18	30				
DN25022D					22	36				
DN35016D	2	35	8.3	12.7	16	30	Red			
DN35018D					18	32				
DN35025D					25	39				
DN50020D	1	50	10.3	15	20	36	Blue	50		
DN50025D					25	40				
DN70021D	2/0	70	13.5	16	21	37	Yellow	50	1	
DN95025D	3/0	95	14.7	18	25	44	Red			
DN96027D	4/0	120	16.7	20	27	48	Blue	20		
DN97032D	250kcmil	150	19.5	23	32	58	Yellow			

Note:
The wire diameter of the table is determined according to UL486E, IEC998-1 and IEC947-7. Please refer to the table to select suitable ferrules. All recommended ferrules in this catalogue are in accordance with this table.

DNT13-0101
28-7 AWG
0.08-10 mm^2

Wire Ferrules

PID connection plugs & terminal blocks

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
30~20	0156-1AXX-BK	3	8	DN00308D	22	0.34	8
	0156-1BXX-BK	3	8	DN00208D	22	0.25	8
	0156-1CXX-BK	3	8				
	0156-1DXX-BK	3	8				
28~20	0136-10XX	77	8	DN00308D	22	0.34	8
	0136-11XX	77	8	DN00208D	22	0.25	8
	0138-10XX	77	8				
	0138-11XX	77	8				
	ESC250V-XXP	26	8				
28~16	0136-20XX	77	8	DN01008D	/	1	8
	0136-21XX	77	8	DN00708D	18	0.75	8
	0156-2AXX-BK	4	8	DN00508D	20	0.5	8
	0156-2BXX-BK	4	8	DN00308D	22	0.34	8
	0156-2CXX-BK	4	8	DN00208D	24	0.25	8
	0156-2DXX-BK	4	8				
	0191-01XX	32	8				
	0138-50XX	78	9	DN01010D	/	1	10
	0138-50XXL	78	9	DN00710D	18	0.75	10
	0138-51XX	82	9	DN00510D	20	0.5	10
	0138-51XXL	82	9				
	0141-01XX	79	9				
	0141-21XX	81	9				
	0141-22XX	79	9				
	0141-24XX	81	9				
28~16	0152-01XX	80	9				
	0152-02XX	80	9				
	0225-01XX	12	9				
	0225-02XX	12	9				
	0225-03XX	12	9				
	0225-04XX	11	9				
	0225-05XX	11	9				
	0225-06XX	11	9				
	0225-07XX	13	9				
	0225-08XX	13	9				
	0225-09XX	11	9				
	0225-0AXX	11	9				
	ESC508V-XXP	28	9				
	ESC508VM-XXP	29	9				

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
28~16	0151-02XX	78	10	DN00510D	20	0.5	10
	141R-XXP	77	10	DN01012D	/	1	12
	141V-XXP	77	10	DN00712D	18	0.75	12
26~14	0138-70XX	80	10	DN01510D	16	1.5	10
				DN01010D	/	1	10
				DN00710D	18	0.75	10
				DN00510D	20	0.5	10
	0177-51XX	82	10	DN02510D	14	2.5	10
	0177-53XX	82	10	DN01510D	16	1.5	10
				DN01010D	/	1	10
				DN00710D	18	0.75	10
				DN00510D	20	0.5	10
	2ESR-XXP	20	11	DN02512D	14	2.5	12
	2ESRK-XXP	20	11	DN01512D	16	1.5	12
	2ESRM-XXP	20	11	DN01012D	/	1	12
	2ESV-XXP	20	11	DN00712D	18	0.75	12
	3ESDSR-XXP	30	11				
	3ESDSRM-XXP	30	11				
	5ESR-XXP	18	11				
	5ESRK-XXP	18	11				
	5ESRM-XXP	18	11				
26~12	5ESV-XXP	18	11				
	5ESVK-XXP	18	11				
	5ESVM-XXP	18	11				
	5ESDS-XXP	28	12	DN02512D	14	2.5	12
	5ESDSM-XXP	29	12	DN01512D	16	1.5	12
	5ESDSR-XXP	28	12	DN01012D	/	1	12
	5ESDSRM-XXP	29	12	DN00712D	18	0.75	12
	2ESDS-XXP	28	12				
	2ESDSM-XXP	29	12				
	2ESDSR-XXP	28	12				
	2ESDSRM-XXP	29	12				
	2ESDSV-XXP	18	13	DN02512D	14	2.5	12
	2ESDSVK-XXP	19	13	DN01512D	16	1.5	12
	2ESDSVM-XXP	19	13	DN01012D	/	1	12
				DN00712D	18	0.75	12
24~20	0137-40XX	78	9	DN00308D	22	0.34	8
	0137-41XX	79	9	DN00208D	24	0.25	8

PID connection plugs & terminal blocks

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
24~16	0221-20XX	6	9	DN01010D	/	1	10
	0221-28XX	7	9	DN00710D	18	0.75	10
	0221-42XX	8	9	DN00510D	20	0.5	10
	0221-43XX	8	9				
	0226-01XX	14	9				
	0226-02XX	14	9				
	0226-03XX	14	9				
	0226-06XX	15	9				
	0226-07XX	15	9				
	0226-08XX	15	9				
	0159-01XX	5	10	DN01010D	/	1	10
	0159-03XX	5	10	DN00710D	18	0.75	10
	0159-04XX	5	10	DN00510D	20	0.5	10
	0181-A1XX	22	10				
	0181-A3XX	22	10				
	0177-31XX	82	10				
	0177-33XX	82	10				
	0150-20XX	24	11	DN04012D	12	4	12
	0150-30XX	25	11	DN02512D	14	2.5	12
	2ESS-XXP	20	11	DN01512D	16	1.5	12
	2ESSM-XXP	20	11	DN01012D	/	1	12
				DN00712D	18	0.75	12
	2ESDB-XXP	28	12	DN02512D	14	2.5	12
	2ESDBM-XXP	29	12	DN01512D	16	1.5	12
	2ESDBA-XXP	28	12	DN01012D	/	1	12
	2ESDBAM-XXP	29	12	DN00712D	18	0.75	12
24~12	0161-01XX	23	13	DN02512D	14	2.5	12
	0161-02XX	23	13	DN01512D	16	1.5	12
	0161-03XX	23	13	DN01012D	/	1	12
	0161-04XX	23	13	DN00712D	18	0.75	12
	0161-11XX	23	13				
	0161-12XX	23	13				
	0161-13XX	23	13				
	0161-14XX	23	13				
	0227-01XX	16	13				
	0227-02XX	16	13				
	0227-03XX	16	13				
	0227-04XX	16	13				
	0153-01XX	80	14	DN02512D	14	2.5	12
	0153-02XX	80	14	DN01512D	16	1.5	12
	0227-06XX	17	13	DN01012D	/	1	12
	0227-07XX	17	13	DN00712D	18	0.75	12
	0227-08XX	17	13				
	0227-09XX	17	13				

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
24~10	0177-76XX	83	13	DN04012D	12	4	12
	0177-78XX	83	13	DN02512D	14	2.5	12
				DN01512D	16	1.5	12
				DN01012D	/	1	12
				DN00712D	18	0.75	12
24~8	0177-86XX	83	15	DN06018D	10	6	18
	0177-88XX	83	15	DN04018D	12	4	18
				DN02518D	14	2.5	18
				DN01518D	16	1.5	18
22~14	142V-XXP	81	9	DN01510D	16	1.5	10
	141R-XXP	81	9	DN01010D	/	1	10
				DN00710D	18	0.75	10
				DN00510D	20	0.5	10
20~4	0177-06XX	83	20	DN10018D	7	10	18
	0177-08XX	83	20	DN06018D	10	6	18
				DN04018D	12	4	18
				DN02518D	14	2.5	18
				DN01518D	16	1.5	18

Spring Clamp Connection Terminal Blocks

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
28~20	WKA250A-XXP	94	6	DN00306D	22	0.34	6
	WKA254A-XXP	95	6	DN00206D	24	0.25	6
	WKV250A-XXP	95	6				
	WKV250A-XXP	95	6				
28~12	WKA500-XXP	94	6	DN01006D	/	1	6
	WKA508-XXP	94	6	DN00706D	18	0.75	6
				DN00506D	20	0.5	6
				DN00306D	22	0.34	6
				DN00206D	24	0.25	6
	WKK500-XXP	95	7	DN02508D	14	2.5	8
	WKK508-XXP	95	7	DN01508D	16	1.5	8
	W4K500-XXP	95	7	DN01008D	18	1	8
	W4K508-XXP	95	7	DN00708D	/	0.75	8
	W3K500-XXP	95	7	DN00508D	20	0.5	8
	W3K508-XXP	95	7	DN00308D	22	0.34	8
				DN00208D	24	0.25	8
	WSKA500S-XXP	95	11	DN02512D	14	2.5	12
				DN01512D	16	1.5	12
				DN01012D	/	1	12
				DN00712D	18	0.75	8

Wire Ferrules

Spring Clamp Connection Terminal Blocks

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
24~16	WKA50B-XXP	94	10	DN01010D	/	1	10
				DN00710D	18	0.75	10
				DN00510D	20	0.5	10
24~6	WSKA100-XXP	95	15	DN10018D	7	10	18
				DN06018D	10	6	18
				DN04018D	12	4	18
				DN02518D	14	2.5	18
				DN01518D	16	1.5	18

Screw Connection Plug

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
30~14	ECSH381V-XXP	52	7	DN01508D	16	1.5	8
				DN01008D	/	1	8
				DN00708D	18	0.75	8
				DN00508D	20	0.5	8
				DN00308D	22	0.34	8
				DN00208D	24	0.25	8
	EC381F-XXP	35	8	DN01508D	16	1.5	8
	EC381FM-XXP	35	8	DN01008D	/	1	8
				DN00708D	18	0.75	8
				DN00508D	20	0.5	8
				DN00308D	22	0.34	8
				DN00208D	24	0.25	8
	EC350F-XXP	35	9	DN01510D	18	0.75	8
	EC350FM-XXP	35	9	DN01010D	20	0.5	8
	EC508V-XXP	36	9	DN00710D	22	0.34	8
	EC508VM-XXP	36	9	DN00510D	24	0.25	8
30~12	2ESDVB-XXP	40	7	DN02508D	14	2.5	8
	2ESDVBM-XXP	40	7	DN01508D	16	1.5	8
	2ESDL-XXP	40	7	DN01008D	/	1	8
	2ESDPL-XXP	40	7	DN00708D	18	0.75	8
	2ESDPLM-XXP	40	7	DN00508D	20	0.5	8
	2ESDP-XXP	39	7	DN00308D	22	0.34	8
	2ESDPM-XXP	39	7	DN00208D	24	0.25	8
	2ESDV-XXP	39	8	DN02508D	14	2.5	8
	2ESDVM-XXP	39	8	DN01508D	16	1.5	8
	3ESDPL-XXP	42	8	DN01008D	/	1	8
	3ESDPLM-XXP	42	8	DN00708D	18	0.75	8
	3ESDP-XXP	42	8	DN00508D	20	0.5	8
	3ESDPM-XXP	42	8	DN00308D	22	0.34	8
	3ESDV-XXP	42	8	DN00208D	24	0.25	8
	3ESDVM-XXP	42	8				

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
	5ESDA-XXP	37	8	DN02508D	14	2.5	8
	5ESDAM-XXP	37	8	DN01508D	16	1.5	8
	5ESDPL-XXP	38	8	DN01008D	/	1	8
	5ESDPLM-XXP	38	8	DN00708D	18	0.75	8
	5ESDP-XXP	37	8	DN00508D	20	0.5	8
	5ESDPM-XXP	38	8	DN00308D	22	0.34	8
	5ESDT-XXP	38	8	DN00208D	24	2.5	8
	5ESDV-XXP	38	8				
30~12	5ESDVM-XXP	38	8				
	7ES-3PL	98	8				
	7ES-3PR	98	8				
	7ESDPL-XXP	41	8				
	7ESDPLM-XXP	41	8				
	7ESDP-XXP	41	8				
	7ESDPM-XXP	41	8				
	7ESDV-XXP	41	8				
	7ESDVM-XXP	41	8				
	EC762V-XXP	46	8	DN02508D	14	2.5	8
	EC762VM-XXP	47	8	DN01508D	16	1.5	8
	EC762VN-XXP	46	8	DN01008D	/	1	8
30~10	EC762VNM-XXP	47	8	DN00708D	18	0.75	8
				DN00508D	20	0.5	8
				DN00308D	22	0.34	8
				DN00208D	24	0.25	8
	EC762HV-XXP	46	8	DN02508D	14	2.5	8
	EC762HVM-XXP	47	8	DN01508D	16	1.5	8
	EC762HVN-XXP	46	8	DN01008D	/	1	8
30~8	EC762HVNM-XXP	47	8	DN00708D	18	0.75	8
				DN00508D	20	0.34	8
				DN00308D	22	0.25	8
				DN00208D	24	1	8

Screw Connection Plug

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
28~14	EC350V-XXP	34	7	DN01508D	16	1.5	8
	EC350VM-XXP	34	7	DN01008D	/	1	8
	EC350R-XXP	34	7	DN00708D	18	0.75	8
	EC350RM-XXP	34	7	DN00508D	20	0.5	8
	EC350RL-XXP	34	7	DN00308D	22	0.34	8
	EC350RLM-XXP	34	7	DN00208D	24	0.25	8
28~14	EC381V-XXP	34	8	DN01508D	22	0.34	8
	EC381VK-XXP	34	8	DN01008D	22	0.25	8
	EC381VM-XXP	34	8	DN00708D	22	0.25	8
	EC381R-XXP	34	8	DN00508D	22	0.25	8
	EC381RM-XXP	34	8	DN00308D	22	0.34	8
	EC381RL-XXP	34	8	DN00208D	22	0.25	8
	EC381RLM-XXP	34	8				
	EC508F-XXP	36	9	DN01510D	22	0.34	8
	EC508FM-XXP	36	9	DN01010D	22	0.25	8
				DN00710D	/	1	8
				DN00510D	18	0.75	8
				DN00508D	20	0.5	8
				DN00308D	22	0.34	8
				DN00208D	24	0.25	8
28~12	3ESNP-XXP	45	8	DN02508D	/	1	10
	3ESNPS-XXP	45	8	DN01508D	18	0.75	10
	3ESNPSM-XXP	45	8	DN01008D	20	0.5	10
	3ESNPM-XXP	46	8	DN00708D	/	1	10
	3ESNPL-XXP	45	8	DN00508D	18	0.75	10
	3ESNPLM-XXP	46	8	DN00308D	20	0.5	10
	3ESNPLS-XXP	45	8	DN00208D	/	1	10
	3ESNPLSM-XXP	46	8				

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
28~12	5ESDF-XXP	37	10	DN02510D	14	2.5	10
	5ESDFM-XXP	37	10	DN01510D	16	1.5	10
	2ESDF-XXP	39	10	DN01010D	/	1	10
	2ESDFM-XXP	39	10	DN00710D	18	0.75	10
				DN00510D	20	0.5	10
22~14	5ES-2PL	98	8	DN01508D	16	1.5	8
	5ES-2PR	99	8	DN01008D	/	1	8
	5ES-3PL	98	8	DN00708D	18	0.75	8
	5ES-3PR	99	8	DN00508D	20	0.5	8
	5ES-4PL	98	8	DN00308D	22	0.34	8
	5ES-4PR	99	8	DN00208D	24	0.25	8
16~6	EC116V-XXP	48	15	DN10018D	16	1.5	8
				DN06018D	/	1	8
				DN04018D	18	0.75	8
				DN02518D	20	0.5	8
				DN01518D	22	0.34	8
				DN01010D	/	1	10
				DN00710D	18	0.75	10
				DN00510D	20	0.5	10

Screw Connection Terminal Blocks

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
30~16	EK381V3L-XXP	85	5	DN01006D	/	1	6
	E3K381V-XXP	85	6	DN00706D	18	0.75	6
	ELK508V-XXP	86	6	DN00506D	20	0.5	6
				DN00306D	22	0.34	6
				DN00206D	24	0.25	6
	EK350V-XXP	85	7	DN01008D	/	1	8
	EK350V4L-XXP	85	7	DN00708D	18	0.75	8
	EK381V-XXP	85	7	DN00508D	20	0.5	8
	EEK381V-XXP	85	7	DN00308D	22	0.34	8
	EK381V4L-XXP	84	7	DN00208D	24	0.25	8
	ELK500V-XXP	85	7				

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
30~14	ELK500S-XXP	85	6	DN01006D	/	1	6
	E2LK508V-XXP	87	6	DN00706D	18	0.75	6
	ELK508S-XXP	87	6	DN00506D	20	0.5	6
				DN00306D	22	0.34	6
				DN00206D	24	0.25	6
	EESK381V-XXP	84	7	DN01508D	16	1.5	8
	ESK381R-XXP	85	7	DN01008D	/	1	8
	ESK381V-XXP	85	7	DN00708D	18	0.75	8
	ESK381V4L-XXP	84	7	DN00508D	20	0.5	8
				DN00308D	22	0.34	8
				DN00208D	24	0.25	8

Wire Ferrules

Screw Connection Terminal Blocks

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
30~10	EKB635V-XXP	88	8	DN04012D	12	4	12
				DN02512D	14	2.5	12
				DN01512D	16	1.5	12
				DN01012D	/	1	12
				DN00712D	18	0.75	12
28~16	EK254V-XXP	84	6	DN01006D	/	1	8
				DN00706D	18	0.75	6
				DN00506D	20	0.5	6
				DN00306D	22	0.34	6
				DN00206D	24	0.25	6
	0171-10XX	97	8	DN01008D	/	1	8
	0171-11XX	97	8	DN00708D	18	0.75	8
	0171-60XX	97	8	DN00508D	20	0.5	8
				DN00308D	22	0.34	8
				DN00208D	24	0.25	8
	0228-21XX	97	9	DN01010D	/	1	10
	0228-22XX	97	9	DN00710D	18	0.75	10
	0228-23XX	97	9	DN00510D	20	0.5	10
28~14	CPC350-XXP	52	8	DN01508D	16	1.5	10
				DN01008D	/	1	8
				DN00708D	18	0.75	8
				DN00508D	20	0.5	8
				DN00308D	22	0.34	8
				DN00208D	24	0.25	8
28~12	5ESDG-XXP	52	8	DN02508D	14	2.5	8
				DN01508D	16	1.5	8
				DN01008D	/	1	8
				DN00708D	18	0.75	8
				DN00508D	20	0.5	8
				DN00308D	22	0.34	8
				DN00208D	24	0.25	8
26~18	EELK508V-XXP	86	7	DN00508D	20	0.5	8
				DN00308D	22	0.34	8
				DN00208D	24	0.25	8
26~16	EHK381V-XXP	84	7	DN00108D	/	1	8
				DN00708D	18	0.75	8
				DN00508D	20	0.5	8
				DN00308D	22	0.34	8
				DN00208D	24	0.25	8
26~12	E3SK508V-XXP	89	9	DN02510D	14	2.5	10
	EESK508V-XXP	88	9	DN01510D	16	1.5	10
	ESK508V3L-XXP	89	9	DN01010D	/	1	10
	ESK508V4L-XXP	89	9	DN00710D	18	0.75	10
				DN00510D	20	0.5	10
26~12	ESK508V-XXP	88	11	DN02512D	14	2.5	12
				DN01512D	16	1.5	12
				DN01012D	/	1	12
				DN00712D	18	0.75	12
26~10	EK950V-XXP	91	7	DN02508D	14	2.5	8
	EK950HVN-XXP	91	8	DN01508D	16	1.5	8
				DN01008D	/	1	8
				DN00708D	18	0.75	8
				DN00508D	20	0.5	8
				DN00308D	22	0.34	8
				DN00208D	24	0.25	8
	ESK635V-XXP	88	11	DN04012D	12	4	12
				DN02512D	14	2.5	12
				DN01512D	16	1.5	12
				DN01012D	/	1	12
				DN00712D	18	0.75	12
	E2HK500V-XXPAM	87	7	DN02508D	14	2.5	8
	E2HK508V-XXPAM	89	7	DN01508D	16	1.5	8
	E3K500V-XXP	86	7	DN01008D	/	1	8
	E3K508V-XXP	89	7	DN00708D	18	10.75	8
	EEK500V-XXP	86	7	DN00508D	20	0.5	8
	EEK508V-XXP	89	7	DN00308D	22	0.34	8
	EHK500R-XXP	87	7	DN00208D	24	0.25	8
24~12	EHK508V2L-XXP	89	7				
	EHK508V3L-XXP	89	7				
	EK508R-XXP	87	7				
	EK500V2L-XXP	88	7				
	EK500V3L-XXP	88	7				
	EL500V4L-XXP	88	7				
	EK508R-XXP	87	7				
	EK508V2L-XXP	88	7				
	EK508V3L-XXP	88	7				
	EK508V4L-XXP	88	7				
	EK508V-XXP	87	7				

Screw Connection Terminal Blocks

Wire range	Terminal blocks	Page	Strip length	Applicable Ferrules			
AWG			mm	Ferrule P/N	AWG	mm²	L1
30~10	EKB635V-XXP	88	8	DN02508D	14	2.5	8
	EHK2V-XXP	88	8	DN01508D	16	1.5	8
	EHK3V-XXP	91	8	DN01008D	/	1	8
	EHK508R-XXP	88	8	DN00708D	18	0.75	8
	EHK5V-XXP	87	8	DN00508D	20	0.5	8
	EHK7V-XXP	90	8	DN00308D	22	0.34	8
	EK508A-XXP	86	8	DN00208D	24	0.25	8
	0171-20XX	97	10	DN02510D	14	2.5	10
	0171-21XX	97	10	DN01510D	16	1.5	10
				DN01010D	/	1	10
				DN00710D	18	10.75	10
				DN00510D	20	0.5	10
24~10	ESK750V-XP	90	11	DN04012D	12	4	12
	EKB762V-XXP	91	11	DN02512D	14	2.5	12
	ESK762V-XXP	90	11	DN01512D	16	1.5	12
				DN01012D	/	1	12
				DN00712D	18	0.75	12
24~6	PDS-10-XX	93	13	DN06012D	10	6	12
	PDS-10A-XX	93	13	DN04012D	12	4	12
	PDS-10S-XXP	93	13	DN02511D	14	2.5	12
	PDS-10SA-XX	93	13	DN01512D	16	1.5	12
				DN01012D	/	1	12
				DN00712D	18	0.75	12
22~14	ED130F-XXP	50	6	DN01006D	/	1	6
	ED130R-XXP	50	6	DN00706D	18	0.75	6
				DN00506D	20	0.5	6
				DN00306D	22	0.34	6
				DN00206D	24	0.25	6
22~12	DT-123RA-XXP	92	14	DN02512F	14	2.5	12
	DT-123VA-XXP	92	14	DN01512D	16	1.5	12
	DT-123RA-XXP3	92	14	DN01012D	/	1	12
	DT-123VA-XXP3	92	14	DN00712D	18	0.75	12
	DT-123HVR-XXP	92	14				
22~10	DT-2300-XXP	93	14	DN04011D	12	4	12
	DT-2301-XXP	93	14	DN02512D	14	2.5	12
	DT-2320-XXP	93	14	DN01512D	16	1.5	12
	DT-2321-XXP	93	14	DN01012D	/	1	12
				DN00712D	18	0.75	12
22~6	ESKW116V-XXP	91	12	DN10012D	7	10	12
				DN06012D	10	6	12
				DN04012D	12	4	12
				DN02512D	14	2.5	12
				DN01512D	16	1.5	12
				DN01012D	/	1	12
				DN00712D	18	0.75	12
20~6	EPK116VN-XXP	91	12	DN10012D	7	10	12
	ESK116R-XXPAM	90	12	DN06012D	10	6	12
				DN04012D	12	4	12
				DN02512D	14	2.5	12
				DN01512D	16	1.5	12
				DN01012D	/	1	12
				DN00712D	18	0.75	12
20~2	ESK116V-XXP	90	11	DN10012D	7	10	12
				DN06012D	10	6	12
				DN04012D	12	4	12
				DN02512D	14	2.5	12
				DN01512D	16	1.5	12
				DN01012D	/	1	12
				DN00712D	18	0.75	12
18~8	EPK635VN-XXP	89	10	DN04010D	12	4	10
				DN02510D	14	2.5	10
				DN01510D	16	1.5	10
				DN01010D	/	1	10
				DN00710D	18	0.75	10

PID (Push-In Design) Plug - Pluggable PCB Terminal Blocks

Connection method: Push-in connection
Pitch: 2.54mm / 3.50mm
UL Rated: 150V / 5A, 150V / 8A
IEC Rated: 320V / 6A, 320V / 10A, 250V / 8A

- Vertical and parallel plug-in directions to PCB are available.
- Compact double-level plug for high connection density.
- Type of locking includes screw flange, lock flange and release tool.
- THR version socket is available, pin length 2.6mm.
 (The last suffix “L” represents THR version.)

2.54mm

Technical Data	UL	IEC
Rated voltage	150V	320V
Rated current	5A	6A
Solid (AWG/mm²)	30~20	0.2~0.5
Flexible (AWG/mm²)	30~20	0.2~0.5
Rated impulse voltage	2.5KV	
Torque(N-m)		
Wire strip length	7~8mm	
Number of Positions		
0156-1AXX-BK	04~44P	
0156-1BXX-BK	06~44P	
0156-1CXX-BK	06~44P	
0156-1DXX-BK	06~44P	

0156-1AXX-BK



0156-1BXX-BK



0156-1CXX-BK



0156-1DXX-BK



2.54mm

Technical Data	UL	IEC
Rated voltage	150V	320V
Rated current	5A	6A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0156-10XX	06~44P	
0156-10XXL	06~44P	
0156-12XX	06~44P	
0156-12XXL	06~44P	
0156-13XX	04~44P	
0156-13XXL	04~44P	
0156-15XX	06~44P	
0156-15XXL	06~44P	
0156-16XX	06~44P	
0156-16XXL	06~44P	
0156-17XX	06~44P	
0156-17XXL	06~44P	
0156-18XX	04~44P	
0156-18XXL	04~44P	
0156-19XX	06~44P	
0156-19XXL	06~44P	

For THR products,
Surge voltage category/pollution degree
III/2 II/2

Rated voltage
160 160

0156-17XX (0156-17XXL)



0156-18XX (0156-18XXL)

with support pins



0156-15XX (0156-15XXL)



0156-19XX (0156-19XXL)



0156-12XX (0156-12XXL)



0156-13XX (0156-13XXL)

with support pins



0156-10XX (0156-10XXL)



0156-16XX (0156-16XXL)



3.50mm

Technical Data	UL	IEC
Rated voltage	150V	320V
Rated current	8A	10A
Solid (AWG/mm²)	28~16	0.2~1.0
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		2.5KV
Torque(N-m)		
Wire strip length	7~8mm	
Number of Positions		
0156-2AXX-BK	04~40P	
0156-2BXX-BK	04~40P	
0156-2CXX-BK	04~40P	
0156-2DXX-BK	04~40P	

0156-2AXX-BK



0156-2BXX-BK





0156-2CXX-BK



0156-2DXX-BK



3.50mm

Technical Data	UL	IEC
Rated voltage	150V	320V
Rated current	8A	10A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque(N-m)		
Wire strip length		
Number of Positions		
0156-20XX-BK	04~44P	
0156-20XXL	04~44P	
0156-21XX-BK	04~40P	
0156-21XXL	04~40P	
0156-24XX-BK	04~44P	
0156-24XXL	04~44P	
0156-25XX-BK	04~44P	
0156-25XXL	04~44P	
0156-26XX-BK	04~40P	
0156-26XXL	04~40P	
0156-29XX-BK	04~40P	
0156-29XXL	04~40P	

0156-26XX-BK (0156-26XXL)



0156-25XX-BK (0156-25XXL)

0156-25XX-BK



0156-29XX-BK (0156-29XXL)



0156-21XX-BK (0156-21XXL)



0156-20XX-BK (0156-20XXL)



0156-24XX-BK (0156-24XXL)



3.50mm

Technical Data	UL	IEC
Rated voltage	150V	250V
Rated current	8A	8A
Solid (AWG/mm²)	24~16	0.2~1.5
Flexible (AWG/mm²)	24~16	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	9~10mm	
Number of Positions		
0159-01XX	04~40P	
0159-03XX	04~40P	
0159-04XX	04~40P	

0159-01XX



0159-03XX



0159K1L

Keycode

0159-04XX



3.50mm

Technical Data	UL	IEC
Rated voltage	150V	250V
Rated current	8A	8A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0159-11XX	04~40P	
0159-11XXL	04~40P	
0159-12XX	04~40P	
0159-12XXL	04~40P	
0159-31XX	04~40P	
0159-31XXL	04~40P	
0159-32XX	04~40P	
0159-32XXL	04~40P	

0159-11XX (0159-11XXL)



0159-31XX (0159-31XXL)



0159-12XX (0159-12XXL)



0159-32XX (0159-32XXL)



Connection method: Push-in connection

Pitch: 3.50mm / 3.81mm

UL Rated: 300V / 8A

IEC Rated: 320V / 8A

- Push-in connection single-level plug, single, double and triple level socket.

- Space saving flat design plug, only 7.7mm in height.

- With testing hole suitable for 1mm Ø test probe.

- The pin length for wave soldering socket is 3.50mm

- THR version socket is available, pin length 2.6mm. (The last suffix "L" represents THR version.)

3.50mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	8A
Solid (AWG/mm²)	24~16	0.2~1.5
Flexible (AWG/mm²)	24~16	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
0221-20XX	8~9mm	
0221-21XX	9~10mm	
0221-24XX	9~10mm	
0221-28XX	8~9mm	
Number of Positions		
0221-20XX	02~20P	
0221-21XX	02~18P	
0221-24XX	02~20P	
0221-28XX	02~20P	

0221-20XX



0221-21XX



0221-24XX



0221-28XX



3.50mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	8A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0221-22XX-BK	04~48P	
0221-22XXL	04~48P	
0221-23XXL	04~48P	
0221-25XX-BK	06~72P	
0221-25XXL	06~72P	
0221-26XXL	04~48P	
0221-27XX-BK	06~72P	
0221-27XXL	06~72P	
0221-35XXL	04~48P	
0221-36XXL	04~48P	
0221-41XX-BK	06~72P	
0221-41XXL	06~72P	
Accessories		
ECHK1	P38	
ECHK1L	P38	

0221-22XX-BK (0221-22XXL)



0221-23XXL



0221-26XXL



0221-35XXL



0221-25XX-BK (0221-25XXL)



0221-41XX-BK (0221-41XXL)



0221-27XX-BK (0221-27XXL)



0221-36XXL



Socket

ECH350H-XXP	P57
ECH350R-XXP	P56
ECH350R-XXPL	P67
ECH350V-XXP	P56
ECH350V-XXPL	P66

Please refer to the related page number for the compatible headers.

Socket

ECH350RJ-XXPL	P67
ECH350VJ-XXPL	P67

Please refer to the related page number for the compatible headers.

Socket

ECH350VT-XXPL	P67

Please refer to the related page number for the compatible headers.

Socket

ECH350RM-XXP	P57
ECH350RM-XXPL	P66
ECH350VM-XXP	P56
ECH350VM-XXPL	P67

Please refer to the related page number for the compatible headers.

Socket

3.81mm

0221-42XX

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	8A
Solid (AWG/mm²)	24~16	0.2~1.5
Flexible (AWG/mm²)	24~16	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
0221-42XX	8~9mm	
0221-43XX	8~9mm	
0221-44XX	8~10mm	
Number of Positions		
0221-42XX	02~20P	
0221-43XX	02~20P	
0221-44XX	02~24P	



0221-43XX



0221-44XX



3.81mm

0221-33XX-BK (0221-33XXL)

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	8A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0221-33XX-BK	04~48P	
0221-33XXL	04~48P	
0221-39XX-BK	04~48P	
0221-39XXL	04~48P	
0221-51XX-BK	04~48P	
0221-51XXL	04~48P	
0221-52XX-BK	04~48P	
0221-52XXL	04~48P	
Accessories		
ECHK1	P38	
ECHK1L	P38	



0221-51XX-BK (0221-51XXL)



0221-39XX-BK (0221-39XXL)



0221-52XX-BK (0221-52XXL)



Socket

ECH381A-XXP	P56
ECH381H-XXP	P57
ECH381R-XXP	P56
ECH381R-XXPL	P67
ECH381V-XXP	P56
ECH381V-XXPL	P66

Please refer to the related page number for the compatible headers.

Socket

ECH381AM-XXP	P56
ECH381RM-XXP	P57
ECH381RM-XXPL	P67
ECH381VM-XXP	P56
ECH381VM-XXPL	P66

Please refer to the related page number for the compatible headers.

Socket

ECH381RJ-XXPL	P66
ECH381VJ-XXPL	P66

Please refer to the related page number for the compatible headers.

DINKLE Memo

PID Pluggable Terminal Blocks - Slim Type

Connection method: Push-in connection
Pitch: 3.50mm / 5.00mm / 5.08mm
UL Rated: 300V / 8A ~ 300V / 15A
IEC Rated: 320V / 14A ~ 600V / 18A

- Double-level plug and socket.
- Options with LED light pipe for indication.
- Versions with screw flange and lock flange.
- THR version socket is available, pin length 2.6mm.

5.08mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0225-04XX	04~40P	
0225-05XX	04~40P	
0225-09XX	04~40P	
0225-0AXX	04~40P	

0225-04XX



0225-05XX



0225-09XX



0225-0AXX



5.08mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0225-46XX	04~40P	
0225-47XX	04~40P	
0225-56XX	04~40P	
0225-57XX	04~40P	
0225-66XX	04~40P	
0225-67XX	04~40P	
0225-76XX	04~40P	
0225-77XX	04~40P	

0225-46XX



0225-56XX



0225-66XX



0225-76XX



0225-47XX



0225-57XX



0225-67XX



0225-77XX



3.50mm 0225-01XX

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	8A	15A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0225-01XX	02~14P	
0225-02XX	02~14P	
0225-03XX	02~14P	

• The product integrates light pipe for better indication



3.50mm 0225-02XX



3.50mm 0225-03XX



3.50mm 0225-11XX

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	8A	15A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0225-11XX	02~14P	
0225-12XX	02~14P	
0225-21XX	02~14P	
0225-22XX	02~14P	
0225-31XX	02~14P	
0225-32XX	02~14P	

• The product integrates light pipe for better indication



3.50mm 0225-21XX



3.50mm 0225-31XX



3.50mm 0225-12XX



3.50mm 0225-22XX





3.50mm 0225-32XX





3.50mm 0225-06XX

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	8A	15A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0225-06XX	02~14P	
0225-07XX	02~14P	
0225-08XX	02~14P	



3.50mm 0225-07XX



3.50mm 0225-08XX



3.50mm 0225-16XX (0225-16XXL)

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	8A	15A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0225-16XX	02~14P	
0225-16XXL	02~14P	
0225-17XX	02~24P	
0225-17XXL	02~24P	
0225-26XX	02~14P	
0225-26XXL	02~14P	
0225-27XX	02~14P	
0225-27XXL	02~14P	
0225-36XX	02~14P	
0225-36XXL	02~14P	
0225-37XX	02~14P	
0225-37XXL	02~14P	

with support pins



3.50mm 0225-26XX (0225-26XXL)



3.50mm 0225-36XX (0225-36XXL)



3.50mm 0225-17XX (0225-17XXL)

with support pins



3.50mm 0225-27XX (0225-27XXL)



3.50mm 0225-37XX (0225-37XXL)



5.00mm

0226-01XX

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	10A	17.5A
Solid (AWG/mm²)	24~16	0.2~1.5
Flexible (AWG/mm²)	24~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0226-01XX	02~16P	
0226-02XX	02~16P	
0226-03XX	02~16P	

- The product integrates light pipe for better indication



0226-02XX



0226-03XX



5.00mm

0226-11XX

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	10A	17.5A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0226-11XX	02~16P	
0226-12XX	02~16P	
0226-21XX	02~16P	
0226-22XX	02~16P	
0226-31XX	02~16P	
0226-32XX	02~16P	

- The product integrates light pipe for better indication



0226-21XX



0226-31XX



0226-12XX



0226-22XX



0226-32XX



5.00mm

0226-06XX

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	10A	17.5A
Solid (AWG/mm²)	24~16	0.2~1.5
Flexible (AWG/mm²)	24~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0226-06XX	02~16P	
0226-07XX	02~16P	
0226-08XX	02~16P	



0226-07XX



0226-08XX



5.00mm

0226-16XX (0226-16XXL)

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	10A	17.5A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0226-16XX	02~16P	
0226-16XXL	02~16P	
0226-17XX	02~16P	
0226-17XXL	02~16P	
0226-26XX	02~16P	
0226-26XXL	02~16P	
0226-27XX	02~16P	
0226-27XXL	02~16P	
0226-36XX	02~16P	
0226-36XXL	02~16P	
0226-37XX	02~16P	
0226-37XXL	02~16P	



0226-17XX (0226-17XXL)



0226-26XX (0226-26XXL)



0226-27XX (0226-27XXL)



0226-36XX (0226-36XXL)



0226-37XX (0226-37XXL)



5.00mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	12~13mm	
Number of Positions		
0227-01XX	02~16P	
0227-02XX	02~16P	
0227-03XX	02~16P	
0227-04XX	02~16P	

• The product integrates light pipe for better indication

0227-01XX



0227-02XX



0227-03XX



0227-04XX



5.00mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0227-11XX	02~16P	
0227-12XX	02~16P	
0227-21XX	02~16P	
0227-22XX	02~16P	
0227-31XX	02~16P	
0227-32XX	02~16P	

• The product integrates light pipe for better indication

0227-11XX



0227-21XX



0227-31XX



0227-12XX



0227-22XX



0227-32XX



5.00mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	12~13mm	
Number of Positions		
0227-06XX	02~16P	
0227-07XX	02~16P	
0227-08XX	02~16P	
0227-09XX	02~16P	

0227-06XX



0227-07XX



0227-08XX



0227-09XX



5.00mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0227-16XX	02~16P	
0227-16XXL	02~16P	
0227-17XX	02~16P	
0227-17XXL	02~16P	
0227-26XX	02~16P	
0227-26XXL	02~16P	
0227-27XX	02~16P	
0227-27XXL	02~16P	
0227-36XX	02~16P	
0227-36XXL	02~16P	
0227-37XX	02~16P	
0227-37XXL	02~16P	

0227-16XX (0227-16XXL)

with support pins



0227-26XX (0227-26XXL)

with support pins



0227-36XX (0227-36XXL)

with support pins



0227-17XX (0227-17XXL)

with support pins



0227-27XX (0227-27XXL)

with support pins



0227-37XX (0227-37XXL)

with support pins



5.00mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	10A	18A
Solid (AWG/mm²)	26~12	0.2~2.5
Flexible (AWG/mm²)	26~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	10~11mm	
Number of Positions		
5ESV-XXP	02~24P	
5ESVM-XXP	02~24P	
5ESVK-XXP	02~24P	
5ESR-XXP	02~24P	
5ESRM-XXP	02~24P	
5ESRK-XXP	02~24P	

5ESV-XXP



5ESR-XXP



Socket

5EHDK-XXP/T	P58
5EHDR-XXP	P57
5EHDR-XXPL	P69
5EHDRC-XXP	P57
5EHDRC-XXPL	P69
5EHDRR-XXP	P58
5EHDRRC-XXP	P68
5EHDV-XXP	P56
5EHDV-XXPL	P68
5EHDVC-XXP	P56
5EHDVC-XXPL	P68

Please refer to the related page number for the compatible headers.

5ESVM-XXP



5ESRM-XXP



5ESVK-XXP



5ESRK-XXP



Socket

5EHDKM-XXP/T	P59	5EHDVM-XXP	P58
5EHDKPM-XXP	P59	5EHDVM-XXPL	P68
5EHDRM-XXP	P57		
5EHDRM-XXPL	P69		

Please refer to the related page number for the compatible headers.

5.08mm

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	10A	12A
Solid (AWG/mm²)	26~12	0.2~2.5
Flexible (AWG/mm²)	26~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	12~13mm	
Number of Positions		
2ESDSV-XXP	02~24P	

2ESDSV-XXP



Socket

2EHDR-XXP	P59	2EHDV-XXP	P58
2EHDRC-XXP	P59	2EHDVC-XXP	P68

Please refer to the related page number for the compatible headers.

5.08mm

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	10A	12A
Solid (AWG/mm²)	26~12	0.2~2.5
Flexible (AWG/mm²)	26~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	12~13mm	
Number of Positions		
2ESDSVM-XXP	02~24P	
2ESDSVK-XXP	02~24P	

2ESDSVM-XXP



2ESDSVK-XXP



Socket

2EHDRM-XXP	P59
2EHDVM-XXP	P58

Please refer to the related page number for the compatible headers.

5.08mm

2ESV-XXP



Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current		
2ESV-XXP	10A	18A
2ESS-XXP	15A	12A
2ESR-XXP	10A	18A
2ESVM-XXP	10A	18A
2ESRM-XXP	10A	18A
2ESSM-XXP	15A	12A
2ESVK-XXP	10A	18A
2ESRK-XXP	10A	18A
Solid (AWG/mm²)		
2ESV-XXP	26~12	0.2~2.5
2ESS-XXP	24~12	0.2~2.5
2ESR-XXP	26~12	0.2~2.5
2ESVM-XXP	26~12	0.2~2.5
2ESRM-XXP	26~12	0.2~2.5
2ESSM-XXP	24~12	0.2~2.5
2ESVK-XXP	26~12	0.2~2.5
2ESRK-XXP	26~12	0.2~2.5
Flexible (AWG/mm²)		
2ESV-XXP	26~12	0.2~2.5
2ESS-XXP	24~12	0.2~2.5
2ESR-XXP	26~12	0.2~2.5
2ESVM-XXP	26~12	0.2~2.5
2ESRM-XXP	26~12	0.2~2.5
2ESSM-XXP	24~12	0.2~2.5
2ESVK-XXP	26~12	0.2~2.5
2ESRK-XXP	26~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	10~11mm	
Number of Positions		
2ESV-XXP	02~24P	
2ESS-XXP	02~24P	
2ESR-XXP	02~24P	
2ESVM-XXP	02~24P	
2ESRM-XXP	02~24P	
2ESSM-XXP	02~24P	
2ESVK-XXP	02~24P	
2ESRK-XXP	02~24P	

2ESS-XXP



2ESR-XXP



Socket

2EHDA-XXP	P58
2EHDAC-XXP	P58
2EHDR-XXP	P59
2EHDR-XXPL	P69
2EHDRC-XXP	P59
2EHDRC-XXPL	P69
2EHDV-XXP	P58
2EHDV-XXPL	P68
2EHDVC-XXP	P58
2EHDVC-XXPL	P68

Please refer to the related page number for the compatible headers.

2ESVM-XXP



2ESRM-XXP



2ESSM-XXP



Socket

2EHDP-XXP	P58
2EHDRM-XXP	P59
2EHDRM-XXPL	P69
2EHDVM-XXP	P58
2EHDVM-XXPL	P68

Please refer to the related page number for the compatible headers.

2ESVK-XXP



2ESRK-XXP



DINKLE Memo

Twin Connectors With Double Push-in Connection



Connection method: Push-in connection
Pitch: 3.50mm / 5.00mm
UL Rated: 300V / 8A, 300V / 15A
IEC Rated: 320V / 8A, 600V / 18A





5.00mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	12~13mm	
Number of Positions		
0161-01XX	02~24P	
0161-02XX	02~16P	
0161-03XX	02~24P	
0161-04XX	02~24P	
0161-11XX	02~24P	
0161-12XX	02~24P	
0161-13XX	02~24P	
0161-14XX	02~24P	

- 0161 series are wire to wire twin connectors.
- Combination options with 0227 series.
- Versions with screw flange and lock flange.

0161-01XX



0161-11XX





0161-01XX Compatible products

0161-11XX Compatible products

0161-02XX



0161-12XX





0161-02XX Compatible products

0161-12XX Compatible products

0161-03XX





0161-13XX





0161-03XX Compatible products

0161-13XX Compatible products

0161-04XX



0161-14XX





0161-14XX Compatible products

3.50mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	8A
Solid (AWG/mm²)	24~16	0.2~1.5
Flexible (AWG/mm²)	24~16	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	10mm	
Number of Positions		
0181-A1XX	02~24P	
0181-A3XX	02~24P	

0181-A1XX



Socket	
ECH350RM-XXP	P57
ECH350RM-XXPL	P66
ECH350VM-XXP	P56
ECH350VM-XXPL	P67

Please refer to the related page number for the compatible headers.

0181-A3XX



Socket	
ECH350H-XXP	P57
ECH350R-XXP	P56
ECH350R-XXPL	P67
ECH350V-XXP	P56
ECH350V-XXPL	P66

Please refer to the related page number for the compatible headers.

PID Pluggable Terminal Blocks - Stable Type

Connection method: Push-in connection
Pitch: 5.08mm / 6.35mm / 7.50mm
UL Rated: 300V / 16A, 600V / 20A
IEC Rated: 320V / 20A, 1000V / 20A

- With lock flange directly beneath the plug housing for minimum width.
- Release tool (SDH-002) allows wiring operation by single hand.
- Additional support pins on both sides of the socket for extra strength.

Easy clip design

Strengthened mounting structure

6.35mm 0150-30XX

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	20A	20A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length	11mm	
Number of Positions		
0150-30XX	02~12P	



6.35mm 0150-31XX

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	20A	20A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length	11mm	
Number of Positions		
0150-31XX	02~12P	



6.35mm 0150-36XX

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	20A	20A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0150-36XX	02~12P	



5.08mm 0150-20XX

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	16A	20A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	11mm	
Number of Positions		
0150-20XX	02~24P	

5.08mm 0150-21XX

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	16A	20A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	11mm	
Number of Positions		
0150-21XX	02~24P	





5.08mm 0150-26XX

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	16A	20A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0150-26XX	02~24P	

· 0150-2605~0150-2624 with support pin

7.50mm 0150-40XX

Technical Data	UL	IEC
Rated voltage	600V	630V
Rated current	18A	18A
Solid (AWG/mm²)	20~12	0.5~2.5
Flexible (AWG/mm²)	20~12	0.5~2.5
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length	12~13mm	
Number of Positions		
0150-40XX	02~12P	



7.50mm 0150-46XX

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	18A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		6KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0150-46XX	02~12P	



SDH-002 (for 0150 series only)

Basic type



SDH-003 (for 0150 series only)

Durable type



PID Pluggable Terminal Blocks - Regular Type



Screw mounting flange for secure connection

Twin connection plug is available

Plug can connect with reflow-solderable sockets

Connection method: Push-in connection
Pitch: 2.50mm / 3.50mm / 3.81mm / 5.0mm / 5.08mm / 7.62mm
UL Rated: 150V / 4A ~ 300V / 15A
IEC Rated: 250V / 12A ~` 800V /15A

- Direct push-in connection single-level and front twin connection plugs.
- Versions with screw flange and release tool.
- Versions with testing holes.

Testing hole dimensions		
Product series	**Pitch(mm)**	**Hole Ø (mm)**
ESC250	2.50	1.10
ESC350	3.50	1.25
ESC381	3.81	1.25
5ESDS	5.00	2.3
2ESDS	5.08	2.3
ESC508	5.08	1.25
3ESDS	7.62	2.30

2.50mm — ESC250V-XXP

Technical Data	UL	IEC
Rated voltage	150V	320V
Rated current	4A	4A
Solid (AWG/mm²)	28~20	0.2~0.5
Flexible (AWG/mm²)	28~20	0.2~0.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	8mm	
Number of Positions		
ESC250V-XXP	02~24P	



Socket	
ECH250R-XXP	P55
ECH250V-XXP	P55
ECHB250R-XXP	P62
ECHB250V-XXP	P62

Please refer to the related page number for the compatible headers.

3.50mm — ESC350V-XXP / ESC350VM-XXP

Technical Data	UL	IEC
Rated voltage	300V	500V
Rated current	8A	10A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
ESC350V-XXP	02~20P	
ESC350VM-XXP	02~20P	







Socket		Socket	
ECH350V-XXP	P56	**ECH350VM-XXP**	P56
ECH350V-XXPL	P66	**ECH350VM-XXPL**	P67
ECHB350V-XXP	P63	**ECHB350VM-XXP**	P63
EECH350V-XXP	P64	**EECH350VM-XXP**	P64
ECH350H-XXP	P57	**ECH350RM-XXP**	P57
ECH350R-XXP	P56	**ECH350RM-XXPL**	P66
ECH350R-XXPL	P67	**ECHB350RM-XXP**	P63
ECHB350R-XXP	P63	**EECH350RM-XXP**	P63
EECH350R-XXP	P64		

Please refer to the related page number for the compatible headers.

Please refer to the related page number for the compatible headers.

3.81mm — ESC381V-XXP / ESC381VM-XXP / ESC381VK-XXP

Technical Data	UL	IEC
Rated voltage	300V	500V
Rated current	8A	10A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	7~8mm	
Number of Positions		
ESC381V-XXP	02~20P	
ESC381VM-XXP	02~20P	
ESC381VK-XXP	02~20P	









Socket		Socket		Socket	
ECH381A-XXP	P56	**ECH381AM-XXP**	P56	**ECHB381RRD-XXP**	P63
ECH381H-XXP	P57	**ECH381RM-XXP**	P57		
ECH381R-XXP	P56	**ECH381RM-XXPL**	P67		
ECH381R-XXPL	P67	**ECH381VM-XXP**	P56		
ECH381V-XXP	P56	**ECH381VM-XXPL**	P66		
ECH381V-XXPL	P66	**ECHB381RRM-XXP**	P63		

Please refer to the related page number for the compatible headers.

Please refer to the related page number for the compatible headers.

Please refer to the related page number for the compatible headers.

5.08mm — ESC508V-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	8A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	9mm	
Number of Positions		
ESC508V-XXP	02~24P	



Socket

ECH508R-XXP	P58	ECH508V-XXP	P58

Please refer to the related page number for the compatible headers.

5.08mm — ESC508VM-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	8A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	9mm	
Number of Positions		
ESC508VM-XXP	02~24P	



Socket

ECH508RM-XXP	P58	ECH508VM-XXP	P58

Please refer to the related page number for the compatible headers.

5.00mm — 5ESDS-XXP / 5ESDSR-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	10A	12A
Solid (AWG/mm²)		0.2~2.5
Flexible (AWG/mm²)	26~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	12mm	
Number of Positions		
5ESDS-XXP	02~24P	
5ESDSR-XXP	02~24P	
Accessories		
ESDK1	P49	
ESDK2	P49	



Socket

5EHDK-XXP/T	P58
5EHDR-XXP	P57
5EHDR-XXPL	P69
5EHDRC-XXP	P57
5EHDRC-XXPL	P69
5EHDRR-XXP	P58
5EHDRRC-XXP	P68
5EHDV-XXP	P56
5EHDV-XXPL	P68
5EHDVC-XXP	P56
5EHDVC-XXPL	P68

Please refer to the related page number for the compatible headers.

5.00mm — 5ESDSM-XXP / 5ESDSRM-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	10A	12A
Solid (AWG/mm²)		0.2~2.5
Flexible (AWG/mm²)	26~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	12mm	
Number of Positions		
5ESDSM-XXP	02~24P	
5ESDSRM-XXP	02~24P	
Accessories		
ESDK1	P49	
ESDK2	P49	



Socket

5EHDKM/T-XXP	P59
5EHDKPM-XXP	P59
5EHDRM-XXP	P57
5EHDRM-XXPL	P69
5EHDVM-XXP	P56
5EHDVM-XXPL	P68

Please refer to the related page number for the compatible headers.

5.08mm — 2ESDS-XXP / 2ESDSR-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	10A	12A
Solid (AWG/mm²)		0.2~2.5
Flexible (AWG/mm²)	26~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	12mm	
Number of Positions		
2ESDS-XXP	02~24P	
2ESDSR-XXP	02~24P	
Accessories		
ESDK1	P49	
ESDK2	P49	





Socket

2EHDA-XXP	P58
2EHDAC-XXP	P58
2EHDR-XXP	P59
2EHDR-XXPL	P69
2EHDRC-XXP	P59
2EHDRC-XXPL	P69
2EHDV-XXP	P58
2EHDV-XXPL	P68
2EHDVC-XXP	P58
2EHDVC-XXPL	P68

Please refer to the related page number for the compatible headers.

5.08mm — 2ESDSM-XXP / 2ESDSRM-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	10A	12A
Solid (AWG/mm²)		0.2~2.5
Flexible (AWG/mm²)	26~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	12mm	
Number of Positions		
2ESDSM-XXP	02~24P	
2ESDSRM-XXP	02~24P	
Accessories		
ESDK1	P49	
ESDK2	P49	





Socket

2EHDRM-XXP	P59
2EHDRM-XXPL	P69
2EHDVM-XXP	P58
2EHDVM-XXPL	P68

Please refer to the related page number for the compatible headers.

5.08mm — 2ESDB-XXP / 2ESDBA-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	12A	15A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	11~12mm	
Number of Positions		
2ESDB-XXP	02~24P	
2ESDBA-XXP	02~24P	





Socket

2EHDA-XXP	P58
2EHDAC-XXP	P58
2EHDR-XXP	P59
2EHDR-XXPL	P69
2EHDRC-XXP	P59
2EHDRC-XXPL	P69
2EHDV-XXP	P58
2EHDV-XXPL	P68
2EHDVC-XXP	P58
2EHDVC-XXPL	P68

Please refer to the related page number for the compatible headers.

5.08mm — 2ESDBM-XXP / 2ESDBAM-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	12A	15A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	11~12mm	
Number of Positions		
2ESDBM-XXP	02~24P	
2ESDBAM-XXP	02~24P	





Socket

2EHDRM-XXP	P59
2EHDRM-XXPL	P69
2EHDVM-XXP	P58
2EHDVM-XXPL	P68

Please refer to the related page number for the compatible headers.

Card Edge – direct connection



Wire connection method: Push-in connection
Pitch: 3.50/ 5.0/ 7.0/ 10.0mm
UL Rated: 150V/5A ~ 300V/5A
IEC Rated: 320V/5A ~ 800V/8A

- Direct connection on a 1.0 or 1.6mm thick PCB without additional pin strip.
- Push-in connection for quick and easy wiring.
- Special indication design on each pole allows integration LED on the PCB for clear signal identification.

0 1 8 4 - 1 1 X X
① ②③ ④

① series number

② Pitch
1 = 3.5mm
3 = 5.0mm
5 = 7.0mm
8 = 10.0mm

③ Compatible PCB thickness & Release tool
1 - 1.0mm PCB thickness
2 - 1.0mm PCB thickness, with release tool
3 - 1.6mm PCB thickness
4 - 1.6mm PCB thickness, with release tool

④ Pole number

7.62mm

Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	10A	15A
Solid (AWG/mm²)	26~12	0.2~2.5
Flexible (AWG/mm²)	26~12	0.2~2.5
Rated impulse voltage		6KV
Torque (N-m)		
Screw		
Wire strip length	10~11mm	
Number of Positions		
3ESDS-XXP	02~12P	
3ESDSR-XXP	02~12P	
Accessories		
ESDK1	P49	
ESDK2	P49	

3ESDS-XXP



3ESDSR-XXP



Socket

3EHDR-XXP	P61
3EHDRC-XXP	P61
3EHDV-XXP	P60
3EHDVC-XXP	P60

Please refer to the related page number for the compatible headers.

7.62mm

Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	10A	15A
Solid (AWG/mm²)	26~12	0.2~2.5
Flexible (AWG/mm²)	26~12	0.2~2.5
Rated impulse voltage		6KV
Torque (N-m)		
Screw		
Wire strip length	10~11mm	
Number of Positions		
3ESDSM-XXP	02~12P	
3ESDSRM-XXP	02~12P	
Accessories		
ESDK1	P49	
ESDK2	P49	

3ESDSM-XXP



3ESDSRM-XXP



Socket

3EHDRM-XXP	P61
3EHDVM-XXP	P60

Please refer to the related page number for the compatible headers.

7.00mm

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	6A	8A
Solid (AWG/mm²)	24~16	0.2~1.5
Flexible (AWG/mm²)	24~16	0.2~1.5
Rated impulse voltage		6KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0184-51XX	02~12P	
0184-52XX	02~12P	
0184-53XX	02~12P	
0184-54XX	02~12P	

10.00mm

Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	6A	8A
Solid (AWG/mm²)	24~16	0.2~1.5
Flexible (AWG/mm²)	24~16	0.2~1.5
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0184-81XX	02~09P	
0184-82XX	02~09P	
0184-83XX	02~09P	
0184-84XX	02~09P	

0184-51XX



0184-52XX



0184-81XX



0184-82XX



0184-53XX



0184-54XX



0184-83XX



0184-84XX



3.50mm

Technical Data	UL	IEC
Rated voltage	150V	320V
Rated current	6A	5A
Solid (AWG/mm²)	24~16	0.2~1.5
Flexible (AWG/mm²)	24~16	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0184-11XX	02~24P	
0184-12XX	02~24P	
0184-13XX	02~24P	
0184-14XX	02~24P	

5.00mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	6A	6A
Solid (AWG/mm²)	24~16	0.2~1.5
Flexible (AWG/mm²)	24~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0184-31XX	02~18P	
0184-32XX	02~18P	
0184-33XX	02~18P	
0184-34XX	02~18P	

0184-11XX



0184-12XX



0184-31XX



0184-32XX



0184-13XX



0184-14XX



0184-33XX



0184-34XX



PID Pluggable Terminal Blocks – pin strip design



Pitch: 3.50/ 5.0mm
UL Rated: 150V/2A ~ 300V/2A
IEC Rated: 160V/4A ~ 320V/9A

- Push-in connection for quick and easy wiring.
- Pin strip in high temperature material suitable for reflow application.
- The cover of the terminal block function as a lever which helps to remove the plug from the pin strip easily.

3.50mm

Technical Data	UL	IEC
Rated voltage	150V	160V
Rated current	2A	4A
Solid (AWG/mm²)	28~16	0.5~1.5
Flexible (AWG/mm²)	28~16	0.5~1.5
Rated impulse voltage		3KV
Torque (N-m)		
Screw		
Wire strip length		
0191-01XX	8mm	
0191-01XXC	8mm	
Number of Positions	02~20P	

· Pin strip: 0191-11XXTH

0191-01XX



0191-01XXC



0191-11XXTH



3.50mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	9A
Solid (AWG/mm²)	24~16	0.2~1.5
Flexible (AWG/mm²)	24~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
0191-06XX	8mm	
0191-06XXC	8mm	
Number of Positions	02~20P	

· Pin strip: 0191-16XXTH
· Various pin lengths available

0191-06XX



0191-06XXC



0191-16XXTH



5.00mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	2A	4A
Solid (AWG/mm²)	28~16	0.5~1.5
Flexible (AWG/mm²)	28~16	0.5~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
0191-02XX	8mm	
0191-02XXC	8mm	
Number of Positions	02~20P	

· Pin strip: 0191-12XXTH
· Various pin lengths available

0191-02XX



0191-02XXC



0191-12XXTH



Screw Connection Plug



Connection method: screw connection with elevated wire cage
Pitch: 3.50mm / 3.81mm / 5.00mm / 5.08mm / 6.35mm / 7.50mm / 7.62mm / 10.16 mm
UL Rated: 300V / 8A ~ 600V / 51A
IEC Rated:320V / 14A ~ 1000V / 76A

- Single and double-level plugs.
- Mating sockets include standard PA version and THR version.
- Key codes are available for identification of individual pole.
- Rigid structure for excellent durability.

The wire cage structure uses a high carbon steel material that undergoes a two-stage heat treatment process which strengthens the steel while maintaining ductility. The screw connection features a large contact surface that is suitable for solid and stranded wires. The wire cage is designed to ensure tight contact point which helps to achieve the low contact resistance and resistance to corrosion.

3.50mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)	28~14	0.2~1.5
Flexible (AWG/mm²)	28~14	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.2	
Screw	M2	
Wire strip length	6~7mm	
Number of Positions		
EC350V-XXP	02~24P	
EC350R-XXP	02~22P	
EC350RL-XXP	02~22P	
EC350VM-XXP	02~24P	
EC350RM-XXP	02~20P	
EC350RLM-XXP	02~20P	

EC350V-XXP



EC350R-XXP



EC350RL-XXP



EC350VM-XXP



EC350RM-XXP



EC350RLM-XXP



3.81mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)	28~14	0.2~1.5
Flexible (AWG/mm²)	28~14	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.2	
Screw	M2	
Wire strip length	7~8mm	
Number of Positions		
EC381V-XXP	02~24P	
EC381R-XXP	02~22P	
EC381RL-XXP	02~22P	
EC381VM-XXP	02~24P	
EC381RM-XXP	02~20P	
EC381RLM-XXP	02~20P	

EC381V-XXP



EC381R-XXP



EC381RL-XXP



EC381VM-XXP



EC381RM-XXP



EC381RLM-XXP



3.50mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)	30~16	0.2~1.5
Flexible (AWG/mm²)	30~14	0.2~1.5
Rated impulse voltage	2KV	2.5KV
Torque (N-m)	0.3	
Screw	M2	
Wire strip length	8~9mm	
Number of Positions		
EC350F-XXP	02~24P	
EC350FM-XXP	02~24P	

EC350F-XXP



EC350FM-XXP



3.81mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)	30~14	0.2~1.5
Flexible (AWG/mm²)	30~14	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.3	
Screw	M2	
Wire strip length	7~8mm	
Number of Positions		
EC381F-XXP	02~20P	
EC381FM-XXP	02~20P	

EC381F-XXP



EC381FM-XXP



Socket

ECH350V-XXP	P56	**ECH350H-XXP**	P57
ECH350V-XXPL	P66	**ECH350R-XXP**	P56
ECHB350V-XXP	P63	**ECH350R-XXPL**	P67
EECH350V-XXP	P64	**ECHB350R-XXP**	P63
		EECH350R-XXP	P64

Please refer to the related page number for the compatible headers.

Socket

ECH350VM-XXP	P56	**ECH350RM-XXP**	P57
ECH350VM-XXPL	P67	**ECH350RM-XXPL**	P66
ECHB350VM-XXP	P63	**ECHB350RM-XXP**	P63
EECH350VM-XXP	P64	**EECH350RM-XXP**	P64

Please refer to the related page number for the compatible headers.

Socket

ECH381V-XXP	P56	**ECH381A-XXP**	P56
ECH381V-XXPL	P66	**ECH381H-XXP**	P57
ECHB381V-XXP	P62	**ECH381R-XXP**	P56
EECH381V-XXP	P64	**ECH381R-XXPL**	P67
		ECHB381R-XXP	P62
		EECH381R-XXP	P64

Please refer to the related page number for the compatible headers.

Socket

ECH381VM-XXP	P56	**ECH381AM-XXP**	P56
ECH381VM-XXPL	P66	**ECH381RM-XXP**	P57
ECHP381V-XXP	P56	**ECH381RM-XXPL**	P67
ECHB381VM-XXP	P62	**ECHB381RM-XXP**	P63
EECH381VM-XXP	P64	**EECH381RM-XXP**	P65

Please refer to the related page number for the compatible headers.

3.81mm

EC381L-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)	28~14	0.2~1.5
Flexible (AWG/mm²)	28~14	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw	M2	
Wire strip length	6~7mm	
Number of Positions		
EC381L-XXP	02~09P	
EC381LM-XXP	02~09P	



Socket			
ECH381V-XXP	P56	ECH381A-XXP	P56
ECH381V-XXPL	P66	ECH381H-XXP	P57
ECHB381V-XXP	P62	ECH381R-XXP	P56
EECH381V-XXP	P64	ECH381R-XXPL	P67
		ECHB381R-XXP	P62
		EECH381R-XXP	P64

Please refer to the related page number for the compatible headers.

EC381LM-XXP



Socket			
ECH381VM-XXP	P56	ECH381AM-XXP	P56
ECH381VM-XXPL	P66	ECH381RM-XXP	P57
ECHP381V-XXP	P56	ECH381RM-XXPL	P67
ECHB381VM-XXP	P62	ECHB381RM-XXP	P63
EECH381VM-XXP	P64	EECH381RM-XXP	P65

Please refer to the related page number for the compatible headers.

5.08mm

EC508V-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	12A	14A
Solid (AWG/mm²)		
EC508V-XXP	30~14	0.2~1.5
EC508F-XXP	28~14	0.2~1.5
EC508VM-XXP	30~14	0.2~1.5
EC508FM-XXP	28~14	0.2~1.5
Flexible (AWG/mm²)		
EC508V-XXP	30~14	0.2~1.5
EC508F-XXP	28~14	0.2~1.5
EC508VM-XXP	30~14	0.2~1.5
EC508FM-XXP	28~14	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
EC508V-XXP	0.2	
EC508F-XXP	0.3	
EC508VM-XXP	0.2	
EC508FM-XXP	0.3	
Screw	M2	
Wire strip length	8~9mm	
Number of Positions		
EC508V-XXP	02~24P	
EC508F-XXP	02~24P	
EC508VM-XXP	02~24P	
EC508FM-XXP	02~24P	



EC508F-XXP



Socket	
ECH508V-XXP	P58
ECH508R-XXP	P58

Please refer to the related page number for the compatible headers.

EC508VM-XXP



EC508FM-XXP



Socket	
ECH508VM-XXP	P58
ECH508RM-XXP	P59

Please refer to the related page number for the compatible headers.

3.81mm

EC381VK-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)	28~14	0.2~1.5
Flexible (AWG/mm²)	28~14	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.2	
Screw	M2	
Wire strip length	7~8mm	
Number of Positions		
EC381VK-XXP	02~24P	



Socket			
ECHB381RRD-XXP	P63		

Please refer to the related page number for the compatible headers.

5.00mm

5ESDA-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
5ESDA-XXP	02~24P	
5ESDP-XXP	02~24P	
Accessories		
ESDK1	P49	
ESDK2	P49	



5ESDP-XXP





Socket	
5EHDV-XXP	P56
5EHDV-XXPL	P68
5EHDVC-XXP	P56
5EHDVC-XXPL	P68
5EHDBV-XXP	P62
5EEHDV-XXP	P64
5EHDR-XXP	P64
5EHDR-XXPL	P57
5EHDRC-XXP	P69
5EHDRC-XXPL	P57
5EHDBR-XXP	P62
5EHDRR-XXP	P58
5EHDRRC-XXP	P58
5EEHDR-XXP	P64
5EHDK-XXP/T	P58

Please refer to the related page number for the compatible headers.

5.00mm

5ESDF-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	9~10mm	
Number of Positions		
5ESDF-XXP	02~24P	
Accessories		
ESDK1	P49	
ESDK2	P49	



5ESDFM-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	9~10mm	
Number of Positions		
5ESDFM-XXP	02~24P	
Accessories		
ESDK1	P49	
ESDK2	P49	



Socket	
5EHDVM-XXP	P56
5EHDVM-XXPL	P68
5EHDBVM-XXP	P62
5EEHDVM-XXP	P64
5EHDRM-XXP	P64
5EHDRM-XXPL	P69
5EHDKM-XXP/T	P59
5EHDKPM-XXP/T	P59
5EHDBRM-XXP	P63
5EEHDRM-XXP	P64

Please refer to the related page number for the compatible headers.

5.00mm

5ESDV-XXP



5ESDPL-XXP



Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
5ESDV-XXP	02~24P	
5ESDPL-XXP	02~24P	
5ESDT-XXP	02~24P	
Accessories		
ESDK1	P49	
ESDK2	P49	

5ESDT-XXP



Socket	
5EHDV-XXP	P56
5EHDV-XXPL	P68
5EHDVC-XXP	P56
5EHDVC-XXPL	P68
5EHDBV-XXP	P62
5EEHDV-XXP	P64
5EHDR-XXP	P64
5EHDR-XXPL	P57
5EHDRC-XXP	P69
5EHDRC-XXPL	P57
5EHDBR-XXP	P62
5EHDRR-XXP	P58
5EHDRRC-XXP	P58
5EEHDR-XXP	P64
5EHDK-XXP/T	P58

Please refer to the related page number for the compatible headers.

5.00mm

5ESDVM-XXP





5ESDPLM-XXP



Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
5ESDVM-XXP	02~24P	
5ESDPLM-XXP	02~24P	
5ESDAM-XXP	02~24P	
5ESDPM-XXP	02~24P	

5ESDAM -XXP



5ESDPM-XXP





Socket	
5EHDVM-XXP	P56
5EHDVM-XXPL	P68
5EHDBVM-XXP	P62
5EEHDVM-XXP	P64
5EHDRM-XXP	P64
5EHDRM-XXPL	P69
5EHDKM-XXP/T	P59
5EHDKPM-XXP	P59
5EHDBRM-XXP	P63
5EEHDRM-XXP	P64

Please refer to the related page number for the compatible headers.

5.08mm

2ESDV-XXP





2ESDP-XXP





Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
2ESDV-XXP	02~24P	
2ESDP-XXP	02~24P	
Accessories		
ESDK1	P49	
ESDK2	P49	

2ESDF-XXP



2ESDA-XXP





Socket	
2EHDV-XXP	P58
2EHDV-XXPL	P68
2EHDC-XXP	P58
2EHDVC-XXPL	P68
2EHDBV-XXP	P62
2EEHDV-XXP	P64
2EHDR-XXP	P59
2EHDR-XXPL	P69
2EHDRC-XXP	P59
2EHDRC-XXPL	P69
2EHDA-XXP	P58
2EHDAC-XXP	P58
2EHDBR-XXP	P62
2EEHDR-XXP	P64

Please refer to the related page number for the compatible headers.

5.08mm

2ESDVM-XXP





2ESDPM-XXP



Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
2ESDVM-XXP	02~24P	
2ESDPM-XXP	02~24P	

2ESDFM-XXP



Socket	
2EHDVM-XXP	P58
2EHDVM-XXPL	P68
2EHDBVM-XXP	P58
2EEHDVM-XXP	P68
2EHDRM-XXP	P59
2EHDRM-XXPL	P69
2EHDBRM-XXP	P63
2EEHDRM-XXP	P65

Please refer to the related page number for the compatible headers.

5.08mm 2ESDPL-XXP 2ESDL-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
2ESDPL-XXP	02~24P	
2ESDL-XXP	03~16P	
Accessories		
ESDK1	P49	
ESDK2	P49	



5.08mm 2ESDVB-XXP

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	16A	18A
Solid (AWG/mm²)	30~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.6	
Screw	M2.5	
Wire strip length	7mm	
Number of Positions		
2ESDVB-XXP	02~12P	



5.08mm 2ESDAM-XXP 2ESDPLM-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
2ESDAM-XXP	02~24P	
2ESDPLM-XXP	02~24P	



5.08mm 2ESDVBM-XXP

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	16A	18A
Solid (AWG/mm²)	30~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.6	
Screw	M2.5	
Wire strip length	7mm	
Number of Positions		
2ESDVBM-XXP	02~12P	



Socket

2EHDV-XXP	P58
2EHDV-XXPL	P68
2EHDC-XXP	P58
2EHDVC-XXPL	P68
2EHDBV-XXP	P62
2EEHDV-XXP	P64
2EHDR-XXP	P59
2EHDR-XXPL	P69
2EHDRC-XXP	P59
2EHDRC-XXPL	P69
2EHDA-XXP	P58
2EHDAC-XXP	P58
2EHDBR-XXP	P62
2EEHDR-XXP	P64

Please refer to the related page number for the compatible headers.

Socket

2EHDVM-XXP	P58
2EHDVM-XXPL	P68
2EHDBVM-XXP	P58
2EEHDVM-XXP	P68
2EHDRM-XXP	P59
2EHDRM-XXPL	P69
2EHDBRM-XXP	P63
2EEHDRM-XXP	P65

Please refer to the related page number for the compatible headers.

7.50mm 7ESDV-XXP 7ESDP-XXP

Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	15A	18A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		6KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
7ESDV-XXP	02~12P	
7ESDP-XXP	02~11P	
7ESDVM-XXP	02~12P	
7ESDPM-XXP	02~11P	
Accessories		
ESDK1	P49	
ESDK2	P49	



Socket

7EHDV-XXP	P60
7EHDVC-XXP	P60
7EHDR-XXP	P61
7EHDRC-XXP	P61

Please refer to the related page number for the compatible headers.

7.50mm 7ESDVM-XXP 7ESDPM-XXP



Socket

7EHDVM-XXP	P60
7EHDRM-XXP	P61

Please refer to the related page number for the compatible headers.

7.50mm 7ESDPL-XXP

Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	15A	18A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		6KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
7ESDPL-XXP	02~11P	
7ESDPLM-XXP	02~11P	
Accessories		
ESDK1	P49	
ESDK2	P49	



7.50mm 7ESDPLM-XXP



Socket

7EHDV-XXP	P60	7EHDR-XXP	P61
7EHDVC-XXP	P60	7EHDRC-XXP	P61

Please refer to the related page number for the compatible headers.

Socket

7EHDVM-XXP	P60	7EHDRM-XXP	P61

Please refer to the related page number for the compatible headers.

7.62mm

3ESDV-XXP

Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	15A	18A
Solid (AWG/mm²)		
3ESDV-XXP	28~12	0.2~2.5
3ESDP-XXP	28~12	0.2~2.5
3ESDVM-XXP	28~12	0.5~2.5
3ESDPM-XXP	28~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		6KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
3ESDV-XXP	02~12P	
3ESDP-XXP	02~12P	
3ESDVM-XXP	02~12P	
3ESDPM-XXP	02~12P	
Accessories		
ESDK1	P49	
ESDK2	P49	



3ESDP-XXP



Socket

3EHDV-XXP	P60
3EHDVC-XXP	P60
3EHDR-XXP	P61
3EHDRC-XXP	P61

Please refer to the related page number for the compatible headers.

3ESDVM-XXP



3ESDPM-XXP



Socket

3EHDVM-XXP	P60
3EHDRM-XXP	P61

Please refer to the related page number for the compatible headers.

7.62mm

3ESDPL-XXP

Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	15A	18A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		6KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
3ESDPL-XXP	02~12P	
3ESDPLM-XXP	02~12P	
Accessories		
ESDK1	P49	
ESDK2	P49	



Socket

3EHDV-XXP	P60	3EHDR-XXP	P61
3EHDVC-XXP	P60	3EHDRC-XXP	P61

Please refer to the related page number for the compatible headers.

3ESDPLM-XXP



Socket

3EHDVM-XXP	P60	3EHDRM-XXP	P61

Please refer to the related page number for the compatible headers.

PID Pluggable Terminal Blocks for Relay Protection Equipment

- Push-in design connection, sufficiently improves wire installation time.
- High conductive material is adopted and structurally designed for low contact resistance.
- Designed for high density connection, suitable for IO device, monitoring device or power distribution applications.

5.08mm

FDC508B-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	6A	6A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
FDC508B-XXP	20~44P	
FDC508B1-XXP	20~44P	
FDC508B3-XXP	20~44P	



FDC508B1-XXP



FDC508B3-XXP



5.08mm

FDCH508R-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	6A	6A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
FDCH508R-XXP	20~32P	



5.08mm

FDC508BM-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	6A	6A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
FDC508BM-XXP	20~44P	



5.08mm

FDCH508RM-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	6A	6A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
FDCH508RM-XXP	20~32P	



Screw Connection Pluggable Terminal Blocks – High Power

Connection method: Screw connection
Pitch: 7.62mm / 10.16mm
UL Rated: 600V / 15A ~ 600V / 51A
IEC Rated: 320V /24A ~ 1000V / 76A

- 3ESNP series plug has a voltage capacity of 600V and current capacity up to 18A in a compact structure, and can be used with standard 3EHD series socket.
- EC762 series has a high current capacity up to 40A UL rating , and adopts M3 screw with connection up to 4mm ² stranded wire. Available in horizontal design 02~06 poles.
- EC116V series plug has a current capacity of 51A UL rating and 75A IEC rating. The socket versions include vertical and horizontal plug-in direction to the PCB and an inverted version is available where solder-in direction is rotated by 180˚.



3ESNP series

EC762 series

EC116V series

7.62mm

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	15A	24A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	28~12	0.2~2.5
Rated impulse voltage		8KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
3ESNP-XXP	02~12P	
3ESNPL-XXP	02~12P	
3ESNPS-XXP	02~12P	
3ESNPLS-XXP	02~12P	
3ESNPM-XXP	02~12P	
3ESNPLM-XXP	02~12P	
3ESNPSM-XXP	02~12P	
3ESNPLSM-XXP	02~12P	

3ESNP-XXP



3ESNPL-XXP



3ESNPS-XXP



3ESNPLS-XXP



7.62mm

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	18A	24A
Solid (AWG/mm²)	28~10	0.2~4
Flexible (AWG/mm²)	28~10	0.2~4
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length	7~8mm	
Number of Positions		
3ESNPHL-XXP	02~12P	

3ESNPHL-XXP



Socket	
3EHDV-XXP	P60
3EHDVC-XXP	P60
3EHDR-XXP	P61
3EHDRC-XXP	P61

Please refer to the related page number for the compatible headers.

7.62mm

3ESNPM-XXP

3ESNPLM-XXP

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	15A	24A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	28~12	0.2~2.5
Rated impulse voltage		8KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
3ESNP-XXP	02~12P	
3ESNPL-XXP	02~12P	
3ESNPS-XXP	02~12P	
3ESNPLS-XXP	02~12P	
3ESNPM-XXP	02~12P	
3ESNPLM-XXP	02~12P	
3ESNPSM-XXP	02~12P	
3ESNPLSM-XXP	02~12P	



3ESNPSM-XXP

3ESNPLSM-XXP



Socket

3EHDVM-XXP	P60
3EHDRM-XXP	P61

Please refer to the related page number for the compatible headers.

7.62mm

EC762V-XXP

EC762VN-XXP

Technical Data	UL	IEC
Rated voltage		
EC762V-XXP	300V	1000V
EC762VN-XXP	300V	1000V
EC762HV-XXP	600V	1000V
EC762HVN-XXP	600V	1000V
Rated current		
EC762V-XXP	30A	32A
EC762VN-XXP	30A	32A
EC762HV-XXP	40A	41A
EC762HVN-XXP	40A	41A
Solid (AWG/mm²)		
EC762V-XXP	30~10	0.2~4
EC762VN-XXP	30~10	0.2~4
EC762HV-XXP	30~8	0.2~6
EC762HVN-XXP	30~8	0.2~6
Flexible (AWG/mm²)		
EC762V-XXP	30~10	0.2~4
EC762VN-XXP	30~10	0.2~4
EC762HV-XXP	30~8	0.2~6
EC762HVN-XXP	30~8	0.2~6
Rated impulse voltage		
EC762V-XXP		6KV
EC762VN-XXP		6KV
EC762HV-XXP		8KV
EC762HVN-XXP		8KV
Torque (N-m)	0.7	
Screw	M3	
Wire strip length	7~8mm	
Number of Positions	02~12P	
Accessories		
ECHK2	P49	



EC762HV-XXP

EC762HVN-XXP



Socket

ECH762V-XXP	P60
ECH762R-XXP	P61
ECH762RR-XXP	P60
ECH762HR-XXP	P61
ECH762HRR-XXP	P61

Please refer to the related page number for the compatible headers.

7.62mm

EC762VM-XXP

EC762VNM-XXP

Technical Data	UL	IEC
Rated voltage		
EC762VM-XXP	300V	1000V
EC762VNM-XXP	300V	1000V
EC762HVM-XXP	600V	1000V
EC762HVNM-XXP	600V	1000V
Rated current		
EC762VM-XXP	30A	32A
EC762VNM-XXP	30A	32A
EC762HVM-XXP	40A	41A
EC762HVNM-XXP	40A	41A
Solid (AWG/mm²)		
EC762VM-XXP	30~10	0.2~4
EC762VNM-XXP	30~10	0.2~4
EC762HVM-XXP	30~8	0.2~6
EC762HVNM-XXP	30~8	0.2~6
Flexible (AWG/mm²)		
EC762VM-XXP	30~10	0.2~4
EC762VNM-XXP	30~10	0.2~4
EC762HVM-XXP	30~8	0.2~6
EC762HVNM-XXP	30~8	0.2~6
Rated impulse voltage		
EC762VM-XXP		6KV
EC762VNM-XXP		6KV
EC762HVM-XXP		8KV
EC762HVNM-XXP		8KV
Torque (N-m)	0.7	
Screw	M3	
Wire strip length	7~8mm	
Number of Positions	02~12P	
Accessories		
ECHK2	P49	





EC762HVM-XXP

EC762HVNM-XXP





Socket

ECH762VM-XXP	P60
ECH762VTM-XXP	P60
ECH762RM-XXP	P61
ECH762RRM-XXP	P60
ECH762RTM-XXP	P61

Please refer to the related page number for the compatible headers.

7.62mm

0183-01XX

0183-01XXTXX

Technical Data	UL	IEC
Rated voltage	600V	630V
Rated current	25A	32A
Solid (AWG/mm²)	20~10	0.2~6
Flexible (AWG/mm²)	20~10	0.2~6
Rated impulse voltage		6KV
Torque (N-m)		
Screw	M3	
Wire strip length	8mm	
Number of Positions		
0183-01XX	02~12P	
0183-01XXTXX	03~12P	





7.62mm

0183-11XX

0183-11XXTXX

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	25A	32A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		6KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0183-11XX	02~12P	
0183-11XXTXX	03~12P	





10.16mm EC116V-XXP

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	51A	76A
Solid (AWG/mm²)	16~6	0.5~16
Flexible (AWG/mm²)	16~6	0.5~16
Rated impulse voltage		8KV
Torque (N-m)	1.8	
Screw	M4	
Wire strip length	14~15mm	
Number of Positions		
EC116V-XXP	02~10P	
Accessories		
ECHK2	P49	



10.16mm 0187-A4XX

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	51A	76A
Solid (AWG/mm²)	20~4	0.75~16
Flexible (AWG/mm²)	20~4	0.75~16
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length	18~20mm	
Number of Positions		
0187-A4XX	02~10P	



10.16mm EC116VM-XXP

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	51A	76A
Solid (AWG/mm²)	16~6	0.5~16
Flexible (AWG/mm²)	16~6	0.5~16
Rated impulse voltage		8KV
Torque (N-m)		
Screw	M4	
Wire strip length	14~15mm	
Number of Positions		
EC116VM-XXP	02~08P	
Accessories		
ECHK2	P49	



10.16mm ECH116V-XXP

Technical Data	UL	IEC
Rated voltage	300V / 600V	1000V
Rated current	51A / 5A	76A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECH116V-XXP	02~10P	
ECH116R-XXP	02~10P	
ECH116L-XXP	02~10P	
Accessories		
ECHK2	P38	



10.16mm ECH116RM-XXP

Technical Data	UL	IEC
Rated voltage	300V	1000V
Rated current	51A	76A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECH116RM-XXP	02~08P	



ECH116R-XXP / ECH116L-XXP



10.16mm ECH116HVS-XXP

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	51A	76A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECH116HVS-XXP	02~10P	



ECHK1



ECHK1-For

ECH350 / ECH381
ECHP381
ECHB350 / ECHB381
ECH508
EECH350 / EECH381
0221-25XX
0221-33XX
0221-39XX
0221-41XX
0221-51XX
0221-52XX

ECHK2



ECHK2-For

EC116
EC762
ECH116
ECH762

ESDK1



ESDK1-For

2ESD
3ESD
5ESD
7ESD

ESDK2



ESDK2-For

2ESD
5ESD
7ESD

* 6pcs of ESDK1

ECHK1L



ECHK1L-For

ECH350 / ECH381
0221-25XX
0221-33XX
0221-39XX
0221-41XX
0221-51XX
0221-52XX

For THR applications

EHDK1



EHDKL1-For

2EHD
3EHD
5EHD
7EHD

CSC-01XX



CSC-01XX-For

EC350

EHDK1L



EHDKL1-For

2EHD
5EHD

Screw Connection Pluggable Terminal Blocks – pin strip design



- Reliable contact structure with high current capacity.
- The plug “ED130R-XXP” is designed with a snap-in locking feet making installation on a mounting plate quick and easy.
- For the pin strips part number which contains “TH” meaning the plastic is in high temperature material and is suitable for reflow process.
- Various length of pin strip is available by request.

5.00mm

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	7A	12A
Solid (AWG/mm²)	22~14	0.5~1.5
Flexible (AWG/mm²)	22~14	0.5~1.5
Rated impulse voltage		4KV
Torque (N-m)	0.3	
Screw	M2.5	
Wire strip length	5~6mm	
Number of Positions		
ED130F-XXP	02、03P	
EDH130F-XX/12.6	02~20P	
EDH130F-XXTH126	02~20P	

ED130F-XXP

EDH130F-XX/12.6

EDH130F-XXTH126

5.00mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	12A	10A
Solid (AWG/mm²)	22~14	0.5~1.5
Flexible (AWG/mm²)	22~14	0.5~1.5
Rated impulse voltage		4KV
Torque (N-m)	0.3	
Screw	M2.5	
Wire strip length	5~6mm	
Number of Positions		
ED130R-XXP	02~20P	
EDH130-21XX	02~20P	
EDH130-21XXTHT	02~20P	

ED130R-XXP



EDH130-21XX



EDH130-21XXTHT



Screw Connection Pluggable Terminal Blocks – pin strip design

- Interlocking design contributes better mating and connection quality, particularly conducive to anti-vibration.
- Unique rotational mating design offers different option of mating orientation from the market.
- The combination of plug and header is applicable to mount together through soldering process.

4.00mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	10A	17.5A
Solid (AWG/mm²)	24~14	0.2~2.5
Flexible (AWG/mm²)	24~14	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
0162-01XX	02~24P	
0162-11XX	02~24P	
0162-A1XX	02~24P	

· Socket: 0162-11XX

0162-01XX

0162-11XX



0162-A1XX

5.08mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	10A	17.5A
Solid (AWG/mm²)	26~12	0.2~2.5
Flexible (AWG/mm²)	26~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
0164-01XX	02~24P	
0164-01XX(T)	02~24P	
0164-11XX	02~24P	
0164-A1XX	02~24P	
0164-A1XX(T)	02~24P	

· Socket: 0164-11XX

0164-01XX
0164-01XX(T)



0164-11XX



0164-A1XX
0164-A1XX(T)



Screw connection
Inverted Pluggable Terminal Blocks

Connection method: screw connection with elevated wire cage

Pitch: 3.50mm / 3.58mm / 3.81mm / 5.00mm / 5.08mm / 7.62mm

UL Rated: 150V / 12A~300V / 16A

IEC Rated: 250V / 12A ~ 400V / 12A

- CPC350 and 5ESDG are card edge design and can connect directly on a 1.6mm thick PCB.
- There are vertical and horizontal versions of inverted plugs and headers.
- Inverted header is suitable for wave soldering application.

3.50mm — CPC350-XXP

Technical Data	UL	IEC
Rated voltage	150V	320V
Rated current	12A	14A
Solid (AWG/mm²)	28~14	0.2~1.5
Flexible (AWG/mm²)	28~14	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.2	
Screw	M2	
Wire strip length	7~8mm	
Number of Positions		
CPC350-XXP	02~24P	



Thickness of the PCB: 1.6mm

5.00mm — 5ESDG-XXP

Technical Data	UL	IEC
Rated voltage	300V	400V
Rated current	16A	12A
Solid (AWG/mm²)	28~12	0.32~2.5
Flexible (AWG/mm²)	28~12	0.32~2.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
5ESDG-XXP	02~14P	



3.81mm — ECSH381V-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	8A
Solid (AWG/mm²)	30~14	0.2~1.5
Flexible (AWG/mm²)	30~14	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.2	
Screw	M2	
Wire strip length	7mm	
Number of Positions		
ECSH381V-XXP	02~24P	



EC381CV-XXP	P53
EC381CR-XXP	P53
EC381V-XXP	P34
EC381R-XXP	P34
EC381RL-XXP	P34
EC381F-XXP	P35

5.08mm — 2ESH-XXP / 2ESHM-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	12A	12A
Solid (AWG/mm²)	24~12	0.5~2.5
Flexible (AWG/mm²)	24~12	0.5~2.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.6	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
2ESH-XXP	02~12P	
2ESHM-XXP	02~12P	
Accessories		
EHDK1	P49	







3.50mm — EC350CV-XXP / EC350CR-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	8A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
EC350CV-XXP	02~16P	
EC350CR-XXP	02~16P	





ECH350V-XXP	P34
ECH350R-XXP	P34

3.81mm — EC381CV-XXP / EC381CR-XXP

Technical Data	UL	IEC
Rated voltage	300V	300V
Rated current	8A	8A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	7~8mm	
Number of Positions		
EC381CV-XXP	02~16P	
EC381CR-XXP	02~16P	





ECSH381V-XXP	P52
ECH381V-XXP	P56
ECH381R-XXP	P56

5.08mm — 2ESDCV-XXP / 2ESDCR-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	12A	12A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
2ESDCV-XXP	02~24P	
2ESDCR-XXP	02~24P	
Accessories		
ESDK1	P49	
ESDK2	P49	
EHDK1	P49	





2ESH-XXP	P53
2EHDV-XXP	P58
2EHDVC-XXP	P58
2EHDR-XXP	P59
2EHDRC-XXP	P59

5.08mm — 2ESDCVM-XXP / 2ESDCRM-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	12A	12A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
2ESDCVM-XXP	02~20P	
2ESDCRM-XXP	02~20P	
Accessories		
ESDK1	P49	
ESDK2	P49	
EHDK1	P49	





2ESHM-XXP	P53
2EHDVM-XXP	P58
2EHDRM-XXP	P59

Headers (Sockets) For Pluggable Terminal Blocks



Pitch: 2.50mm / 3.50mm / 3.81mm / 5.00mm / 5.08mm / 7.50mm / 7.62mm
UL Rated: 150V / 4A, 300V / 8A, 300V / 15A, 300V / 30A, 600V / 30A
IEC Rated: 320V / 4A ~ 1000V / 41A

- Single and double level socket for pluggable PCB terminal blocks
- Horizontal, vertical and 45 degrees plug-in direction.
- With screw flange and lock flange versions.

5.00mm — 5ESN-XXP

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	15A	15A
Solid (AWG/mm²)	28~14	0.08~1.5
Flexible (AWG/mm²)	28~14	0.08~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	11~12mm	
Number of Positions		
5ESN-XXP	02~24P	





0227-36XX	P17
0227-37XX	P17

5.08mm — 2EHDRS-XXP / 2EHDRD-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	12A	12A
Solid (AWG/mm²)	24~12	0.5~2.5
Flexible (AWG/mm²)	24~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.6	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
2EHDRS-XXP	02~20P	
2EHDRD-XXP	02~20P	









2ESV-XXP	P20
2ESR-XXP	P20
2ESDV-XXP	P39
2ESDF-XXP	P39
2ESDP-XXP	P39

5.08mm — 2EHDRSM-XXP / 2EHDRDM-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	12A	12A
Solid (AWG/mm²)	24~12	0.5~2.5
Flexible (AWG/mm²)	24~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.6	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
2EHDRSM-XXP	02~20P	
2EHDRDM-XXP	02~20P	









2ESVM-XXP	P20
2ESRM-XXP	P20
2ESDVM-XXP	P39
2ESDFM-XXP	P39
2ESDPM-XXP	P39

7.62mm — 3ESH-XXP / 3ESDHM-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	12A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		6KV
Torque (N-m)	0.4~0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
3ESH-XXP	02~12P	
3ESDHM-XXP	02~12P	





3ESDV-XXP	P34	**3ESDVM-XXP**	P34
3ESDP-XXP	P34	**3ESDPM-XXP**	P34

2.50mm — ECH250V-XXP / ECH250R-XXP

Technical Data	UL	IEC
Rated voltage	150V	320V
Rated current	4A	4A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECH250V-XXP	02~24P	
ECH250R-XXP	02~24P	







3.50mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECH350V-XXP	02~24P	
ECH350VM-XXP	02~24P	
ECH350R-XXP	02~24P	
ECH350RM-XXP	02~24P	
ECH350H-XXP	02~16P	
ECH350RR-XXP	02~24P	
ECH350RRM-XXP	02~24P	
Accessories		
ECHK1	P49	

ECH350V-XXP



ECH350VM-XXP



ECH350R-XXP



ECH350RM-XXP



ECH350H-XXP



ECH350RR-XXP



ECH350RRM-XXP



3.81mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECH381V-XXP	02~24P	
ECH381VM-XXP	02~24P	
ECH381R-XXP	02~24P	
ECH381RM-XXP	02~24P	
ECH381H-XXP	02~16P	
ECH381RR-XXP	02~20P	
ECH381RRM-XXP	02~20P	
ECH381A-XXP	02~24P	
ECH381AM-XXP	02~22P	
ECHP381V-XXP	02~24P	
ECH381RG-XXP	02~10P	
Accessories		
ECHK1	P49	

ECH381V-XXP



ECH381VM-XXP



ECH381R-XXP



ECH381RM-XXP



ECH381H-XXP



ECH381RR-XXP



ECH381RRM-XXP



ECH381A-XXP



ECH381AM-XXP



ECHP381V-XXP



ECH381RG-XXP



ECHG1





Socket (ECH381RG-XXP) assembled with light pipe(ECHG1)

5.00mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
5EHDV-XXP	02~24P	
5EHDVC-XXP	02~24P	
5EHDVM-XXP	02~24P	
5EHDR-XXP	02~24P	
5EHDRC-XXP	02~24P	
5EHDRM-XXP	02~24P	
Accessories		
5EHDV-XXP	EHDK1	P49
5EHDVC-XXP	EHDK1	P49
5EHDVM-XXP	EHDK1	P49

5EHDV-XXP



5EHDVC-XXP



5EHDVM-XXP



5EHDR-XXP



5EHDRC-XXP



5EHDRM-XXP



5.00mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
5EHDRR-XXP	02~13P	
5EHDRRC-XXP	02~13P	
5EHDK-XXP/T	02~12P/T (T1.0、1.2、1.4、1.6)	
5EHDKM-XXP/T	02~12P/T (T1.0、1.2、1.4、1.6)	
5EHDKPM-XXP	02~12P	
Accessories		
5EHDK-XXP	EHDK1	P49
5EHDKM-XXP	EHDK1	P49
5EHDKPM-XXP	EHDK1	P49

5EHDK-XXP/T &5EHDKM-XXP/T
The suffix "T" represents the panel thickness in 1.0, 1.2, 1.4, 1.6mm

5EHDRR-XXP



5EHDRRC-XXP



5EHDK-XXP/T



5EHDKM-XXP/T



5EHDKPM-XXP



5.08mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	12A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECH508V-XXP	02~24P	
ECH508VM-XXP	02~24P	
ECH508R-XXP	02~24P	
ECH508RM-XXP	02~24P	

ECH508V-XXP



ECH508VM-XXP



ECH508R-XXP



ECH508RM-XXP



5.08mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
2EHDV-XXP	02~24P	
2EHDVC-XXP	02~24P	
2EHDVM-XXP	02~24P	
2EHDR-XXP	02~24P	
2EHDRC-XXP	02~24P	
2EHDRM-XXP	02~24P	
2EHDP-XXP	02~24P	
2EHDA-XXP	02~24P	
2EHDAC-XXP	02~24P	
Accessories		
EHDK1	P49	

2EHDV-XXP



2EHDVC-XXP



2EHDVM-XXP



2EHDR-XXP



2EHDRC-XXP



2EHDRM-XXP



2EHDP-XXP



2EHDA-XXP



2EHDAC-XXP



7.50mm

7EHDV-XXP

Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		6KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
7EHDV-XXP	02~12P	
7EHDVC-XXP	02~12P	
7EHDVM-XXP	02~12P	
7EHDR-XXP	02~12P	
7EHDRC-XXP	02~12P	
7EHDRM-XXP	02~12P	
Accessories		
EHDK1	P49	



7EHDVC-XXP



7EHDVM-XXP



7EHDR-XXP



7EHDRC-XXP



7EHDRM-XXP



7.62mm

3EHDV-XXP

Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		6KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
3EHDV-XXP	02~14P	
3EHDVC-XXP	02~14P	
3EHDVM-XXP	02~14P	
3EHDR-XXP	02~14P	
3EHDRC-XXP	02~14P	
3EHDRRC-XXP	02~14P	
3EHDRM-XXP	02~14P	
Accessories		
EHDK1	P49	



3EHDVC-XXP



3EHDVM-XXP



3EHDR-XXP



3EHDRC-XXP



3EHDRRC-XXP



3EHDRM-XXP



7.62mm

ECH762V-XXP

Technical Data	UL	IEC
Rated voltage	300V	1000V
Rated current	30A	41A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECH762V-XXP	02~12P	
ECH762VM-XXP	02~12P	
ECH762VTM-XXP	02~12P	
ECH762R-XXP	02~12P	
ECH762RM-XXP	02~12P	
ECH762RTM-XXP	02~12P	
Accessories		
ECHK2	P49	



ECH762VM-XXP



ECH762VTM-XXP



ECH762R-XXP



ECH762RM-XXP



ECH762RTM-XXP



7.62mm

ECH762RR-XXP

Technical Data	UL	IEC
Rated voltage	300V	1000V
Rated current	30A	41A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		6KV
Torque (N-m)		
Screw		
Number of Positions		
ECH762RR-XXP	02~12P	
ECH762RRM-XXP	02~12P	
ECH762RRT-XXP	02~12P	
Accessories		
ECHK2	P49	



ECH762RRM-XXP



ECH762RRT-XXP



7.62mm

ECH762HR-XXP

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	40A	41A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Number of Positions		
ECH762HR-XXP	02~12P	
ECH762HRR-XXP	02~12P	
Accessories		
ECHK2	P49	



ECH762HRR-XXP



2.50mm

Technical Data	UL	IEC
Rated voltage	150V	320V
Rated current	4A	4A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECHB250V-XXP	04~48P	
ECHB250R-XXP	04~48P	

ECHB250V-XXP



ECHB250R-XXP



3.50mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECHB350V-XXP	04~44P	
ECHB350VM-XXP	04~32P	
ECHB350R-XXP	04~44P	
ECHB350RM-XXP	04~32P	
Accessories		
ECHK1	P49	

ECHB350V-XXP



ECHB350VM-XXP



ECHB350R-XXP



ECHB350RM-XXP



3.81mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECHB381V-XXP	04~36P	
ECHB381VM-XXP	04~32P	
ECHB381R-XXP	04~36P	
ECHB381RM-XXP	04~32P	
Accessories		
ECHK1	P49	

ECHB381V-XXP



ECHB381VM-XXP



ECHB381R-XXP



ECHB381RM-XXP



3.81mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECHB381RRD-XXP	04~48P	
ECHB381RRM-XXP	04~48P	
Accessories		
ECHK1	P49	

ECHB381RRD-XXP



ECHB381RRM-XXP



5.00mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
5EHDBV-XXP	04~40P	
5EHDBVM-XXP	04~36P	
5EHDBR-XXP	04~40P	
5EHDBRM-XXP	04~36P	
Accessories		
EHDK1	P49	

5EHDBV-XXP



5EHDBVM-XXP



5EHDBR-XXP



5EHDBRM-XXP



5.08mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
2EHDBV-XXP	04~48P	
2EHDBVM-XXP	04~44P	
2EHDBR-XXP	04~48P	
2EHDBRM-XXP	04~44P	
Accessories		
EHDK1	P49	

2EHDBV-XXP



2EHDBVM-XXP



2EHDBR-XXP



2EHDBRM-XXP



3.50mm

EECH350V-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
EECH350V-XXP	04~32P	
EECH350VM-XXP	04~40P	
EECH350R-XXP	04~32P	
EECH350RM-XXP	04~40P	
Accessories		
ECHK1	P49	



EECH350VM-XXP



EECH350R-XXP



EECH350RM-XXP



3.81mm

EECH381V-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
EECH381V-XXP	04~36P	
EECH381VM-XXP	04~32P	
EECH381R-XXP	04~36P	
EECH381RM-XXP	04~32P	
Accessories		
ECHK1	P49	



EECH381VM-XXP



EECH381R-XXP



EECH381RM-XXP



5.00mm

5EEHDV-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
5EEHDV-XXP	04~56P	
5EEHDVM-XXP	04~44P	
5EEHDR-XXP	04~56P	
5EEHDRM-XXP	04~44P	
Accessories		
EHDK1	P49	



5EEHDVM-XXP



5EEHDR-XXP



5EEHDRM-XXP



5.08mm

2EEHDV-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
2EEHDV-XXP	04~48P	
2EEHDVM-XXP	04~48P	
2EEHDR-XXP	04~48P	
2EEHDRM-XXP	04~48P	
Accessories		
EHDK1	P49	



2EEHDVM-XXP



2EEHDR-XXP



2EEHDRM-XXP



Sockets – THR application



Pitch: 3.50mm / 3.81mm / 5.00mm / 5.08mm
UL Rated: 300V / 8A, 300V / 15A
IEC Rated: 320V / 14A, 600V / 18A

- PCB single-level socket for THR applications.
- Horizontal and vertical plug-in direction.
- Versions with and without side walls.
- Versions with threaded flange.

3.50mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECH350V-XXPL	02~24P	
ECH350VM-XXPL	02~24P	
ECH350VJ-XXPL	02~24P	
ECH350VT-XXPL	02~24P	
ECH350R-XXPL	02~24P	
ECH350RM-XXPL	02~24P	
ECH350RT-XXPL	02~24P	
ECH350RR-XXPL	02~24P	
ECH350RRM-XXPL	02~24P	
ECH350RJ-XXPL	02~24P	
Accessories		
ECH1L	P49	

ECH350V-XXPL



ECH350VM-XXPL



ECH350VJ-XXPL



ECH350VT-XXPL



ECH350R-XXPL



ECH350RM-XXPL



ECH350RT-XXPL



ECH350RR-XXPL



ECH350RRM-XXPL



ECH350RJ-XXPL



3.81mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		2.5KV
Rated impulse voltage		
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
ECH381V-XXPL	02~24P	
ECH381VM-XXPL	02~24P	
ECH381VJ-XXPL	02~24P	
ECH381R-XXPL	02~24P	
ECH381RM-XXPL	02~24P	
ECH381RR-XXPL	02~24P	
ECH381RRM-XXPL	02~24P	
ECH381RJ-XXPL	02~24P	
Accessories		
ECH1L	P49	

ECH381V-XXPL



ECH381VM-XXPL



ECH381VJ-XXPL



ECH381R-XXPL



ECH381RM-XXPL



ECH381RR-XXPL



ECH381RRM-XXPL



ECH381RJ-XXPL



5.00mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
5EHDV-XXPL	02~24P	
5EHDVC-XXPL	02~24P	
5EHDVM-XXPL	02~24P	
5EHDR-XXPL	02~24P	
5EHDRC-XXPL	02~24P	
5EHDRM-XXPL	02~24P	
5EHDRR-XXPL	02~24P	
5EHDRRC-XXPL	02~24P	
5EHDRRM-XXPL	02~24P	
Accessories		
EHDK1L	P49	

5EHDV-XXPL



5EHDVC-XXPL



5EHDVM-XXPL



5EHDR-XXPL



5EHDRC-XXPL



5EHDRM-XXPL



5EHDRR-XXPL



5EHDRRC-XXPL



5EHDRRM-XXPL



5.08mm

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
2EHDV-XXPL	02~24P	
2EHDVC-XXPL	02~24P	
2EHDVM-XXPL	02~24P	
2EHDR-XXPL	02~24P	
2EHDRC-XXPL	02~24P	
2EHDRM-XXPL	02~24P	
Accessories		
EHDK1L	P49	

2EHDV-XXPL



2EHDVC-XXPL



2EHDVM-XXPL



2EHDR-XXPL



2EHDRC-XXPL



2EHDRM-XXPL



2EHDRR-XXPL



2EHDRRC-XXPL



2EHDRRM-XXPL



Tape & Reel Packaging

For 3.50/3.81/5.0/5.08/7.62 mm Pitches

- Part number contains letter “L” meaning its suitable for reflow process.
  (e.g., 0156-24XXLWR, this item is suitable for reflow process.)
- Part number without “L” meaning its suitable for wave soldering.
- For headers with plug-in direction vertical to the PCB, pick up cap is included.

Pick up cap for vertical socket/header

T & R packaging in antistatic material

Customized tape, tube magazine packing by request

3.50mm

Technical Data	UL	IEC
Rated voltage	150V	320V
Rated current	8A	10A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque(N-m)		
Wire strip length		
Part Number	No. of pcs	Pcs/Pkt
0156-20XX-BK-WR	02~14P	200
0156-20XXLWR	02~14P	200
0156-21XX-BK-WR	04~34P	200
0156-21XXLWR	04~34P	200
0156-24XX-BK-WR	04~32P	200
0156-24XXLWR	04~32P	200
0156-25XX-BK-WR	04~36P	200
0156-25XXLWR	04~36P	200
0156-26XX-BK-WR	04~36P	200
0156-26XXLWR	04~36P	200
0156-29XX-BK-WR	04~32P	200
0156-29XXLWR	04~32P	200

0156-20XX-BK-WR 0156-20XXLWR



0156-21XX-BK-WR 0156-21XXLWR



0156-24XX-BK-WR 0156-24XXLWR



0156-25XX-BK-WR 0156-25XXLWR



0156-26XX-BK-WR 0156-26XXLWR



0156-29XX-BK-WR 0156-29XXLWR



3.50mm

Technical Data	UL	IEC
Rated voltage	150V	250V
Rated current	8A	8A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Part Number	No. of pcs	Pcs/Pkt
0159-11XXWR	04~40P	100
0159-11XXLWR	04~40P	100
0159-12XXWR	04~40P	100
0159-12XXLWR	04~40P	100
0159-31XXWR	04~40P	100
0159-31XXLWR	04~40P	100
0159-32XXWR	04~40P	100
0159-32XXLWR	04~40P	100

0159-11XXWR 0159-11XXLWR



0159-12XXWR 0159-12XXLWR



0159-31XXWR 0159-31XXLWR



0159-32XXWR 0159-32XXLWR



Part number with suffix "*" meaning its suitable for wave soldering, the housing is in green color.

Part number contains letter "L" meaning its suitable for reflow process, the housing is in black color.

Below part numbers are for wave soldering application, the housing in green color.

ECH350V-XXPWR
ECH350VM-XXPWR
ECH350VT-XXPWR
ECH350R-XXPWR
ECH350RM-XXPWR
ECH350RR-XXPWR
ECH350RRM-XXPWR
ECH381V-XXPWR
ECH381VM-XXPWR
ECH381R-XXPWR
ECH381RM-XXPWR
ECH381RR-XXPWR
ECH381RRM-XXPWR
5EHDV-XXPWE
5EHDVM-XXPWR
5EHDVC-XXPWR
5EHDR-XXPWR
5EHDRM-XXPWR
5EHDRR-XXPWR
5EHDRRC-XXPWR
5EHDRRM-XXPWR
2EHDV-XXPWE
2EHDVM-XXPWR
2EHDVC-XXPWR
2EHDR-XXPWR
2EHDRM-XXPWR
2EHDRC-XXPWR

3.50mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		

Part Number	No. of pcs	Pcs/Pkt
ECH350V-XXPWR	02~24P	300
ECH350V-XXPLWR	02~24P	300
ECH350VM-XXPWR	02~24P	300
ECH350VM-XXPLWR	02~24P	300
ECH350VT-XXPLWR	02~24P	300
ECH350R-XXPWR	02~24P	450
ECH350R-XXPLWR	02~24P	450
ECH350RM-XXPWR	02~24P	450
ECH350RM-XXPLWR	02~24P	450
ECH350RT-XXPLWR	02~24P	450
ECH350RR-XXPWR	02~24P	450
ECH350RR-XXPLWR	02~24P	450
ECH350RRM-XXPWR	02~24P	450
ECH350RRM-XXPLWR	02~24P	450

*ECH350V-XXPWR ECH350V-XXPLWR



*ECH350VM-XXPWR ECH350VM-XXPLWR



ECH350VT-XXPLWR



*ECH350R-XXPWR ECH350R-XXPLWR



*ECH350RM-XXPWR ECH350RM-XXPLWR



ECH350RT-XXPLWR



*ECH350RR-XXPWR ECH350RR-XXPLWR



*ECH350RRM-XXPWR ECH350RRM-XXPLWR



3.81mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	14A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		

Part Number	No. of pcs	Pcs/Pkt
ECH381V-XXPWR	02~24P	300
ECH381V-XXPLWR	02~24P	300
ECH381VM-XXPWR	02~24P	300
ECH381VM-XXPLWR	02~24P	300
ECH381R-XXPWR	02~24P	350
ECH381R-XXPLWR	02~24P	350
ECH381RM-XXPWR	02~24P	350
ECH381RM-XXPLWR	02~24P	350
ECH381RR-XXPWR	02~24P	350
ECH381RR-XXPLWR	02~24P	350
ECH381RRM-XXPWR	02~24P	350
ECH381RRM-XXPLWR	02~24P	350

*ECH381V-XXPWR ECH381V-XXPLWR



*ECH381VM-XXPWR ECH381VM-XXPLWR



*ECH381R-XXPWR ECH381R-XXPLWR



*ECH381RM-XXPWR ECH381RM-XXPLWR



*ECH381RR-XXPWR ECH381RR-XXPLWR



*ECH381RRM-XXPWR ECH381RRM-XXPLWR



Tape & Reel Packaging

5.00mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		

Part Number	No. of pcs	Pcs/Pkt
5EHDV-XXPWR	02~24P	200
5EHDV-XXPLWR	02~24P	200
5EHDVC-XXPWR	02~24P	200
5EHDVC-XXPLWR	02~24P	200
5EHDVM-XXPWR	02~24P	200
5EHDVM-XXPLWR	02~24P	200
5EHDR-XXPWR	02~24P	350
5EHDR-XXPLWR	02~24P	350
5EHDRC-XXPWR	02~24P	350
5EHDRC-XXPLWR	02~24P	350
5EHDRM-XXPWR	02~24P	350
5EHDRM-XXPLWR	02~24P	350
5EHDRR-XXPWR	02~24P	350
5EHDRR-XXPLWR	02~24P	350
5EHDRRC-XXPWR	02~24P	350
5EHDRRC-XXPLWR	02~24P	350
5EHDRRM-XXPLWR	02~24P	350

*5EHDV-XXPWR 5EHDV-XXPLWR



*5EHDVC-XXPWR 5EHDVC-XXPLWR



*5EHDVM-XXPWR 5EHDVM-XXPLWR



*5EHDR-XXPWR 5EHDR-XXPLWR



*5EHDRC-XXPWR 5EHDRC-XXPLWR



*5EHDRM-XXPWR 5EHDRM-XXPLWR



*5EHDRR-XXPWR 5EHDRR-XXPLWR



*5EHDRRC-XXPWR 5EHDRRC-XXPLWR



5EHDRRM-XXPLWR



5.08mm

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		

Part Number	No. of pcs	Pcs/Pkt
2EHDV-XXPWR	02~24P	200
2EHDV-XXPLWR	02~24P	200
2EHDVC-XXPWR	02~24P	200
2EHDVC-XXPLWR	02~24P	200
2EHDVM-XXPWR	02~24P	200
2EHDVM-XXPLWR	02~24P	200
2EHDR-XXPWR	02~24P	350
2EHDR-XXPLWR	02~24P	350
2EHDRC-XXPWR	02~24P	350
2EHDRC-XXPLWR	02~24P	350
2EHDRM-XXPWR	02~24P	350
2EHDRM-XXPLWR	02~24P	350

*2EHDV-XXPWR 2EHDV-XXPLWR



*2EHDVC-XXPWR 2EHDVC-XXPLWR



*2EHDVM-XXPWR 2EHDVM-XXPLWR



*2EHDR-XXPWR 2EHDR-XXPLWR



*2EHDRC-XXPWR 2EHDRC-XXPLWR



*2EHDRM-XXPWR 2EHDRM-XXPLWR



7.62mm

Technical Data	UL	IEC
Rated voltage	300V	800V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		6KV
Torque (N-m)		
Screw		
Wire strip length		

Part Number	No. of pcs	Pcs/Pkt
3EHDV-XXP	02~14P	200
3EHDVC-XXP	02~14P	200
3EHDVM-XXP	02~14P	200
3EHDR-XXP	02~14P	350
3EHDRC-XXP	02~14P	350
3EHDRM-XXP	02~14P	350

*3EHDV-XXPWR



*3EHDVC-XXPWR



*3EHDVM-XXPWR



*3EHDR-XXPWR



*3EHDRC-XXPWR



*3EHDRM-XXPWR



Tape & Reel Packaging

PID (Push-in Design) PCB Terminal Blocks

Connection method: Push-in connection

Pitch: 2.50mm / 2.54mm / 3.50mm / 3.81mm / 5.00mm / 5.08mm

UL Rated: 150V/5A~ 300V/10A

IEC Rated: 130V/6A~ 450V/17.5A

- Push-in connection single and double level PCB terminal blocks
- Horizontal, vertical and 45 degrees plug-in directions
- Versions with support pin for additional stability on PCB.
- Color identification for each individual pole is available by request.

The Push-in design adopts specially designed spring technology which allows fast and easy wiring free of tool. The structure is rigid, durable and takes moderate force to release the wire with a screwdriver.

2.50mm — 0188-01XXL / 0188-02XXL

Technical Data	UL	IEC
Rated voltage	150V	160V
Rated current	5A	6A
Solid (AWG/mm²)	26~18	0.2~0.5
Flexible (AWG/mm²)	26~18	0.2~0.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
0188-01XXL	02~20P	
0188-02XXL	02~20P	
0188-01XXSMD	02~20P	
0188-02XXSMD	02~20P	







0188-01XXSMD / 0188-02XXSMD







2.50mm — 0136-10XX

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	2A	2A
Solid (AWG/mm²)	28~20	0.2~0.5
Flexible (AWG/mm²)		0.2~0.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8mm	
Number of Positions		
0136-10XX	02~24P	



2.50mm — 0136-11XX

Technical Data	UL	IEC
Rated voltage	150V	130V
Rated current	2A	2A
Solid (AWG/mm²)	28~20	0.2~0.5
Flexible (AWG/mm²)		0.2~0.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	8mm	
Number of Positions		
0136-11XX	02~24P	



2.54mm — 0138-10XX

Technical Data	UL	IEC
Rated voltage	150V	130V
Rated current	5A	6A
Solid (AWG/mm²)	28~20	0.5
Flexible (AWG/mm²)	28~20	0.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	8mm	
Number of Positions		
0138-10XX	02~24P	
0138-11XX	02~24P	



2.54mm — 0138-11XX





2.54mm — 141V-XXP

Technical Data	UL	IEC
Rated voltage	150V	250V
Rated current	5A	12A
Solid (AWG/mm²)	26~20	0.5
Flexible (AWG/mm²)	26~20	0.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	10~11mm	
Number of Positions		
141V-XXP	02~20P	
141R-XXP	02~20P	





2.54mm — 141R-XXP





3.50mm — 0136-20XX

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	6A	8A
Solid (AWG/mm²)	28~16	0.2~0.75
Flexible (AWG/mm²)		0.2~0.75
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8mm	
Number of Positions		
0136-20XX	02~24P	



3.50mm — 0136-21XX

Technical Data	UL	IEC
Rated voltage	300V	130V
Rated current	6A	8A
Solid (AWG/mm²)	28~16	0.2~0.75
Flexible (AWG/mm²)		0.2~0.75
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	8mm	
Number of Positions		
0136-21XX	02~24P	



3.50mm — 0137-40XX / 0137-41XX

Technical Data	UL	IEC
Rated voltage	300V	130V
Rated current	5A	17.5A
Solid (AWG/mm²)	26~16	0.2~1.5
Flexible (AWG/mm²)	24~20	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	9mm	
Number of Positions		
0137-40XX	02~24P	
0137-41XX	02~24P	







3.50mm — 0138-50XX / 0138-50XXL / 0138-51XX / 0138-51XXL

Technical Data	UL	IEC
Rated voltage	300V	160V
Rated current	12A	17.5A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	9mm	
Number of Positions		
0138-50XX	02~24P	
0138-50XXL	02~24P	
0138-51XX	02~24P	
0138-51XXL	02~24P	





3.50mm — 0185-11XX / 0185-12XX

Technical Data	UL	IEC
Rated voltage	300V	200V
Rated current	10A	14A
Solid (AWG/mm²)	26~16	0.2~1.5
Flexible (AWG/mm²)	26~16	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0185-11XX	02~24P	
0185-12XX	02~24P	







3.81mm — 0141-01XX / 0141-22XX

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	10A	10A
Solid (AWG/mm²)	26~16	0.2~1.5
Flexible (AWG/mm²)	26~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	9mm	
Number of Positions		
0141-01XX	02~24P	
0141-22XX	02~24P	





3.50mm — 0151-01XX / 0151-02XX

Technical Data	UL	IEC
Rated voltage	300V	160V
Rated current	9A	14A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	10mm	
Number of Positions		
0151-01XX	02~24P	
0151-02XX	04~48P	





3.50mm — 0151-01XXL / 3.50mm — 0151-02XXL

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	10A	14A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	10mm	
Number of Positions		
0151-01XXL	02~24P	



Technical Data	UL	IEC
Rated voltage	300V	160V
Rated current	10A	14A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	10mm	
Number of Positions		
0151-02XXL	02~24P	



5.00mm — 0185-31XX / 0185-32XX

Technical Data	UL	IEC
Rated voltage	300V	200V
Rated current	10A	14A
Solid (AWG/mm²)	26~16	0.2~1.5
Flexible (AWG/mm²)	26~16	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0185-31XX	02~24P	
0185-32XX	02~24P	







5.00mm — 0137-11XX

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	10A	17.5A
Solid (AWG/mm²)	26~14	0.2~1.5
Flexible (AWG/mm²)	26~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	9~10mm	
Number of Positions		
0137-11XX	02~24P	



5.00mm — 0138-70XX / 0138-76XX

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	10A	17.5A
Solid (AWG/mm²)	26~14	0.2~1.5
Flexible (AWG/mm²)		0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	10mm	
Number of Positions		
0138-70XX	02~24P	
0138-76XX	02~24P	





5.00mm — 0152-01XX / 0152-02XX

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	10A	17.5A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0152-01XX	02~24P	
0152-02XX	04~48P	







5.00mm — 0153-01XX / 0153-02XX

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	20A	24A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	12~14mm	
Number of Positions		
0153-01XX	02~24P	
0153-02XX	04~48P	





5.08mm — 0138-60XX / 0138-60XXL / 0138-61XX / 0138-61XXL

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	12A	17.5A
Solid (AWG/mm²)	28~16	0.14~1.5
Flexible (AWG/mm²)	28~16	0.14~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0138-60XX	02~16P	
0138-60XXL	02~24P	
0138-61XX	02~16P	
0138-61XXL	02~24P	





5.08mm — 0141-21XX / 0141-24XX

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	10A	10A
Solid (AWG/mm²)	26~16	0.2~1.5
Flexible (AWG/mm²)	26~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	9mm	
Number of Positions		
0141-21XX	02~24P	
0141-24XX	02~24P	





5.08mm — 142V-XXP / 142R-XXP

Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	10A	17.5A
Solid (AWG/mm²)	22~14	0.5~1.5
Flexible (AWG/mm²)	22~14	0.5~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	9mm	6~7mm
Number of Positions		
142V-XXP	02~24P	
142R-XXP	02~24P	







10.00mm — 0152-41XX

Technical Data	UL	IEC
Rated voltage	300V	1000V
Rated current	10A	17.5A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0152-41XX	02~12P	



10.00mm — 0153-41XX

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	20A	24A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length	12~14mm	
Number of Positions		
0153-41XX	02~12P	



Front Entry PID Terminal Blocks

Pitch: 3.50mm / 5.00mm / 6.35mm / 7.50mm / 10.00mm
UL Rated: 300V / 10A ~ 600V / 66A
IEC Rated: 320V / 17.5A ~ 1000V / 76A

- 2 pins on each pole for excellent stability on PCB.
- Versions with horizontal and vertical wire entry direction.
- For stranded wire connection without ferrules, the clamp shall be opened by a screwdriver.



3.50mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	10A	17.5A
Solid (AWG/mm²)	26~16	0.2~1.5
Flexible (AWG/mm²)	26~16	0.2~1.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	9~10mm	
Number of Positions		
0177-31XX	02~24P	
0177-33XX	02~24P	

0177-31XX



0177-33XX



5.00mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	20A	24A
Solid (AWG/mm²)	26~12	0.2~2.5
Flexible (AWG/mm²)	26~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	9~10mm	
Number of Positions		
0177-51XX	02~12P	
0177-53XX	02~12P	

0177-51XX



0177-53XX



6.35mm

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	25A	32A
Solid (AWG/mm²)	24~10	0.2~4
Flexible (AWG/mm²)	24~10	0.2~4
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length	13mm	
Number of Positions		
0177-76XX	02~16P	
0177-78XX	02~16P	

0177-76XX



0177-78XX



7.50mm

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	36A	41A
Solid (AWG/mm²)	24~8	0.2~10
Flexible (AWG/mm²)	24~8	0.2~6
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length	15mm	
Number of Positions		
0177-86XX	02~16P	
0177-88XX	02~16P	

0177-86XX



0177-88XX



10.00mm

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	66A	76A
Solid (AWG/mm²)	20~4	0.75~16
Flexible (AWG/mm²)	20~4	0.75~16
Rated impulse voltage		8KV
Torque (N-m)		
Screw		
Wire strip length	18~20mm	
Number of Positions		
0177-06XX	02~12P	
0177-08XX	02~12P	

0177-06XX



0177-08XX



Screw Connection

PCB Type Terminal Blocks

Pitch: 3.50mm / 5.00mm / 6.35mm / 7.50mm / 10.00mm

UL Rated: 150V/10A~ 600V/65A

IEC Rated: 130V/8A~1000V/76A

- Versions with single, double and triple-level PCB terminal blocks.
- Horizontal, vertical and 45 degrees wire entry directions.
- Space saving and finger-safe housing design.
- Special markings on the housing for identification are available by request.

2.54mm — EK254V-XXP

Technical Data	UL	IEC
Rated voltage	150V	130V
Rated current	10A	8A
Solid (AWG/mm²)	28~16	0.5~1.5
Flexible (AWG/mm²)	28~16	0.5~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.2	
Screw	M1.6	
Wire strip length	5~6mm	
Number of Positions		
EK254V-XXP	02~16P	



3.50mm — EK350V-XXP

Technical Data	UL	IEC
Rated voltage	300V	130V
Rated current	10A	12A
Solid (AWG/mm²)	30~16	0.14~1.5
Flexible (AWG/mm²)	30~16	0.14~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.2	
Screw	M2	
Wire strip length	6~7mm	
Number of Positions		
EK350V-XXP	02~24P	



3.50mm — EK350V4L-XXP

Technical Data	UL	IEC
Rated voltage	300V	130V
Rated current	10A	10A
Solid (AWG/mm²)	30~16	0.5~1.5
Flexible (AWG/mm²)	30~16	0.5~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.2	
Screw	M2	
Wire strip length	6~7mm	
Number of Positions		
EK350V4L-XXP	04~40P	



3.81mm — EHK381V-XXP

Technical Data	UL	IEC
Rated voltage	300V	130V
Rated current	10A	8A
Solid (AWG/mm²)	26~16	0.5~1.5
Flexible (AWG/mm²)	26~16	0.5~1.5
Rated impulse voltage		4KV
Torque (N-m)	0.2	
Screw	M2	
Wire strip length	6~7mm	
Number of Positions		
EHK381V-XXP	02~16P	



3.81mm — EK381V-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	12A	12A
Solid (AWG/mm²)	30~16	0.5~1.5
Flexible (AWG/mm²)	30~16	0.5~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.2	
Screw	M2	
Wire strip length		
EK381V-XXP	6~7mm	
EEK381V-XXP	6~7mm	
E3K381V-XXP	5~6mm	
Number of Positions		
EK381V-XXP	02~24P	
EEK381V-XXP	02~24P	
E3K381V-XXP	02~24P	



EEK381V-XXP



E3K381V-XXP



3.81mm — EK381V4L-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	12A	12A
Solid (AWG/mm²)	30~16	0.5~1.5
Flexible (AWG/mm²)	30~16	0.5~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.2	
Screw	M2	
Wire strip length		
EK381V4L-XXP	6~7mm	
EK381V3L-XXP	4~5mm	
Number of Positions		
EK381V4L-XXP	04~48P	
EK381V3L-XXP	06~72P	



EK381V3L-XXP



3.81mm — ESK381V-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	12A	12A
Solid (AWG/mm²)	30~14	0.5~1.5
Flexible (AWG/mm²)	30~14	0.5~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.2	
Screw	M2	
Wire strip length	6~7mm	
Number of Positions		
ESK381V-XXP	02~24P	
ESK381R-XXP	02~24P	



ESK381R-XXP



3.81mm — EESK381V-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	12A	12A
Solid (AWG/mm²)	30~14	0.5~1.5
Flexible (AWG/mm²)	30~14	0.5~1.5
Rated impulse voltage		2.5KV
Torque (N-m)	0.2	
Screw	M2	
Wire strip length	6~7mm	
Number of Positions		
EESK381V-XXP	02~24P	
ESK381V4L-XXP	04~48P	



ESK381V4L-XXP



5.00mm — ELK500V-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	13.5A	17.5A
Solid (AWG/mm²)	30~16	0.14~1.5
Flexible (AWG/mm²)	30~16	0.14~1.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
ELK500V-XXP	02~24P	



5.00mm — ELK500S-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	13.5A	17.5A
Solid (AWG/mm²)	30~14	0.14~1.5
Flexible (AWG/mm²)	30~14	0.14~1.5
Rated impulse voltage		4KV
Torque (N-m)	0.4	
Screw	M2.5	
Wire strip length	6mm	
Number of Positions		
ELK500S-XXP	02~24P	



5.00mm — EK500A-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	20A	24A
Solid (AWG/mm²)	24~12	0.14~2.5
EK500A-XXP	24~12	0.14~2.5
EK500V-XXP	24~12	0.5~2.5
EK500R-XXP	24~12	0.5~2.5
Flexible (AWG/mm²)		
EK500A-XXP	24~12	0.14~2.5
EK500V-XXP	24~12	0.5~2.5
EK500R-XXP	24~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length		
EK500A-XXP	6mm	
EK500V-XXP	6mm	
EK500R-XXP	6~7mm	
Number of Positions	02~24P	



EK500V-XXP



EK500R-XXP



5.00mm — EK500V4L-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	20A	24A
Solid (AWG/mm²)	24~12	0.5~2.5
Flexible (AWG/mm²)	24~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
EK500V4L-XXP	04~48P	
EK500V2L-XXP	04~48P	
EK500V3L-XXP	06~72P	



EK500V2L-XXP



EK500V3L-XXP



5.00mm — E3K500V-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	20A	24A
Solid (AWG/mm²)	24~12	0.5~2.5
Flexible (AWG/mm²)	24~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
E3K500V-XXP	02~24P	
EEK500V-XXP	02~14P	



EEK500V-XXP



5.00mm — EHK5V-XXP

Technical Data	UL	IEC
Rated voltage	300V	300V
Rated current	25A	24A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	8mm	
Number of Positions		
EHK5V-XXP	02~24P	



5.00mm — EHK500R-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current		
EHK500R-XXP	25A	24A
E2HK500V-XXPAM	20A	24A
Solid (AWG/mm²)	24~12	0.5~2.5
Flexible (AWG/mm²)	24~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)		
EHK500R-XXP	0.5	
E2HK500V-XXPAM	0.4	
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
EHK500R-XXP	02~16P	
E2HK500V-XXPAM	02P、03P.....	



E2HK500V-XXPAM



5.00mm — EHK5V3L-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	20A	24A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
EHK5V3L-XXP	06~72P	



5.08mm — ELK508V-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	13.5A	14A
Solid (AWG/mm²)	30~16	0.5~1.5
Flexible (AWG/mm²)	30~16	0.5~1.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	5~6mm	
Number of Positions		
ELK508V-XXP	02~24P	



5.08mm — ELK508S-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	13.5A	17.5A
Solid(AWG/mm²)	30~14	0.14~1.5
Flexible (AWG/mm²)	30~14	0.14~1.5
Rated impulse voltage		4KV
Torque(N-m)	0.4	
Screw	M2.5	
Wire strip length	6mm	
Number of Positions		
ELK508S-XXP	02~24P	



5.08mm — E2LK508V-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	13.5A	13.5A
Solid (AWG/mm²)	30~14	0.2~1.5
Flexible (AWG/mm²)	30~14	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)	0.6	
Screw	M2.5	
Wire strip length	6mm	
Number of Positions		
E2LK508V-XXP	02~24P	



5.08mm — EELK508V-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	13.5A	14A
Solid (AWG/mm²)	26~18	0.5~1.5
Flexible (AWG/mm²)	26~18	0.5~1.5
Rated impulse voltage		4KV
Torque (N-m)	0.6	
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
EELK508V-XXP	04~18P	



5.08mm — EK508A-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	20A	24A
Solid (AWG/mm²)	24~12	0.14~2.5
Flexible (AWG/mm²)	24~12	0.14~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
EK508A-XXP	02~24P	



5.08mm — EK508V-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	20A	24A
Solid (AWG/mm²)	24~12	0.5~2.5
Flexible (AWG/mm²)	24~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
EK508V-XXP	02~24P	



5.08mm — EK508R-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	20A	10A
Solid (AWG/mm²)	24~12	0.5~2.5
Flexible (AWG/mm²)	24~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
EK508R-XXP	02~24P	



5.08mm — EK508V4L-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	20A	24A
Solid (AWG/mm²)	24~12	0.5~2.5
Flexible (AWG/mm²)	24~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
EK508V4L-XXP	04~48P	
EK508V2L-XXP	04~48P	
EK508V3L-XXP	06P、09P...up to 72P	
E3K508V-XXP	02P、03P...up to 24P	
EEK508V-XXP	02~15P	



EK508V2L-XXP



EK508V3L-XXP



E3K508V-XXP



EEK508V-XXP



5.08mm — EHK2V-XXP

Technical Data	UL	IEC
Rated voltage		
EHK2V-XXP	300V	300V
EHK508R-XXP	300V	250V
EEHK508V-XXP	300V	250V
Rated current	25A	24A
Solid (AWG/mm²)		
EHK2V-XXP	24~12	0.2~2.5
EHK508R-XXP	24~12	0.5~2.5
EEHK508V-XXP	24~12	0.5~2.5
Flexible (AWG/mm²)		
EHK2V-XXP	24~12	0.2~2.5
EHK508R-XXP	24~12	0.5~2.5
EEHK508V-XXP	24~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions	02~24P	

EHK508R-XXP

EEHK508V-XXP

5.08mm — E2HK508V-XXPAM

Technical Data	UL	IEC
Rated voltage		
E2HK508V-XXPAM	300V	250V
EHK508V2L-XXP	300V	450V
EHK508V3L-XXP	300V	450V
Rated current	25A	24A
Solid (AWG/mm²)	24~12	0.5~2.5
Flexible (AWG/mm²)	24~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)		
E2HK508V-XXPAM	0.4	
EHK508V2L-XXP	0.5	
EHK508V3L-XXP	0.5	
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
E2HK508V-XXP	02P、03P...up to 24P	
EHK508V2L-XXP	04P、06P...up to 48P	
EHK508V3L-XXP	06P、09P...up to 72P	

EHK508V2L-XXP

EHK508V3L-XXP



5.08mm — ESK508V-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	23A	24A
Solid (AWG/mm²)	26~12	0.5~2.5
Flexible (AWG/mm²)	26~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.8	
Screw	M3	
Wire strip length	10~11mm	
Number of Positions		
ESK508V-XXP	02~24P	



5.08mm — EESK508V-XXP

Technical Data	UL	IEC
Rated voltage	300V	400V
Rated current	20A	24A
Solid (AWG/mm²)	26~12	0.5~2.5
Flexible (AWG/mm²)	26~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M3	
Wire strip length	8~9mm	
Number of Positions		
EESK508V-XXP	02~16P	
E3SK508V-XXP	02~16P	
ESK508V4L-XXP	04~32P	
ESK508V3L-XXP	06~48P	



E3SK508V-XXP



ESK508V4L-XXP



ESK508V3L-XXP



6.35mm — ESK635V-XXP

Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	30A	32A
Solid (AWG/mm²)	26~10	0.2~4.0
Flexible (AWG/mm²)	26~10	0.2~4.0
Rated impulse voltage		4KV
Torque (N-m)	0.5~0.8	
Screw	M3	
Wire strip length	10~11mm	
Number of Positions		
ESK635V-XXP	02~12P	



6.35mm — EKB635V-XXP

Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	30A	32A
Solid (AWG/mm²)	30~10	0.2~4.0
Flexible (AWG/mm²)	30~10	0.2~4.0
Rated impulse voltage		4KV
Torque (N-m)	0.8	
Screw	M3	
Wire strip length	10~11mm	
Number of Positions		
EKB635V-XXP	04、06P...up to 48P	



6.35mm — EPK635VN-XXP

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	35A	41A
Solid (AWG/mm²)	18~8	0.2~6
Flexible (AWG/mm²)	18~8	0.2~6
Rated impulse voltage		8KV
Torque (N-m)	0.5	
Screw	M3	
Wire strip length	9~10mm	
Number of Positions		
EPK635VN-XXP	02~16P	



7.50mm EHK7V-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	25A	24A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		6KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	8mm	
Number of Positions		
EHK7V-XXP	02~16P	



7.50mm ESK750V-XXP

Technical Data	UL	IEC
Rated voltage	300V / 600V	750V
Rated current	30A / 5A	32A
Solid(AWG/mm²)	24~10	0.2~4.0
Flexible (AWG/mm²)	24~10	0.2~4.0
Rated impulse voltage		6KV
Torque(N-m)	0.6~1.4	
Screw	M3.5	
Wire strip length	10~11mm	
Number of Positions		
ESK750V-XXP	02~12P	



7.62mm EKB762V-XXP

Technical Data	UL	IEC
Rated voltage	300V / 600V	750V
Rated current	30A / 5A	32A
Solid (AWG/mm²)	24~10	0.2~4.0
Flexible (AWG/mm²)	24~10	0.2~4.0
Rated impulse voltage		4KV
Torque (N-m)	1.4	
Screw	M3.5	
Wire strip length	10~11mm	
Number of Positions		
EKB762V-XXP	04P - 06P.....	



7.62mm EHK3V-XXP

Technical Data	UL	IEC
Rated voltage	300V	600V
Rated current	25A	24A
Solid (AWG/mm²)	24~12	0.5~4
Flexible (AWG/mm²)	24~12	0.5~2.5
Rated impulse voltage		6KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	6~7mm	
Number of Positions		
EHK3V-XXP	02~16P	



7.62mm ESK762V-XXP

Technical Data	UL	IEC
Rated voltage	300V / 600V	750V
Rated current	30A / 5A	32A
Solid (AWG/mm²)	24~10	0.2~4.0
Flexible (AWG/mm²)	24~10	0.2~4.0
Rated impulse voltage		6KV
Torque (N-m)	0.6~1.4	
Screw	M3.5	
Wire strip length	10~11mm	
Number of Positions		
ESK762V-XXP	02~12P	



9.52mm EK950V-XXP

Technical Data	UL	IEC
Rated voltage	300V / 600V	1000V
Rated current	30A / 5A	32A
Solid (AWG/mm²)	26~10	0.5~4.0
Flexible (AWG/mm²)	26~10	0.5~4.0
Rated impulse voltage		8KV
Torque (N-m)	0.5~0.8	
Screw	M3	
Wire strip length	6~7mm	
Number of Positions		
EK950V-XXP	02~25P	



9.52mm EK950HVN-XXP

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	30A	32A
Solid (AWG/mm²)	26~10	0.2~4.0
Flexible (AWG/mm²)	26~10	0.2~4.0
Rated impulse voltage		8KV
Torque (N-m)	0.6	
Screw	M3	
Wire strip length	7~8mm	
Number of Positions		
EK950HVN-XXP	02~25P	



10.16mm ESK116V-XXP

Technical Data	UL	IEC
Rated voltage	300V / 600V	1000V
Rated current	65A / 5A	57A
Solid (AWG/mm²)	20~6	0.5~10
Flexible (AWG/mm²)	20~6	0.5~10
Rated impulse voltage		8KV
Torque (N-m)	1.8	
Screw	M4	
Wire strip length	10~11mm	
Number of Positions		
ESK116V-XXP	02P、03P.....	



10.16mm ESK116R-XXPAM

Technical Data	UL	IEC
Rated voltage	300V / 600V	750V
Rated current	65A / 5A	57A
Solid (AWG/mm²)	20~6	0.5~10
Flexible (AWG/mm²)	20~6	0.5~10
Rated impulse voltage		8KV
Torque (N-m)	1.8	
Screw	M4	
Wire strip length	11~12mm	
Number of Positions		
ESK116R-XXPAM	02P、03P.....	



10.16mm ESKW116V-XXP

Technical Data	UL	IEC
Rated voltage	300V	750V
Rated current	65A	57A
Solid (AWG/mm²)	22~6	0.5~10
Flexible (AWG/mm²)	22~6	0.5~10
Rated impulse voltage		6KV
Torque (N-m)	2.0	
Screw	M4	
Wire strip length	11~12mm	
Number of Positions		
ESKW116V-XXP	02P、03P.....	



10.16mm EPK116VN-XXP

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	57A / 65A	76A
Solid (AWG/mm²)	20~6	0.5~16
Flexible (AWG/mm²)	20~6	0.5~16
Rated impulse voltage		8KV
Torque (N-m)	1.2	
Screw	M4	
Wire strip length	12mm	
Number of Positions		
EPK116VN-XXP	02~16P	



15.00mm ESK150V-XXP

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	115A	125A
Solid (AWG/mm²)	20~2	0.5~35
Flexible (AWG/mm²)	20~2	0.5~35
Rated impulse voltage		8KV
Torque (N-m)	3.8	
Screw	M5	
Wire strip length	18mm	
Number of Positions		
ESK150V-XXP	02~09P	
ESK150VM-XXP	01~07P	



15.00mm ESK150VM-XXP



20.00mm ESK200VM-XXP

Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	200A	232A
Solid (AWG/mm²)	6~3/0	16~95
Flexible (AWG/mm²)	6~3/0	25~95
Rated impulse voltage		8KV
Torque (N-m)		
Screw	M8	
Wire strip length	25~26mm	
Number of Positions		
ESK200VM-XXP	01~06P	



Front Entry Screw Connection Terminal Blocks

Pitch: 5.00mm / 6.35mm / 7.50mm / 7.62mm / 10.00mm

- 2 pins on each pole for excellent stability on PCB.
- Versions with horizontal and vertical wire entry direction to the PCB.
- High current capacity up to 30A for 7.62mm pitch products.

5.00mm — DT-123VA-XXP

Technical Data	UL	IEC
Rated voltage	300V	300V
Rated current	20A / 26A	24A
Solid (AWG/mm²)	22~12	0.5~2.5
Flexible (AWG/mm²)	22~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	13~14mm	
Number of Positions		
DT-123VA-XXP	02~24P	



5.00mm — DT-123RA-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	20A / 26A	24A
Solid (AWG/mm²)	22~12	0.5~2.5
Flexible (AWG/mm²)	22~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	13~14mm	
Number of Positions		
DT-123RA-XXP	02~24P	



7.50mm — DT-123HVR-XXP

Technical Data	UL	IEC
Rated voltage	600V	750V
Rated current	20A	24A
Solid (AWG/mm²)	22~12	0.5~2.5
Flexible (AWG/mm²)	22~12	0.5~2.5
Rated impulse voltage		8KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	13~14mm	
Number of Positions		
DT-123HVR-XXP	02~24P	



7.50mm — DT-123VA-XXP3

Technical Data	UL	IEC
Rated voltage	300V	750V
Rated current	20A / 26A	24A
Solid (AWG/mm²)	22~12	0.5~2.5
Flexible (AWG/mm²)	22~12	0.5~2.5
Rated impulse voltage		6KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	13~14mm	
Number of Positions		
DT-123VA-XXP3	02~24P	



7.50mm — DT-123RA-XXP3

Technical Data	UL	IEC
Rated voltage	300V	500V
Rated current	20A / 26A	24A
Solid (AWG/mm²)	22~12	0.5~2.5
Flexible (AWG/mm²)	22~12	0.5~2.5
Rated impulse voltage		6KV
Torque (N-m)	0.5	
Screw	M2.5	
Wire strip length	13~14mm	
Number of Positions		
DT-123RA-XXP3	02~24P	



6.35mm — DT-2301-XXP / DT-2300-XXP

Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	30A	24A
Solid (AWG/mm²)	22~10	0.5~2.5
Flexible (AWG/mm²)	22~10	0.5~2.5
Rated impulse voltage		6KV
Torque (N-m)	0.6	
Screw	M3	
Wire strip length	13~14mm	
Number of Positions		
DT-2301-XXP	02~16P	
DT-2300-XXP	02~16P	





7.62mm — DT-2321-XXP / DT-2320-XXP

Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	30A	24A
Solid (AWG/mm²)	22~10	0.5~2.5
Flexible (AWG/mm²)	22~10	0.5~2.5
Rated impulse voltage		6KV
Torque (N-m)	0.6	
Screw	M3	
Wire strip length	13~14mm	
Number of Positions		
DT-2321-XXP	02~16P	
DT-2320-XXP	02~16P	





10.00mm — PDS-10-XX / PDS-10S-XX

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	65A	57A
Solid (AWG/mm²)	24~6	0.5~10
Flexible (AWG/mm²)	24~6	0.5~10
Rated impulse voltage		4KV
Torque (N-m)	1.2	
Screw	M4	
Wire strip length	12~13mm	
Marking label	TM28	
Number of Positions		
PDS-10-XX	01P、02P、03P.....	
PDS-10S-XX	01P、02P、03P.....	





10.00mm — PDS-10A-XX / PDS-10SA-XX

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current		
Solid (AWG/mm²)	24~6	0.5~10
Flexible (AWG/mm²)	24~6	0.5~10
Rated impulse voltage		4KV
Torque (N-m)	1.2~1.5	
Screw	M4	
Wire strip length	12~13mm	
Marking label	TM28	
Number of Positions		
PDS-10A-XX	01P、02P、03P.....	
PDS-10AS-XX	01P、02P、03P.....	





Spring Clamp Connection

PCB Type Terminal Blocks



Pitch: 2.50mm / 5.00mm / 5.08mm / 7.50mm / 10mm

UL Rated: 300V/4A~ 300V/57A

IEC Rated: 130V/6A~ 450V/76A

- Versions with single, double, triple and four-level PCB terminal blocks
- Colored marking of individual pole is available by request.

2.50mm — WKA250A-XXP

Technical Data	UL	IEC
Rated voltage	300V	130V
Rated current	4A	6A
Solid (AWG/mm²)	28~20	0.5
Flexible (AWG/mm²)		0.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	5~6mm	
Number of Positions		
WKA250A-XXP	02P、03P、04P.....	
WKV250A-XXP	02P、03P、04P.....	



WKV250A-XXP



2.54mm — WKA254A-XXP

Technical Data	UL	IEC
Rated voltage	300V	130V
Rated current	4A	6A
Solid (AWG/mm²)	28~20	0.5
Flexible (AWG/mm²)		0.5
Rated impulse voltage		2.5KV
Torque (N-m)		
Screw		
Wire strip length	5~6mm	
Number of Positions		
WKA254A-XXP	02P、03P、04P.....	
WKV254A-XXP	02P、03P、04P.....	



WKV254A-XXP



5.00mm — WKA500-XXP

Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	24A
Solid (AWG/mm²)	28~12	0.5~2.5
Flexible (AWG/mm²)	28~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	5~6mm	
Number of Positions		
WKA500-XXP	02P、03P、04P.....	



5.00mm — WKK500-XXP

Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	10A	24A
Solid (AWG/mm²)	28~12	0.5~2.5
Flexible (AWG/mm²)	28~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	6~7mm	
Number of Positions		
WKK500-XXP	02P、04P、06P、08P.....	
W3K500-XXP	06P、09P、12P.....	
W4K500-XXP	08P、12P、16P.....	



W3K500-XXP



W4K500-XXP



5.00mm — WKA500-XXPL

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	15A	24A
Solid (AWG/mm²)	28~12	0.2~2.5
Flexible (AWG/mm²)	28~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	5~6mm	
Number of Positions		
WKA500-XXPL	02~12P	



5.08mm — WKA508-XXP

Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	24A
Solid (AWG/mm²)	28~12	0.5~2.5
Flexible (AWG/mm²)	28~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	5~6mm	
Number of Positions		
WKA508-XXP	02P、03P、04P.....	



5.08mm — WKK508-XXP

Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	10A	24A
Solid (AWG/mm²)	28~12	0.5~2.5
Flexible (AWG/mm²)	28~12	0.5~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	6~7mm	
Number of Positions		
WKK508-XXP	02P、04P、06P、08P.....	
W3K508-XXP	06P、09P、12P.....	
W4K508-XXP	08P、12P、16P.....	



W3K508-XXP



W4K508-XXP



5.00mm — WKA50B-XXP

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	10A	17.5A
Solid (AWG/mm²)	24~16	0.2~1.5
Flexible (AWG/mm²)	24~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	9~10mm	
Number of Positions		
WKA50B-XXP	02P、03P.....	



5.00mm — WSKA500S-XXP

Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	15A	24A
Solid (AWG/mm²)	28~12	0.5~4
Flexible (AWG/mm²)		0.5~4
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	10~11mm	
Number of Positions		
WSKA500S-XXP	02P、03P.....	



7.50mm — WSKA750S-XXP

Technical Data	UL	IEC
Rated voltage	300V	750V
Rated current	30A	41A
Solid (AWG/mm²)		0.5~6
Flexible (AWG/mm²)	26~10	0.5~6
Rated impulse voltage		6KV
Torque (N-m)		
Screw		
Wire strip length	14~15mm	
Number of Positions		
WSKA750S-XXP	02P、03P.....	



10.00mm — WSKA100-XXP

Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	57A	76A
Solid (AWG/mm²)	24~6	0.5~16
Flexible (AWG/mm²)	24~6	0.5~16
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	14~15mm	
Number of Positions		
WSKA100-XXP	02P、03P.....	



PCB Terminal Blocks For Electronic Housing Applications

Pitch: 5.08mm / 9.00mm / 12.5mm
UL Rated: 300V / 8A, 300V / 15A
IEC Rated: 320V / 10A, 320V / 20A, 600V / 15A

The terminal block design aims to increase the density of connections on PCB while using as less space as possible, the terminal pins are situated at a right angle of the wire entry direction.

- Connection methods include elevated wire cage and PID (Push-in Design).
- Versions with LED light pipe on 0171 series.
- 5ESDT plug (p. 30) is the mating plug for 5EH-XXP sockets.

5.08mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	8A	10A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	8~9mm	
Number of Positions		
0228-21XX	04~40P	
0228-22XX	04~40P	
0228-23XX	04~40P	

0228-21XX



0228-22XX



0228-23XX



9.00mm

Technical Data	UL	IEC
Number of Positions		
0171-10XX	300V	320V
0171-11XX	300V	320V
0171-60XX	300V	630V
Rated current		
0171-10XX	8A	14A
0171-11XX	8A	14A
0171-60XX	8A	15A
Solid (AWG/mm²)	28~16	0.2~1.5
Flexible (AWG/mm²)	28~16	0.2~1.5
Rated impulse voltage		
0171-10XX		4KV
0171-11XX		4KV
0171-60XX		6KV
Wire strip length	7~8mm	
Number of Positions		
0171-10XX	02~08P	
0171-11XX	02~08P	
0171-60XX	01~04P	

0171-10XX

No marking



0171-11XX

With marking



0171-60XX



12.50mm

Technical Data	UL	IEC
Rated voltage	300V	320V
Rated current	15A	20A
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length	9~10mm	
Number of Positions		
0171-20XX	02~08P	
0171-21XX	02~08P	

0171-20XX

No marking



0171-21XX

With marking



5.00mm

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	10A	18A
Solid (AWG/mm²)	22~14	0.2~2.5
Flexible (AWG/mm²)	22~14	0.2~2.5
Rated impulse voltage	2KV	4KV
Torque (N-m)	0.4	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
5ES-2PL	02P	
5ES-3PL	03P	
5ES-4PL	04P	
5ES-2PR	02P	
5ES-3PR	03P	
5ES-4PR	04P	

5ES-2PL



5ES-3PL



5ES-4PL



5ES-2PR



5ES-3PR



5ES-4PR



5.00mm

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	15A	18A
Solid (AWG/mm²)		
Flexible (AWG/mm²)		
Rated impulse voltage		4KV
Torque (N-m)		
Screw		
Wire strip length		
Number of Positions		
5EH-2PL	02P	
5EH-3PL	03P	
5EH-4PL	04P	
5EH-2PR	02P	
5EH-3PR	03P	
5EH-4PR	04P	

5EH-2PL



5EH-3PL



5EH-4PL



5EH-2PR



5EH-3PR



5EH-4PR



5.00mm

Technical Data	UL	IEC
Rated voltage	300	320
Rated current	20	24
Solid (AWG/mm²)	24~12	0.2~2.5
Flexible (AWG/mm²)	24~12	0.2~2.5
Rated impulse voltage		2KV
Torque (N-m)		
Screw		
Wire strip length	10~11mm	
Number of Positions		
0189-20XPL	02~04P	
0189-20XPR	02~04P	

0189-20XPL



0189-20XPR



7.50mm

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	20A	24A
Solid (AWG/mm²)	30~12	0.2~2.5
Flexible (AWG/mm²)	30~12	0.2~2.5
Rated impulse voltage		6KV
Torque (N-m)	0.4	
Screw	M2.5	
Wire strip length	7~8mm	
Number of Positions		
7ES-3PL	03P	
7ES-3PR	03P	

7ES-3PL



7ES-3PR





5ES and 5EH series terminal blocks are designed specifically for electronic housing DMEN type.

5ES series are PCB type terminal blocks, and is adopting elevated wire cage with screw connection.

5EH series are headers(sockets) which are compatible with 5ESDT plug (P. 29). Please pay attention to identify left and right side features when using this product range. Please visit www.dinkle.com for more information on electronic housing DMEN type.

Panel Feed-through Terminal Blocks

Cross section: 4~95mm²
UL Rated: 300V / 30A ~ 600V / 230A
IEC Rated: 400V / 41A ~ 1000V / 232A

- Screw connection with elevated wire cage on both sides of the terminal blocks.
- Easy installation, simply to engage the two terminal halves and then interlock them securely.
-Finger safe housing design.



Specification

Technical Data	UL	IEC
Rated voltage	300V	400V
Rated current	30A	41A
Wire range (AWG/mm²)	30~10	0.2~6
Rated impulse voltage	6KV	
Torque (N-m)	0.6	
Screw	M3	
Wire strip length	9mm	
Insulating material	PA	
Outer dimension	T x H x W (mm)	
PPACN-4	8.1 x 21 x 20	
PPACNV-4	8.1 x 21 x 24.5	
Inner dimension T x H x W (mm)	8.1 x 21 x 15	
Marking label	TM22	

Mounting panel 1.0~2.5mm 400V 2.5~4.0mm 320V — Plastic panel 500V

PPACN-4



PPACNV-4



Specification

Technical Data	UL	IEC
Rated voltage	300V	500V
Rated current	65A	76A
Wire range (AWG/mm²)	24~6	0.5~16
Rated impulse voltage	6KV	
Torque (N-m)	1.7	
Screw	M4	
Wire strip length	10mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	10.1 x 31 x 24.5	
Inner dimension T x H x W (mm)	10.1 x 28.5 x 18	
Marking label	TM22 / TM38	

Mounting panel 1.0~2.5mm 500V 2.5~4.0mm 320V — Plastic panel 500V

PPACN-10

Specification

Technical Data	UL	IEC
Rated voltage	300V	500V
Rated current	65A	76A
Wire range (AWG/mm²)	24~6	0.5~16
Rated impulse voltage	6KV	
Torque (N-m)	1.5	
Screw	M4	
Wire strip length	10mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	10.1 x 31 x 24.5	
Inner dimension T x H x W (mm)	10.1 x 28.5 x 18	
Marking label	TM22	

Mounting panel 1.0~2.5mm 500V 2.5~4.0mm 320V — Plastic panel 500V

PPACN-10Z

Specification

Technical Data	UL	IEC
Rated voltage	300V	500V
Rated current	65A	76A
Wire range (AWG/mm²)	24~6	0.5~16
Rated impulse voltage	6KV	
Torque (N-m)	0.5	
Screw	M4	
Wire strip length	10mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	10.1 x 30.5 x 31	
Inner dimension T x H x W (mm)	10.1 x 28.5 x 18	
Marking label	TM22	

Mounting panel 1.0~2.5mm 500V 2.5~4.0mm 320V — Plastic panel 500V

PPACNV-10



Specification

Technical Data	UL	IEC
Rated voltage	300V	500V
Rated current	65A	76A
Wire range (AWG/mm²)	24~6	0.5~16
Rated impulse voltage	6KV	
Torque (N-m)	1.5	
Screw	M4	
Wire strip length	10mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	10.1 x 30.5 x 31	
Inner dimension T x H x W (mm)	10.1 x 28.5 x 18	
Marking label	TM22	

Mounting panel 1.0~2.5mm 500V 2.5~4.0mm 320V — Plastic panel 500V

PPACNV-10Z



Specification

Technical Data	UL	IEC
Rated voltage	600V	500V
Rated current	85A	101A
Wire range (AWG/mm²)	22~4	0.5~25
Rated impulse voltage	6KV	
Torque (N-m)	3.4	
Screw	M5	
Wire strip length	16mm	
Insulating material	PA	
Outer dimension	T x H x W (mm)	
PPAC-16	12.1 x 40 x 34.6	
PPACV-16	12.1 x 39.7 x 38.1	
PPACV-16Z	12.1 x 39.7 x 38.1	
Inner dimension T x H x W (mm)	12.1 x 38.1 x 28.9	
Marking label	TM28	

PPAC-16



PPACV-16



PPACV-16Z



Specification

Technical Data	UL	IEC
Rated voltage	600V	800V
Rated current	115A	125A
Wire range (AWG/mm²)	8~2	6~35
Rated impulse voltage	6KV	
Torque (N-m)	3.4~3.9	
Screw	M5	
Wire strip length	19mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	15.1 x 48.5 x 38.5	
Inner dimension T x H x W (mm)	15.1 x 45 x 30	
Marking label	TM28	

Mounting panel 5.0~6.0mm 630V 1.0~5.0mm 800V — Plastic panel 800V

PPAC-25



Specification

Technical Data	UL	IEC
Rated voltage	300V	400V
Rated current	115A	125A
Wire range (AWG/mm²)	8~2	6~35
Rated impulse voltage	8KV	
Torque (N-m)		
Screw	M5	
Wire strip length	19mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	15.1x71x38.5	
Inner dimension T x H x W (mm)	15.1x33.3x27.5	
Marking label	TM28	

PPAC-25MAS



Specification

Technical Data	UL	IEC
Rated voltage	600V	800V
Rated current	150A	150A
Wire range (AWG/mm²)	6~1/0	16~50
Rated impulse voltage	8KV	
Torque (N-m)	5.9	
Screw	M6	
Wire strip length	24mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	18.8 x 54 x 43	
Inner dimension T x H x W (mm)	18.8 x 55 x 35	
Marking label	TM28	

Mounting panel 1.0~2.5mm 800V 2.5~6.0mm 630V — Plastic panel 800V

PPAC-50



Specification

Technical Data	UL	IEC
Rated voltage	300V	400V
Rated current	150A	150A
Wire range (AWG/mm²)	6~1/0	16~50
Rated impulse voltage	8KV	
Torque (N-m)		
Screw	M6	
Wire strip length	24mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	15.8x78x43	
Inner dimension T x H x W (mm)	18.8x37x33.9	
Marking label	TM28	

PPAC-50MAS



Specification

Technical Data	UL	IEC
Rated voltage	600V	630V
Rated current	230A	232A
Wire range (AWG/mm²)	4~4/0	25~95
Rated impulse voltage	8KV	
Torque (N-m)	14.7	
Screw	M8	
Wire strip length	27mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	25 x 74 x 50	
Inner dimension T x H x W (mm)	25 x 74 x 45	
Marking label	TM28	

Mounting panel Plastic panel 630V
1.0~5.0mm 630V
5.0~6.0mm 500V

PPAC-95



Specification

Technical Data	UL	IEC
Rated voltage	600V	630V
Rated current	230A	232A
Wire range (AWG/mm²)	4~4/0	25~95
Rated impulse voltage	8KV	
Torque (N-m)	14.7	
Screw	M8	
Wire strip length	27mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	25 x 100 x 50	
Inner dimension T x H x W (mm)	25 x 74 x 45	
Marking label	TM28	

Mounting panel Plastic panel 630V
1.0~5.0mm 630V
5.0~6.0mm 500V

PPAC-95M



Specification

Technical Data	UL	IEC
Rated voltage	300V	630V
Rated current	230A	232A
Wire range (AWG/mm²)	4~4/0	25~95
Rated impulse voltage	8KV	
Torque (N-m)	14.7	15
Screw	M8	
Wire strip length	27mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	25 x 100 x 50	
Inner dimension T x H x W (mm)	25 x 50 x 40.45	
Marking label	TM28	

PPAC-95MAS





Specification

Technical Data	UL	IEC
Rated voltage	300V	400V
Rated current	30A	41A
Wire range (AWG/mm²)	30~10	0.2~6
Rated impulse voltage	6KV	
Torque (N-m)		
Screw	M3	
Wire strip length	9mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	8.1x22.5x24.5	
Inner dimension T x H x W (mm)	8.1x21x15	
Marking label	TM22	

PPACNVH-4



Specification

Technical Data	UL	IEC
Rated voltage	300V	400V
Rated current	65A	76A
Wire range (AWG/mm²)	24~6	0.5~16
Rated impulse voltage	6KV	
Torque (N-m)	1.7	
Screw	M4	
Wire strip length	10mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	10.1 x 31 x 24.5	
Inner dimension T x H x W (mm)	10.1 x 25 x 16.9	
Marking label	TM22	

PPACN-10AS





Specification

Technical Data	UL	IEC
Rated voltage	300V	400V
Rated current	65A	76A
Wire range (AWG/mm²)	24~6	0.5~16
Rated impulse voltage	6KV	
Torque (N-m)	1.7	
Screw	M4	
Wire strip length	10mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	10.1 x 30.5 x 31	
Inner dimension T x H x W (mm)	10.1 x 25 x 16.9	
Marking label	TM22	

PPACNV-10AS



Specification

Technical Data	UL	IEC
Rated voltage	300V	500V
Rated current	85A	101A
Wire range (AWG/mm²)	22~4	0.5~25
Rated impulse voltage	6KV	
Torque (N-m)	2.9	
Screw	M5	
Wire strip length	16mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	12.1 x 40 x 34.6	
Inner dimension T x H x W (mm)	12.1 x 26 x 25.4	
Marking label	TM28	

PPAC-16AS



Specification

Technical Data	UL	IEC
Rated voltage	300V	500V
Rated current	85A	101A
Wire range (AWG/mm²)	22~4	0.5~25
Rated impulse voltage	6KV	
Torque (N-m)	2.9	
Screw	M5	
Wire strip length	16mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	12.1 x 39.7 x 38.1	
Inner dimension T x H x W (mm)	12.1 x 26 x 25.4	
Marking label	TM28	

PPACV-16AS



Specification

Technical Data	UL	IEC
Rated voltage	300V	400V
Rated current	115A	125A
Wire range (AWG/mm²)	8~2	6~35
Rated impulse voltage	6KV	
Torque (N-m)	3.38~3.9	4
Screw	M5	
Wire strip length	19mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	15.1 x 48.5 x 38.5	
Inner dimension T x H x W (mm)	15.1 x 33.3 x 27.5	
Marking label	TM28	

PPAC-25AS





Specification

Technical Data	UL	IEC
Rated voltage	300V / 600V	400V
Rated current	150A / 5A	150A
Wire range (AWG/mm²)	6~1/0	16~50
Rated impulse voltage	8KV	
Torque (N-m)	6	
Screw	M6	
Wire strip length	24mm	
Insulating material	PA	
Outer dimension T x H x W (mm)	18.8 x 54 x 43	
Inner dimension T x H x W (mm)	18.8 x 37 x 33.9	
Marking label	TM28	

PPAC-50AS



Index

Part number	Page
01	
0136-10XX	77
0136-11XX	77
0136-20XX	77
0136-21XX	77
0137-11XX	79
0137-40XX	78
0137-41XX	78
0138-10XX	77
0138-11XX	77
0138-50XX	78
0138-50XXL	78
0138-51XX	78
0138-51XXL	78
0138-60XX	80
0138-60XXL	80
0138-61XX	80
0138-61XXL	80
0138-70XX	80
0138-76XX	80
0141-01XX	79
0141-21XX	81
0141-22XX	79
0141-24XX	81
0150-20XX	24
0150-21XX	24
0150-26XX	24
0150-30XX	25
0150-31XX	25
0150-36XX	25
0150-40XX	25
0150-46XX	25
0151-01XX	78
0151-01XXL	78
0151-02XX	78
0151-02XXL	78
0152-01XX	80
0152-02XX	80
0152-41XX	81
0153-01XX	80
0153-02XX	80
0153-41XX	81
0156-10XX	3
0156-10XXL	3
0156-12XX	3
0156-12XXL	3
0156-13XX	3
0156-13XXL	3
0156-15XX	3
0156-15XXL	3
0156-16XX	3
0156-16XXL	3
0156-17XX	3
0156-17XXL	3
0156-18XX	3
0156-18XXL	3
0156-19XX	3
0156-19XXL	3
0156-1AXX-BK	3
0156-1BXX-BK	3
0156-1CXX-BK	3
0156-1DXX-BK	3
0156-20XX-BK	4
0156-20XXL	4
0156-20XX-BK-WR	71
0156-20XXLWR	71
0156-21XX-BK	4
0156-21XXL	4
0156-21XX-BK-WR	71
0156-21XXLWR	71
0156-24XX-BK	4
0156-24XXL	4
0156-24XX-BK-WR	71
0156-24XXLWR	71
0156-25XX-BK	4
0156-25XXL	4
0156-25XX-BK-WR	71
0156-25XXLWR	71
0156-26XX-BK	4
0156-26XXL	4
0156-26XX-BK-WR	71
0156-26XXLWR	71
0156-29XX-BK	4
0156-29XXL	4
0156-29XX-BK-WR	71
0156-29XXLWR	71
0156-2AXX-BK	4
0156-2BXX-BK	4
0156-2CXX-BK	4
0156-2DXX-BK	4
0159-01XX	5
0159-03XX	5
0159-04XX	5
0159-11XX	5
0159-11XXL	5
0159-11XXWR	71
0159-11XXLWR	71
0159-12XX	5
0159-12XXL	5
0159-12XXWR	71
0159-12XXLWR	71
0159-31XX	5
0159-31XXL	5
0159-31XXWR	71
0159-31XXLWR	71
0159-32XX	5
0159-32XXL	5
0159-32XXWR	71
0159-32XXLWR	71
0159K1L	5
0161-01XX	23
0161-02XX	23
0161-03XX	23
0161-04XX	23
0161-11XX	23
0161-12XX	23
0161-13XX	23
0161-14XX	23
0162-01XX	51
0162-11XX	51
0162-A1XX	51
0164-01XX	51
0164-01XX(T)	51
0164-11XX	51
0164-A1XX	51
0164-A1XX(T)	51
0171-10XX	97
0171-11XX	97
0171-20XX	97
0171-21XX	97
0171-60XX	97
0177-06XX	83
0177-08XX	83
0177-31XX	82
0177-33XX	82
0177-51XX	82
0177-51XXP3	83
0177-53XX	82
0177-53XXP3	83
0177-76XX	83
0177-78XX	83
0177-86XX	83
0177-88XX	83
0181-A1XX	22
0181-A3XX	22
0183-01XX	47
0183-01XXTXX	47
0183-11XX	47
0183-11XXTXX	47
0184-11XX	31
0184-12XX	31
0184-13XX	31
0184-14XX	31
0184-31XX	31
0184-32XX	31
0184-33XX	31
0184-34XX	31
0184-51XX	30
0184-52XX	30
0184-53XX	30
0184-54XX	30
0184-81XX	30
0184-82XX	30
0184-83XX	30
0184-84XX	30
0185-11XX	79
0185-12XX	79
0185-31XX	79
0185-32XX	79
0187-A4XX	48
0188-01XXL	76
0188-01XXSMD	76
0188-02XXL	76
0188-02XXSMD	76
0189-20XPL	98
0189-20XPR	98
0191-01XX	32
0191-01XXC	32
0191-02XX	32
0191-02XXC	32
0191-06XX	32
0191-06XXC	32
0191-11XXTH	32
0191-12XXTH	32
0191-16XXTH	32
02	
0221-20XX	6
0221-21XX	7
0221-22XX-BK	6
0221-22XXL	6
0221-23XXL	6
0221-24XX	7
0221-25XX-BK	6
0221-25XXL	6
0221-26XXL	7
0221-27XX-BK	7
0221-27XXL	7
0221-28XX	7
0221-33XX-BK	8
0221-33XXL	8
0221-35XXL	7
0221-36XXL	7
0221-39XX-BK	8
0221-39XXL	8
0221-41XX-BK	6
0221-41XXL	6
0221-42XX	8
0221-43XX	8
0221-44XX	8
0221-51XX-BK	8
0221-51XXL	8
0221-52XX-BK	8
0221-52XXL	8
0225-01XX	12
0225-02XX	12
0225-03XX	12
0225-04XX	11
0225-05XX	11
0225-06XX	13
0225-07XX	13
0225-08XX	13
0225-09XX	11
0225-0AXX	11
0225-11XX	12
0225-12XX	12
0225-16XX	13
0225-16XXL	13
0225-17XX	13
0225-17XXL	13
0225-21XX	12
0225-22XX	12
0225-26XX	13
0225-26XXL	13
0225-27XX	13
0225-27XXL	13
0225-31XX	12
0225-32XX	12
0225-36XX	13
0225-36XXL	13
0225-37XX	13
0225-37XXL	13
0225-46XX	11
0225-47XX	11
0225-56XX	11
0225-57XX	11
0225-66XX	11
0225-67XX	11
0225-76XX	11
0225-77XX	11
0226-01XX	14
0226-02XX	14
0226-03XX	14
0226-06XX	15
0226-07XX	15
0226-08XX	15
0226-11XX	14
0226-12XX	14
0226-16XX	15
0226-16XXL	15
0226-17XX	15
0226-17XXL	15
0226-21XX	14
0226-22XX	14
0226-26XX	15
0226-26XXL	15
0226-27XX	15
0226-27XXL	15
0226-31XX	14
0226-32XX	14
0226-36XX	15
0226-36XXL	15
0226-37XX	15
0226-37XXL	15
0227-01XX	16
0227-02XX	16
0227-03XX	16
0227-04XX	16
0227-06XX	17
0227-07XX	17
0227-08XX	17
0227-09XX	17
0227-11XX	16
0227-12XX	16
0227-16XX	17
0227-16XXL	17
0227-17XX	17
0227-17XXL	17
0227-21XX	16
0227-22XX	16
0227-26XX	17
0227-26XXL	17
0227-27XX	17
0227-27XXL	17
0227-31XX	16
0227-32XX	16
0227-36XX	17
0227-36XXL	17
0227-37XX	17
0227-37XXL	17
0228-21XX	97
0228-22XX	97
0228-23XX	97
1	
141R-XXP	77
141V-XXP	77
142R-XXP	81
142V-XXP	81
2	
2EEHDR-XXP	64
2EEHDRM-XXP	65
2EEHDV-XXP	64
2EEHDVM-XXP	64
2EHDA-XXP	58
2EHDAC-XXP	58
2EHDBR-XXP	62
2EHDBRM-XXP	63
2EHDBV-XXP	62
2EHDBVM-XXP	62
2EHDP-XXP	58
2EHDR-XXP	59
2EHDR-XXPL	69
2EHDR-XXPWR	75
2EHDR-XXPLWR	75
2EHDRC-XXP	59
2EHDRC-XXPL	69
2EHDRC-XXPWR	75
2EHDRC-XXPLWR	75
2EHDRD-XXP	54
2EHDRDM-XXP	54
2EHDRR-XXPL	68
2EHDRRC-XXPL	68
2EHDRRM-XXPL	68
2EHDRM-XXP	59
2EHDRM-XXPL	69
2EHDRM-XXPWR	75
2EHDRM-XXPLWR	75
2EHDRS-XXP	54
2EHDRSM-XXP	54
2EHDV-XXP	58
2EHDV-XXPL	68
2EHDV-XXPWR	74
2EHDV-XXPLWR	74
2EHDVC-XXP	58
2EHDVC-XXPL	68
2EHDVC-XXPWR	74
2EHDVC-XXPLWR	74
2EHDVM-XXP	58
2EHDVM-XXPL	68
2EHDVM-XXPWR	74
2EHDVM-XXPLWR	74
2ESDA-XXP	39
2ESDAM-XXP	40
2ESDB-XXP	28
2ESDBA-XXP	28
2ESDBAM-XXP	29
2ESDBM-XXP	29
2ESDCR-XXP	53
2ESDCRM-XXP	53
2ESDCV-XXP	53
2ESDCVM-XXP	53
2ESDF-XXP	39
2ESDFM-XXP	39
2ESDL-XXP	40
2ESDP-XXP	39
2ESDPL-XXP	40
2ESDPLM-XXP	40
2ESDPM-XXP	39
2ESDS-XXP	28
2ESDSM-XXP	29
2ESDSR-XXP	28
2ESDSRM-XXP	29
2ESDSV-XXP	18
2ESDSVK-XXP	19
2ESDSVM-XXP	19
2ESDV-XXP	39
2ESDVB-XXP	40
2ESDVBM-XXP	40
2ESDVM-XXP	39
2ESH-XXP	52
2ESHM-XXP	52
2ESR-XXP	20
2ESRK-XXP	20
2ESRM-XXP	20
2ESS-XXP	20
2ESSM-XXP	20
2ESV-XXP	20
2ESVK-XXP	20
2ESVM-XXP	20
3	
3EHDR-XXP	61
3EHDR-XXPWR	75
3EHDRC-XXP	61

Part number	Page
3EHDRC-XXPWR	75
3EHDRRC-XXP	61
3EHDRM-XXP	61
3EHDRM-XXPWR	75
3EHDV-XXP	60
3EHDV-XXPWR	74
3EHDVC-XXP	60
3EHDVC-XXPWR	74
3EHDVM-XXP	60
3EHDVM-XXPWR	74
3ESDHM-XXP	54
3ESDP-XXP	42
3ESDPL-XXP	42
3ESDPLM-XXP	42
3ESDPM-XXP	42
3ESDS-XXP	30
3ESDSM-XXP	30
3ESDSR-XXP	30
3ESDSRM-XXP	30
3ESDV-XXP	42
3ESDVM-XXP	42
3ESH-XXP	54
3ESNP-XXP	45
3ESNPL-XXP	45
3ESNPHL-XXP	45
3ESNPLM-XXP	46
3ESNPLS-XXP	45
3ESNPLSM-XXP	46
3ESNPM-XXP	46
3ESNPS-XXP	45
3ESNPSM-XXP	46
4	
5	
5EEHDR-XXP	64
5EEHDRM-XXP	65
5EEHDV-XXP	64
5EEHDVM-XXP	64
5EH-2PL	98
5EH-2PR	99
5EH-3PL	98
5EH-3PR	99
5EH-4PL	98
5EH-4PR	99
5EHDBR-XXP	62
5EHDBRM-XXP	63
5EHDBV-XXP	62
5EHDBVM-XXP	62
5EHDK-XXP/T	58
5EHDKM-XXP/T	59
5EHDKPM-XXP	59
5EHDR-XXP	57
5EHDR-XXPL	69
5EHDR-XXPWR	75
5EHDR-XXPLWR	75
5EHDRC-XXP	57
5EHDRC-XXPL	69
5EHDRC-XXPWR	75
5EHDRC-XXPLWR	75
5EHDRM-XXP	57
5EHDRM-XXPL	69
5EHDRM-XXPWR	75
5EHDRM-XXPLWR	75
5EHDRR-XXP	58
5EHDRR-XXPL	68
5EHDRR-XXPWR	74
5EHDRR-XXPLWR	74
5EHDRRC-XXP	58
5EHDRRC-XXPL	68
5EHDRRC-XXPWR	74
5EHDRRC-XXPLWR	74
5EHDRRM-XXPL	68
5EHDRRM-XXPLWR	74
5EHDV-XXP	56
5EHDV-XXPL	68
5EHDV-XXPWR	74
5EHDV-XXPLWR	74
5EHDVC-XXP	56
5EHDVC-XXPL	68
5EHDVC-XXPWR	74
5EHDVC-XXPLWR	74
5EHDVM-XXP	56
5EHDVM-XXPL	68
5EHDVM-XXPWR	74
5EHDVM-XXPLWR	74
5ES-2PL	98
5ES-2PR	99
5ES-3PL	98
5ES-3PR	99
5ES-4PL	98
5ES-4PR	99
5ESDA-XXP	37
5ESDAM-XXP	38
5ESDF-XXP	37
5ESDFM-XXP	37
5ESDG-XXP	52
5ESDP-XXP	37
5ESDPL-XXP	38
5ESDPLM-XXP	38
5ESDPM-XXP	38
5ESDS-XXP	28
5ESDSM-XXP	29
5ESDSR-XXP	28
5ESDSRM-XXP	29
5ESDT-XXP	38
5ESDV-XXP	38
5ESDVM-XXP	38
5ESN-XXP	54
5ESR-XXP	18
5ESRK-XXP	19
5ESRM-XXP	18
5ESV-XXP	18
5ESVK-XXP	18
5ESVM-XXP	18
6	
7	
7EHDR-XXP	61
7EHDRC-XXP	61
7EHDRM-XXP	61
7EHDV-XXP	60
7EHDVC-XXP	60
7EHDVM-XXP	60
7ES-3PL	98
7ES-3PR	98
7ESDP-XXP	41
7ESDPL-XXP	41
7ESDPLM-XXP	41
7ESDPM-XXP	41
7ESDV-XXP	41
7ESDVM-XXP	41
C	
CPC350-XXP	52
CSC-01XX	49
D	
DT-123HVR-XXP	92
DT-123RA-XXP	92
DT-123RA-XXP3	92
DT-123VA-XXP	92
DT-123VA-XXP3	92
DT-2300-XXP	93
DT-2301-XXP	93
DT-2320-XXP	93
DT-2321-XXP	93
E	
E2HK500V-XXPAM	87
E2HK508V-XXPAM	89
E2LK508V-XXP	87
E3K381V-XXP	85
E3K500V-XXP	86
E3K508V-XXP	89
E3SK508V-XXP	89
EC116V-XXP	48
EC116VM-XXP	48
EC350CR-XXP	53
EC350CV-XXP	53
EC350F-XXP	35
EC350FM-XXP	35
EC350R-XXP	34
EC350RL-XXP	34
EC350RLM-XXP	34
EC350RM-XXP	34
EC350V-XXP	34
EC350VM-XXP	34
EC381CR-XXP	53
EC381CV-XXP	53
EC381F-XXP	35
EC381FM-XXP	35
EC381L-XXP	36
EC381LM-XXP	36
EC381R-XXP	34
EC381RL-XXP	34
EC381RLM-XXP	34
EC381RM-XXP	34
EC381V-XXP	34
EC381VK-XXP	37
EC381VM-XXP	34
EC508F-XXP	36
EC508FM-XXP	36
EC508V-XXP	36
EC508VM-XXP	36
EC762HV-XXP	46
EC762HVM-XXP	47
EC762HVN-XXP	46
EC762HVNM-XXP	47
EC762V-XXP	46
EC762VM-XXP	47
EC762VN-XXP	46
EC762VNM-XXP	47
ECH116L-XXP	48
ECH116R-XXP	49
ECH116RM-XXP	48
ECH116HVSXXP	48
ECH116V-XXP	48
ECH250R-XXP	55
ECH250V-XXP	55
ECH350H-XXP	57
ECH350R-XXP	56
ECH350R-XXPL	67
ECH350R-XXPWR	73
ECH350R-XXPLWR	73
ECH350RM-XXP	57
ECH350RM-XXPL	66
ECH350RM-XXPWR	73
ECH350RM-XXPLWR	73
ECH350RR-XXP	57
ECH350RR-XXPL	67
ECH350RR-XXPWR	72
ECH350RR-XXPLWR	72
ECH350RRM-XXP	57
ECH350RRM-XXPL	67
ECH350RRM-XXPWR	72
ECH350RRM-XXPLWR	72
ECH350RJ-XXPL	67
ECH350RT-XXPL	67
ECH350RT-XXPLWR	73
ECH350V-XXP	56
ECH350V-XXPL	66
ECH350V-XXPWR	72
ECH350V-XXPLWR	72
ECH350VM-XXP	56
ECH350VM-XXPL	67
ECH350VM-XXPWR	72
ECH350VM-XXPLWR	72
ECH350VJ-XXPL	67
ECH350VT-XXPL	67
ECH350VT-XXPLWR	73
ECH381A-XXP	56
ECH381AM-XXP	56
ECH381H-XXP	57
ECH381R-XXP	56
ECH381R-XXPL	67
ECH381R-XXPWR	73
ECH381R-XXPLWR	73
ECH381RG-XXP	57
ECH381RJ-XXPL	66
ECH381RM-XXP	57
ECH381RM-XXPL	67
ECH381RM-XXPWR	73
ECH381RM-XXPLWR	73
ECH381RR-XXP	57
ECH381RR-XXPL	67
ECH381RR-XXPWR	73
ECH381RR-XXPLWR	73
ECH381RRM-XXP	57
ECH381RRM-XXPL	67
ECH381RRM-XXPWR	73
ECH381RRM-XXPLWR	73
ECH381V-XXP	56
ECH381V-XXPL	66
ECH381V-XXPWR	72
ECH381V-XXPLWR	72
ECH381VM-XXP	56
ECH381VM-XXPL	66
ECH381VM-XXPWR	72
ECH381VM-XXPLWR	72
ECH381VJ-XXPL	66
ECH508R-XXP	58
ECH508RM-XXP	59
ECH508V-XXP	58
ECH508VM-XXP	58
ECH762HR-XXP	61
ECH762HRR-XXP	61
ECH762R-XXP	61
ECH762RM-XXP	61
ECH762RR-XXP	60
ECH762RRM-XXP	60
ECH762RRT-XXP	60
ECH762RTM-XXP	61
ECH762V-XXP	60
ECH762VM-XXP	60
ECH762VTM-XXP	60
ECHB250R-XXP	62
ECHB250V-XXP	62
ECHB350R-XXP	63
ECHB350RM-XXP	63
ECHB350V-XXP	63
ECHB350VM-XXP	63
ECHB381R-XXP	62
ECHB381RM-XXP	63
ECHB381RRD-XXP	63
ECHB381RRM-XXP	63
ECHB381V-XXP	62
ECHB381VM-XXP	62
ECHG1	57
ECHK1	49
ECHK1L	49
ECHK2	49
ECHP381V-XXP	56
ECSH381V-XXP	52
ED130F-XXP	50
ED130R-XXP	50
EDH130-21XX	50
EDH130-21XXTHT	50
EDH130F-XXTH126	50
EDH130F-XX/12.6	50
EECH350R-XXP	64
EECH350RM-XXP	65
EECH350V-XXP	64
EECH350VM-XXP	64
EECH381R-XXP	64
EECH381RM-XXP	65
EECH381V-XXP	64
EECH381VM-XXP	64
EEHK508V-XXP	88
EEK381V-XXP	85
EEK500V-XXP	86
EEK508V-XXP	89
EELK508V-XXP	86
EESK381V-XXP	84
EESK508V-XXP	88
EHDK1	49
EHDK1L	49
EHK2V-XXP	88
EHK381V-XXP	84
EHK3V-XXP	91
EHK500R-XXP	87
EHK508V2L-XXP	89
EHK508V3L-XXP	89
EHK5V-XXP	87
EHK5V3L-XXP	86
EHK7V-XXP	90
EK254V-XXP	84
EK350V-XXP	85
EK350V4L-XXP	85
EK381V-XXP	85
EK381V3L-XXP	85
EK381V4L-XXP	84
EK500A-XXP	86
EK500R-XXP	86
EK500V2L-XXP	87
EK500V3L-XXP	87
EK500V4L-XXP	87
EK500V-XXP	86
EK508A-XXP	86
EK508R-XXP	87
EK508V-XXP	87
EK508V2L-XXP	88
EK508V3L-XXP	88
EK508V4L-XXP	88
EK950V-XXP	91
EK950HVN-XXP	91
EKB635V-XXP	88
EKB762V-XXP	91
ELK500S-XXP	85
ELK500V-XXP	85
ELK508S-XXP	87
ELK508V-XXP	86
EPK116VN-XXP	91
EPK635VN-XXP	89
ESC250V-XXP	26
ESC350V-XXP	27
ESC350VM-XXP	27
ESC381V-XXP	27
ESC381VK-XXP	27
ESC381VM-XXP	27
ESC508V-XXP	28
ESC508VM-XXP	29
ESDK1	49
ESDK2	49
ESK116R-XXPAM	90
ESK116V-XXP	90
ESK150V-XXP	90
ESK150VM-XXP	90
ESK200VM-XXP	91
ESK381R-XXP	85
ESK381V4L-XXP	84
ESK381V-XXP	85
ESK508V-XXP	88
ESK508V3L-XXP	89
ESK508V4L-XXP	89
ESK635V-XXP	88
ESK750V-XXP	90
ESK762V-XXP	90

Part number	Page
ESKW116V-XXP	91
F	
FDC508B-XXP	43
FDC508B1-XXP	43
FDC508B3-XXP	43
FDC508BM-XXP	43
FDCH508R-XXP	43
FDCH508RM-XXP	43
G~O	
P	
PDS-10-XX	93
PDS-10A-XX	93
PDS-10S-XXP	93
PDS-10SA-XX	93
PPAC-16	101
PPAC-16AS	102
PPAC-25	101
PPAC-25AS	102
PPAC-25MAS	101
PPAC-50	101
PPAC-50AS	102
PPAC-50MAS	101
PPAC-95	102
PPAC-95M	102
PPAC-95MAS	103
PPACN-10	100
PPACN-10AS	102
PPACN-10Z	100
PPACN-4	100
PPACNV-4	100
PPACNV-10	101
PPACNV-10AS	102
PPACNV-10Z	101
PPACV-16	101
PPACV-16AS	102
PPACV-16Z	101
PPACNVH-4	103
S	
SDH-002	25
SDH-003	25
T~V	
W	
W3K500-XXP	95
W3K508-XXP	95
W4K500-XXP	95
W4K508-XXP	95
WKA250A-XXP	94
WKA254A-XXP	95
WKA500-XXP	94
WKA500-XXPL	94
WKA50B-XXP	94
WKA508-XXP	94
WKK500-XXP	95
WKK508-XXP	95
WKV250A-XXP	95
WKV254A-XXP	95
WSKA100-XXP	95
WSKA500S-XXP	94
WSKA750S-XXP	95