

() ,
INTERSTATE COUNCIL FOR STANDARDIZATION, METROLOGY AND CERTIFICATION
(ISC)

32601-2022
(ISO 13709:2009)

,

**(ISO 13709:2009, «Centrifugal pumps for petroleum,
petrochemical and natural gas industries», MOD)**

2022

32601—2022

1.0 «
 1.2 «
 »
 1 ()
 2 245 « »
 3
 (31 2022 . 149-)

(3166) 004—97	(3166) 004—97	
	BY KZ KG RU UZ UA	« »

4 2022 . 578- 32601—2022 (ISO 13709:2009) 7
 1 2023 .

5 ISO 13709:2009 «
 » («Centrifugal pumps for petroleum, petrochemical and natural gas industries», MOD).
 (, ,),
 /

1.5 (3.6).

6 32601—2013

() -

, , -

, . -

, « - »

© ISO, 2009

© . « », 2022



32601—2022

1	1
2	1
3	3
4	7
4.1	7
4.2	7
5	15
5.1	15
5.2	15
5.3	15
6	15
6.1	15
6.2	20
6.3	21
6.4	24
6.5	28
6.6	34
6.7	36
6.8	38
6.9	41
6.10	53
6.11	58
6.12	58
6.13	64
7	65
7.1	65
7.2	67
7.3	().....	69
7.4	- 72	
7.5 72	
7.6 74	
8 74	
8.1 74	
8.2 75	
8.3 78	
8.4 84	
9 86	
9.1 86	
9.2	(1, 2, 5)..... 87	
9.3	(VS1-VS7)..... 92	
10 98	
10.1 98	
10.2 98	
10.3 102	
() 104	
() 105	
() 111	
D () ().....	115	
() 117	
F () 119	
G () 128	

()	130
I ()	142
J ()	147
()	152
L ()	157
()	164
N ()	169
()	().....	170
()	177
.....	178

32601—2022

(•)

Centrifugal pumps for petroleum, petrochemical and natural gas industries.
General technical requirements

— 2023—03—01

1

() , -
) , -
(4.2. 9 -
-
:
- ()—1,9 (275 psi; 19,0) ;
- ()—0,5 (75 psi; 5,0) ;
- — 150 °C (300 °F);
- — 3600 / ;
- — 120 (400) ;
- — 330 (13").
— 34252 [1], -
, — [2].

2

:
12.2.003 .
12.2.062 .
356 , .
977 .

32601—2022

1050				-
1412	1940-1			1.
4543				
5632				
6134—2007 (9906:1999)			
7512				
8479				-
8724 (261-98)			
9454				-
9567				
ISO 10684				
14782				
16093 (965-1:1998, 965-3:1998)			
ISO 17769-1				-
18442				
18855 (281—89)			
()			
19281				
21105				
22247				-
24069 (3117—77)			
24705 (724:1993)			-
31252 (3740:2000)			
31320 (11342:1998)			
31610.0	(IEC 60079-0:2004)			
0.				
32600	(ISO 21049:2004)			-
33259—2015				-
PN 250.				
34233.1				
34252	(ISO 15783:2002)			

II

(www.easc.by)

3

		17769,	-
3.1	(similar pump):	,	-
3.2	(vertical in-line pump):	,	-
3.3	VS6 VS7 (1) (vertically suspended pump):	,	-
3.4	« » (barrel pump): (« »).	,	-
3.5	(allowable operating region):	;	-
3.6	(throat bushing):	(-
3.7	(normal-wear part):	,	-
3.8	(purchaser):	()	-
		;	-
		: « » —	-
3.9	(identical pump):	,	-
3.10	available):	NPSHA NPSHa (net positive suction head	-
3.11		() n_{ss} (suction-specific speed):	-

32601—2022

3.12	(cartridge-type element):	-
3.13	(classically stiff rotor):	-
- 20 %		
- 30 %		
3.14	(unit responsibility):	-
		-
		-
		-
		-
3.15	(drive-train component):	-
		-
3.16	(overhung pump):	-
3.17	(witnessed test, witnessed	
inspection):		
3.18	(observed inspection,	
observed test):		-
		-
3.19	(double casing):	-
		-
		-
3.20	(axially split):	-
3.21	(radially split):	-
3.22	(pressure casing):	-
		-
		-
3.23	(critical speed):	-
3.24	« » (wet critical speed):	-

3.25	« »	(dry critical speed):	-
3.26		(maximum suction pressure):	-
3.27		(maximum discharge pressure):	-
3.28	pressure):	(maximum dynamic sealing	-
3.29	MAWP:	(maximum allowable working pressure);	-
3.30		(maximum operating temperature):	-
3.31	pressure):	(maximum static sealing	-
3.32	driver):	(trip speed, electric motor	-
3.33	speed driver):	(trip speed, variable-	-
3.34		(minimum allowable speed):	-
3.35		(minimum design metal temperature):	-
3.36		(rated operating point):	-
)		-

32601—2022

3.37		; DN (diametre nominal)	NPS (nominal pipe size):	-
	— DN		, a NPS —	
3.38		(datum elevation):		-
	(NPSH).			
3.39		(data sheets):		-
	—	()		-
(final data sheets)				-
			6.1.2	
			6.1.8	
	NPSH3.			
3.40		(relative density, specific gravity):		-
	4 °C.			
	—		4 °C (39,2 °F)	
1000 / ³.				
3.41		(total indicator reading, total indicated runout); TIR:		-
	—			
	TIR			
3.42		(vendor):		-
3.43		(preferred operating region):		-
3.44		(normal operating point):	(-),	-
	—			-
				(-
				« -
	»	6.1.13		
3.45		(operating region):		-
3.46		(hydraulic power recovery turbine); HPRT:		-
			(-
)	
3.47		(element bundle):		-
	(),	
3.48		(oil-mist lubrication):		-
				-

32601—2022

3.49 (pure oil-mist lubrication, dry sump): (-),

3.50 (purge oil-mist lubrication, wet sump): ,

3.51 (stage): - () .

3.52 ; (best efficiency point): (—), ()

— -

3.53 (bidder): -

4

4.1

4.2

4.2.1

1.

1—

	-			1
				2
			—	
	-		—	4
			—	5
			—	6
-	-		—	1
			—	2
	-		—	
				4
				5

32601—2022

1

				VS1	
				VS2	
				VS3	
				()	VS4
					VS5
				—	VS6
				—	VS7
				-	
				-	


4.2.2

4.2.2.1

1 (. 1)

1.

(. 6.2).




1 — 1

4.2.2.2

2 (. 2)

2.



2 — 2

4.2.2.3

(. 3)




Рисунок 3 — Насос типа OH3

4.2.2.4

4 (. 4)

4.

(. 6.2).




Рисунок 4 — Насос типа OH4

4.2.2.5

5 (. 5)

5.

(. 6.2).




Рисунок 5 — Насос типа OH5

32601—2022

4.2.2.6

6 (. 6)

6.





Рисунок 6 — Насос типа OH6

4.2.2.7

1 (. 7)


1.




4.2.2.8

2 (. 8)

2.



4.2.2.9 (. 9)



4.2.2.10 4 (. 10)

4.

(. 6.2).




Рисунок 10 — Насос типа ВВ4

4.2.2.11 5 (. 11)

са («баррельные» насосы) обозначаются как ВВ5.





Рисунок 11 — Насос типа ВВ5

32601—2022

4.2.2.12 VS1 (. 12)


VS1.



12 — VS1

4.2.2.13 VS2 (. 13)


VS2.



13 — VS2

4.2.2.14 VS3 (. 14)


VS3.



14 — VS3

4.2.2.15 VS4 (. 15)

() VS4.




15 — VS4

32601—2022

4.2.2.16

VS5 (. 16)

VS5.




16 — VS5

4.2.2.17

VS6 (. 17)

VS6.




17 — VS6

4.2.2.18

VS7 (. 18)

VS7.



18 — VS7

5

5.1

USC, (. ,) , , -
USC, USC, , -
USC. , -

5.2

5.3

5.3.1

(. , /) , , -
5.3.2 , , 9, 9. , -

6

6.1

6.1.1 (. ,) ,

20 [f) 10.2.3] 3 , -

32601—2022

• 6.1.2

6.1.3

6.1.4

5 %

()

6.1.5

)

)

105 %

6.1.6

6.1.7

(

6.1.8

(NPSH3)

55 °C (130 °F),

(NPSHA)

(NPSH3).

1) . 32600 [3].

NPSHA

n_{ss}

NPSH3.

NPSHA

NPSH3,

NPSHA

NPSH3

« »,

• 6.1.9

n_{ss}

6.1.10

6134—2007 (1_)\

),

6134—2007 (

L).

[4] [5]

• 6.1.11

10 %.

6.1.12

70 % 120 %

80 % 110 %

n_s (.).

n_s

« »

(—).

110 %

105 %

(. 10.2.4).

1) . [4] [5].

32601—2022

6.9.3.1.

6.1.13

()

• 6.1.14

6.1.15
(300 . .)

200 (650)

31252^.

225

()

3 %

6 % —

(6.1.6). , %,

$$= 100 (R_2 - R^{\wedge}) / R_v \quad (1)$$

R_2 —

()

$I_{?_1}$ —

V-

) 8.3.3.7.

(. 10.3.4.1).

6.1.16

3600 / /

300 (-400 . .)

• 6.1.17

6.1.18

6.1.19

6.1.20

()

2.

1) . [6] [7].

2 —

		USC
	1,5—2,5 /	5—8 /
(MAWP),	700	100 psi; 7
(> 1,5 MAWP),	1 050	150 psi; 10,5
	100	15 psi; 1
	30 °C	90 °F
	50 °C	120 °F
	20 °C	30 °F
	0,35 ² /	0,002 h-ft ² -°R/Btu
()	3,0	0,125"

6.1.21

• 6.1.22

(,),
31610.0^Λ,

() ()

6.1.23

(,),

6.1.24

(,)

6.1.25

6.1.26

6.9.3,

6.1.27

6.1.28

(,)

1) [8] [9].

32601—2022

6.1.29

• 6.1.29.1 8724, 24705, 16093¹⁾.

6.1.29. 2 123)

2

6.1.29. 3

8724^{3) >}

6.1.30

6g

6

6.1.31 4).

6.1.32

6.1.33

1,5

()

10 (3/8)

6 (1/4)

6.1.34

12 (1/2).

6.2

6.2.1 3

3

3—

— 1	-) (6.3.5).)		MAWP (6.3.11).
4	-) —))	(7.1.7 7.1.8). (6.9.1.3).	-
	d)	(6.10.1.1).	(6.6.9 6.8.5).
— 5	-) -))	(7.1.7 7.1.8).	(6.8.2).

1) . [10] [11].

2) . [11].

3) . [10].

4) . [12].

3

)	(6.9.1.3).	
	-)	(6.9.1.3).	
4	-) —)	(6.3.3 6.3.10). (6.1.24).	
) (-)	(6.8.2).	

6.3

6.3.1

()

• 6.3.2

():

)

;

)

)

)—)

—

)—)

6.3.3

)

)

6.5.4,

)

(.8.3.2).

—

6.5.4.

6.3.4

25 %

67 %

(MAWP).

32601—2022

4.2 () () -
 ISO, ASTM, UNS, EN, JIS),
 .2 (),
 1 —) 6.3.3
 (),
 ()) -
 2 —
 , , 0,5 0,7 -
 4 —

/	0,8
	0,9
	0,9
	1,0

6.3.5 (MAWP) 6.3.6, -
 6.3.2), 10 % , (. 6.3.1
 ;
)
 , PN 16 PN 20¹⁾ -
 , 356
) 4,0 (40 , 600 psi) 38 °C (100 °F) —
 1 — 125²⁾
 PN 20³⁾ PN 16 PN 16 356, 150⁴⁾ -
 PN 20^{5>} PN 16 356.
 2 —
 3 — 6).
 6.1.4 - 10 % 6.1.5 -
 (. ,) 8.3.3.3).
 4 — 300⁷⁾
 PN 50⁸⁾ PN 40 356.

- 1) . [13] [14].
- 2) . [15].
- 3> . [13].
- 4) . [16] [17].
- 5) . [14].
- 6) . [18].
- 7) . [16] [17].
- 8) . [14].

32600^.

• 6.3.6 (5), (4) 6) (VS),

6.3.7 6.1.1. 3 (0,12).

6.3.8

350 (3,5 , 50 psi).

6.3.9

) 200 °C (400 °F)

) 0,7

) 10 (100 , 1450 psi).

• 6.3.10 «

VS, VS, 9.3.2.3. .1 ()

32600^

[175 °C (350 °F)].

6.3.11 1 9.2.1.2.

1) [3].

32601—2022

6.3.12 Ra 1,6 (63
0,8 (32
3
(0,12), 2 (0,08) 1,5 (0,06) 30°

6.3.13

6.3.14

6.3.15

6.3.16

6.4

6.4.1

6.4.1.1 28338. DN32, DN65, DN90, DN125, DN175
DN225 (NPS 1 %, NPS 2 %, NPS 3 ¹, NPS 5, NPS 7 NPS 9)

- 6.4.1.2 DN15 (NPS %) DN50 (NPS 2)
DN80 (NPS 3)
DN20 (NPS %). :
DN15 (NPS 16)

6.4.2

6.4.2.1

6.4.2.2 6.4.2.4, 33259—2015[^]. DN 200 (NPS 8) PN20 (125) PN40 (250).


1) [13], [15], [19].

6.4.2.3		6.4.2.4,	-
PN40	33259—2015 (. 6.3.5)	PN 50 ¹⁾	
33259—2015 ²⁾			
PN40	—	³⁾ PN50 ¹⁾	
PN40	33259—2015.		
6.4.2.4			-
()	33259—2015		-
			-
6.4.2.5			-
)	(-
6.4.2.6			-
		0,5°	-
6.4.3			
• 6.4.3.1		6.4.2.2	6.4.2.3.
	()		-
			-
• 6.4.3.2			
55 °C (130 °F)			
• 6.4.3.3			(
			-
			-
19.			
6.4.3.4			/
6.4.3.5			
(. 8.3.2).			
6.4.3.6			-
6.4.3.7			-
		621 7 ⁴⁾ .	
	6211 ⁵⁾		
	—	[21] [22]	-
6211.			
• 6.4.3.8			-
	6357 ⁶⁾		

¹⁾ . [14].
²⁾ . [14], [16], [20].
³⁾ . [16], [17], [20].
⁴⁾ . [21].
⁵⁾ . [16].
⁶⁾ . [23].

32601—2022

19.



19 —

()

6.4.3.9

	5	150 DN15, 5,5	(6)	DN20, 6,5 160 (Schedule 160)	DN25, 5 160	DN40, ANSI/ 80 (Schedule 80) 5,5
ASME DN40 (NPS 1%).	DN25 (NPS 1)		DN32			

(. 7.3.4).

• 6.4.3.10

)

25 3 (1 0,12),

9 (0,38);

20;

)

)


d)

6.12.3,

8.2.2;

)

f)



20 —

6.4.3.11

1-1 I-2

6211

6.4.3.7,

16983

11737.

1)

6357.

2).

• 6.4.3.12

33259³⁾

[13] [14]

33259.

[15] [16]

6.4.3.13

6.4.3.14

(. 6.8.10).

6.4.3.15

1) . [24].

2) . [25].

3) . [13] [14].

32601—2022

6.5

6.5.1

6.5.2

6.5.3

5.1.

6.5.4

21—25

(. 7.3.20).

DN1000 (NPS40),

(USC).

() I Id I pyOKd		() ,														
		DN														
		<50	80	100	150	200	250	300	350	400	500	600	700	800	900	1000
	FX	710	1070	1420	2490	3780	5340	6670	7120	8450	10850	13160	15480	17790	20100	22420
	FY	580	890	1160	2050	3110	4450	5340	5780	6670	8700	10540	12380	14220	16070	17910
	FZ	890	1330	1780	3110	4890	6670	8000	8900	10230	13280	16100	18910	21720	24540	27350
	FR	1280	1930	2560	4480	6920	9630	11700	12780	14850	19230	23310	27390	31470	35560	39640
	FX	710	1070	1420	2490	3780	5340	6670	7120	8450	10850	13160	15480	17790	20100	22420
	FY	890	1330	1780	3110	4890	6670	8000	8900	10230	13280	16100	18910	21720	24540	27350
	FZ	580	890	1160	2050	3110	4450	5340	5780	6670	8700	10540	12380	14220	16070	17910
	FR	1280	1930	2560	4480	6920	9630	11700	12780	14850	19230	23310	27390	31470	35560	39640
	FX	890	1330	1780	3110	4890	6670	8000	8900	10230	13280	16100	18910	21720	24540	27350
	FY	710	1070	1420	2490	3780	5340	6670	7120	8450	10850	13160	15480	17790	20100	22420
	FZ	580	890	1160	2050	3110	4450	5340	5780	6670	8700	10540	12380	14220	16070	17910
	FR	1280	1930	2560	4480	6920	9630	11700	12780	14850	19230	23310	27390	31470	35560	39640
	MX	460	950	1330	2300	3530	5020	6100	6370	7320	9720	11780	13840	15910	17970	20040
	MY	230	470	680	1180	1760	2440	2980	3120	3660	4790	5800	6820	7830	8850	9860
	MZ	350	720	1000	1760	2580	3800	4610	4750	5420	7240	8780	10310	11850	13380	14920
	MR	620	1280	1800	3130	4710	6750	8210	8540	9820	13030	15800	18560	21330	24090	26860
		(USC), -														
		NPS														
		<2	3	4	6	8	10	12	14	16	20	24	28	32	36	40
	FX	160	240	320	560	850	1200	1500	1600	1900	2440	2960	3480	4000	4520	5040
	FY	130	200	260	460	700	1000	1200	1300	1500	1955	2370	2785	3200	3610	4025
	FZ	200	300	400	700	1100	1500	1800	2000	2300	2985	3620	4250	4885	5515	6150
	FR	290	430	570	1010	1560	2200	2600	2900	3300	4325	5240	6160	7080	7990	8910
	FX	160	240	320	560	850	1200	1500	1600	1900	2440	2960	3480	4000	4520	5040
	FY	200	300	400	700	1100	1500	1800	2000	2300	2985	3620	4250	4885	5515	6150
	FZ	130	200	260	460	700	1000	1200	1300	1500	1955	2370	2785	3200	3610	4025
	FR	290	430	570	1010	1560	2200	2600	2900	3300	4325	5240	6160	7080	7990	8910
	FX	200	300	400	700	1100	1500	1800	2000	2300	2985	3620	4250	4885	5515	6150
	FY	160	240	320	560	850	1200	1500	1600	1900	2440	2960	3480	4000	4520	5040
	FZ	130	200	260	460	700	1000	1200	1300	1500	1955	2370	2785	3200	3610	4025
	FR	290	430	570	1010	1560	2200	2600	2900	3300	4325	5240	6160	7080	7990	8910


32601—2022

g


5

		(USC), -														
		NPS														
		<2	3	4	6	8	10	12	14	16	20	24	28	32	36	40
		, •														
	MX	340	700	980	1700	2600	3700	4500	4700	5400	7170	8690	10210	11255	13255	14780
	MY	170	350	500	870	1300	1800	2200	2300	2700	3535	4280	5030	5775	6525	7270
	MZ	260	530	740	1300	1900	2800	3400	3500	4000	5340	6475	7605	8740	9870	11005
	MR	460	950	1330	2310	3500	5000	6100	6300	7200	9610	11650	13690	15730	17770	19810
	1 —	21—25 (X, Y, Z).														
	2 —	5														
		;				160	160				160.					

32601—2022




— ; b — ; —
21 —




— ; b — ; —
22 —

32601—2022



1 — ; 2 — ; 3 — ; — ; b — ;


23 —



1— ; 2— ; 3— ; — ; b— ;

24 —

32601—2022



1 — ; 2 — ; 3 — ; — ; b — ;

25 —

• 6.5.5

5

50 %

5,

6.6

6.6.1

6.6.2

—

(N_g).

6.6.3

6.6.4

—

[26] [27]

24069^Λ.

24069.

6.6.5

260 °C (500 °F)

540 °C (1000 °F)

6.6.6

1,5 (0,06)

6.3.12.

F7/h6

25346

6.6.7

25347.

6.6.8

6.6.9

(TIR)

25

(0,001)

6.6.10

7.4.2.2,

)

)

)

d)

(Ra —

)

0,8

(32) ,
() ;

1) [26] [27].

32601—2022

) 1) ;

1) — 25 %

« 2) 6 (0,25 mil), — 13 (0,5 mil). ;

6.6.11 , -

6.6.10. ,

, 17-4 , -

6.6.12 , -

() 7.4.2.2,

6.6.13 () ,

(360 °)

6.6.14 /

() ,

« », 6,5 (0,25 mil), , 25 %

6.7

6.7.1 , -

() , -

6.7.2 ,

50 ,

() 400 ,

6.7.3 , () , -

1/3

6.7.4 : -

) , -

;

) , -

1) . [28].

32601—2022

6. , , -
, 260 °C (500 °F), ,
6, 125 (0,005). ,
;
) -
6. ,
(). ,
— , 50 % 6. ,

6 —

50	0,25	2	0,010
50—64,99	0,28	2—2,499	0,011
65—79,99	0,30	2,5—2,999	0,012
80—89,99	0,33	3—3,499	0,013
90—99,99	0,35	3,5—3,999	0,014
100—114,99	0,38	4—4,499	0,015
115—124,99	0,40	4,5—4,999	0,016
125—149,99	0,43	5—5,999	0,017
150—174,99	0,45	6—6,999	0,018
175—199,99	0,48	7—7,999	0,019
200—224,99	0,50	8—8,999	0,020
225—249,99	0,53	9—9,999	0,021
250—274,99	0,55	10—10,999	0,022
275—299,99	0,58	11—11,999	0,023
300—324,99	0,60	12—12,999	0,024
325—349,99	0,63	13—13,999	0,025
350—374,99	0,65	14—14,999	0,026
375—399,99	0,68	15—15,999	0,027
400—424,99	0,70	16—16,999	0,028
425—449,99	0,73	17—17,999	0,029
450—474,99	0,75	18—18,999	0,030
475—499,99	0,78	19—19,999	0,031
500—524,99	0,80	20—20,999	0,032
525—549,99	0,83	21—21,999	0,033

32601—2022

6

550—574,99	0,85	22—22,999	0,034
575—599,99	0,88	23—23,999	0,035
600—624,99	0,90	24—24,999	0,036
625—649,99)	0,95	25—25,999	0,037
) 0,95 (0,037) 649,99 (25,999), (0,001 1 1).			

6.8

• 6.8.1

32600^.

26 7.

32600^.

6.8.2

6.8.3


26 7.

6.3.5,


6.3.4,

1) . [3].

()



а) Одинарное торцевое уплотнение



1 — () ; 2 — ; L —
 ; L_1 —
 26 —
 7 —

()

		13)	0)	6)	6)			use
								d_2
1	20 (0,787)	70 (2,756)	105 (4,13)	85 (3,46)	150 (5,90)	100 (3,94)	12 1,75	1/2"—13
2	30 (1,181)	80 (3,150)	115 (4,53)	95 (3,740)	155 (6,10)	100 (3,94)	12 1,75	1/2"—13
3	40 (1,575)	90 (3,543)	125 (4,92)	105 (4,134)	160 (6,30)	100 (3,94)	12 1,75	1/2"—13
4	50 (1,968)	100 (3,937)	140 (5,51)	115 (4,528)	165 (6,50)	110 (4,33)	16 2,0	5/8"—11

32601—2022

7

()


	d_1	d_2	d_3	d_4	L			use
5	60 (2,362)	120 (4,724)	160 (6,30)	135 (5,315)	170 (6,69)	110 (4,33)	16 2,0	5/8"—11
6	70 (2,756)	130 (5,118)	170 (6,69)	145 (5,709)	175 (6,89)	110 (4,33)	16 2,0	5/8"—11
7	80 (3,150)	140 (5,512)	180 (7,09)	155 (6,102)	180 (7,09)	110 (4,33)	16 2,0	5/8"—11
8	90 (3,543)	160 (6,299)	205 (8,07)	175 (6,890)	185 (7,28)	120 (4,72)	20 2,5	3/4"—10
9	100 (3,937)	170 (6,693)	215(8,46)	185 (7,283)	190 (7,48)	120 (4,72)	20 2,5	3/4"—10
10	110 (4,331)	180 (7,087)	225 (8,86)	195 (7,677)	195 (7,68)	120 (4,72)	20 2,5	3/4"—10

) — h6.
) — 7;
 ± 75 (0,003) — f7.
) — f7.
 d) 6.9.1.3
 1 2
 1 2

6.8.4

(TIR) 125 (0,005),

27.



1—

:2—


27 —

6.8.5 (0,0005),

0,5 / TIR

28.

6.8.6



1 —
28 —

6.8.7 ()

32600^.

6.8.8
()

6.4.3.11.

• 6.8.9

6.8.10

• 6.8.11

6.8.12

• 6.8.13

) 6.3.5].

6.9

6.9.1

6.9.1.1

9.

6.9.1.2

« »

20 %

1) [3].

32601—2022

6.9.1.3

50 (0,002)

6.9.2

6.9.2.1

)

)

)

),

6.9.2.2

:

)

1500 (2000 . .) ;

)

1500 (2040 . .) ;

)

250

(340 . .) ;

d)

500

(680 . .) ;

)

()

f)

1000 (1360 . .) ;


750 (1020 . .)

6.9.2.3—6.9.2.9.

• 6.9.2.3

()

12-



29 —

• 6.9.2.4

500 (670 . .)

6.9.2.11—6.9.2.14.

43

32601—2022

—
,
6.9.2.5
:
)
);
)
) 1- 2-
d)
,
)
,
f)
(),
)
h)
—
1)
2)
6.9.2.6
10 % 10 %
(
6.9.2.7
,
6.9.2.8
, 6.9.2.6,
,
—
6.9.2.9
—
• 6.9.2.10
,
)
)
)
d)
)

6.9.2.11

6.9.2.2,

)
)
)
)
)

6.9.2.12

6.9.2.13

6.9.2.14

1000 ... 1500.
5000.

[29]

375

— 20-

1

1040

6.9.3

• 6.9.3.1

(N_g)

(A_{ss}) .


30

$(NPSH3)$

(6.1.12)

, $NPSHA$

32601—2022



X — ; 1 — ; 2 — ; 1 — ; 2 — ; 5 —
 ; 3 — () ; — ; 4 — ; 8 — ()
 ; 7 — ; 8 — ()
 30 —






6.9.3.2

5 1000
 (FFT),
 ;
 ;
) () ;
 31—33;
)
 () , ;

• 6.9.3.3

5 2Z, (Z —
 ;
 , Z)
 ,
 Z, — ()
 Z, —

()



1— (.6.10.2.10); — (.6.10.2.9); 2— ; —


; V—

31 —

()

32601—2022

()



1—
4—

; 2—

; 3—
(. 6.10.2.10); —





(. 6.10.2.9);
; X, Y—

32 —

(VS)

32601—2022

()



— (— 5); b —
 d— (6); — (. 6.10.2.9);
 ; 3 — ; 4 — (. 6.10.2.10); 1 — ; 2 —
 ; — ; X, Y — ; 5 — ; 6 —

33 —

(— 6)

6.9.3.4

(RMS) , / (/).

6.9.3.5

), (

6.9.3.6

, , -

- — 8;

- — 9.

, , -

, , -

, , -

(RMS)

32601—2022


8 —

	(. 31 33)	() >
	3600 / 300 (400 .) v _u < 3,0 / RMS ^b (0,12 / RMS) ^{b>} . 3600 / 300 (400 . .) 34	() : < (5,2 • 1 ^{6/}) ^{0,5}) [(8 /) ^{0,5} mils] ^{b>} , () : < 50 (2,0 mils)
	< 2,0 / RMS ^b (0,08 / RMS) ^{b>}	f < : <0,33 >
	30 %)	30 %)
))) 1 — : v _u — ; V _f — (FFT) , 400 ; — , ; A _f — (FFT) 400 ; f— ; — / . 2 — (,) , 3 — , 1,0.		6.9.3.1.

9 —

	(. 32)	() >
	v _u < 5,0 / RMS ^b (0,20 / RMS) ^{b>}	() : < (6,2 • 10 ^{6/}) ^{0,5}) [(/) ^{0,5} mils] ^{b>} () : < 100 (4,0 mils)
	< 3,4 / RMS ^b (0,13 / RMS) ^b	f < n: A _f < 0,33 •)

	(. 32)	() >
-	30 %)	30 %)
>))	6.9.3.1.	
1 — ; —	i_u —	
(FFT)	400 ; —	-
	(FFT)	-
400 ; f— ; —	/ .	-
2 —		-



X — ; / ; Y_1 — , / , RMS; Y_2 — , / , RMS; 1 — > 3000 / ;
 2 — =2000 / ; 3 — =1500 / ; 4 — =1000 / ; 5 — =700 / ; 6 — =500 / ;
 7 — < 300 /

$v_u = 3,0 \cdot (/)^{0,30} [/]^{0,21}$ 3,0 / 4,5 / :

$v_f < 0,67 \cdot v_u$ v_u — , -

34 —

3600 /

300 (400 . .)

32601—2022

6.9.3.7

150 %

6.9.3.8

6.9.4

6.9.4.1

/ (. 6.7.1)

G2.5

1940-1.

1 2




(9.2.4.2)

6.9.4.2


D/b

6,0

(. 35).



с) Упорный диск



d)

; $\varnothing D$ —

35 —

6.9.4.3

• 6.9.4.4

G1

1940-1 (

$4W/n$ USC).

USC

$$U = KW/n,$$

(2)

U —

— , 4 (. J);
 / — () , ; -
 ; () , -
 — , / .
 KW/n USC. -
 1940-1 1940-1.
 USC
 1940-1.
 II = 4 // (USC) (G1 1940-1), -
 , U = 8 // (USC) (G2.5 -
 1940-1), -
 , G2.5 (8 /7 USC). -

6.10

6.10.1

• 6.10.1.1

()

:

-

-

-

10.

10 —

3)) 6)	,
6) , 9)	-
3) / 6)	- - -
6)	-
3) 6)	-
6) , /	-

3)

500 000

350 000

$[(d + D)/2]$,

6.10.1.5

$n d_m$

d_m

6.10.1.6.

6)

)

(. .)

/ .

32601—2022

	10							
d)		$4,0 \cdot 10^6$	/	$(5,44 \cdot 10^6 \dots)$				-
	1 —			$\cdot d_m$			6.10.2.4,	-
	2 —							-
	6.10.1.2							-
	:							-
)							-
)							-
								-
					()	-
								-
)							-
								-
	d)							-
	6.10.1.3							-
"N" ()	3-		24810^\wedge				-
	6.10.2.4			6.9.3.6				-
	—				3-	[30]	[31]	-
	3-			24810.				-
6.10.1.4				$40^\circ (0,7)$			(7000),	-
								-
				« - - ».				-
								-
	6.10.1.5							-
	25 000						L_{10h} 18855^{12}	-
							16 000	-
	1)			[30].				-
	2)			[32].				-

1 — 18855^Λ L_{10h} -
 2 — [32] [33] L_{10h} -
 18855.

• 6.10.1.6 (25 000)
 16 000 L_{10h system} :

$$L_{10h,system} = K^{1/\lambda} (10hA)^{3/2} + (10hB)^{2} + - (10hC)^{3/2} + 273$$
 (3)

L_{10hA} — L_{10h} 18855^Λ ;
 /- — L_{10h} 18855^Λ ;
 Z-iOhN — L_{10h} 18855^Λ N;
 N —

.2 ().
 — , L_{10h} 25 000 16 000 (L_{10h}) -

6.10.1.7 , 6.10.1.5,

6.10.1.8 :
)
) 3325²
) ;
) , -

d) ;
 — , , -
 , , -

6.10.2
 6.10.2.1 , -

• 6.10.2.2 DN15 (NPS 1/2). -
 0,12
 (4) , () -
) , () -
) . () -

1) . [32].

2) . [34].

32601—2022

)

6.10.2.3

6.10.2.4

43 °C (110 °F),

)

70 °C (160 °F),

)

28 °C (50,4 °F);

)

82 °C (180 °F).

40 °C (72 °F),

)

93 °C (200 °F).

—

8.3.4.2.1.

1 °C (1,8 °F) 10

6.10.2.5

()

1,0 (0,04) 12

(0,50).

—

6.10.2.6

—

2 % 0,2 %, (. .

)

31441.

6.10.2.7

6.10.2.7.1 6.10.2.7.2.

6.10.2.7.1

)

6 (NPS 1/4)

1) [35].

b)

— ;
) ;

d)

— ;
)
— 300 °C (570 °F),

- ;
- ;
- ;
- ;

6.10.2.7.2

)
6 12 (NPS 1/4 1/2),
);
)
)
)
d)

6.10.2.7.3

6.10.2.7.4

6.10.2.7.5

6.10.2.8

6.10.2.9

• 6.10.2.10

1) [28].

31—33.

2 (0,080) 120°.

1) (. 31—33).

8 1,25.

32601—2022

• 6.10.2.11 , -

25 (1).

• 6.10.2.12 , -

() .

6.11

6.11.1 , -

6.11.2 -

• 6.11.3 ,

6.10.2.7.

• 6.11.4 ,

) (;

) () -

);

) ,

2000 ;

) 2000 ,

25 000 ,

d) ; 25 000 ,

6.12

6.12.1

• 6.12.1.1 -

G.1 (G) -

, , -

6.12.1.2 , -

.1 (), -

.2 (). -

, -

6.12.1.3 , -

32600^.

6.12.1.4 ,

« » « » .1

() . « » -

7.5.

1) [3].

• 6.12.1.5

« » (N).

6.12.1.6

(17,25 , 250 psi) (. 6.3.5). 1-1 I-2 .1 (), 1,725

6.12.1.7

— 0,10 %

• 6.12.1.8

• 6.12.1.9

1 — :
2 — 10 /
(10 ppm),

• 6.12.1.10

« » ().

6.12.1.11

• 6.12.1.12

(H₂S)

32601—2022

• 6.12.1.12.1

6.12.1.12.2

6.12.1.12.1,

^,

— [36]

• 6.12.1.12.3

^{12)13).}

1 —

[36]

[37].

2 —

[37]

6.12.1.12.4

^{4^},

620 / ² (90'000 psi)

HRC 22.

—

[36]

[37].

6.12.1.12.5

)

) (

)

);

d)

)

()

• 6.12.1.12.6

HRC 22

6.12.1.1 3

1) . [36].

2)

53678—2009.

3) . [37].

4) . [36] [37].

6.12.1.1 4

—

[38]

6.12.1.1 5

1-1 I-2

.1 ()

6.12.2

6.12.2.1

1).

977 () 26358 ()

6.12.2.2

(-

),

6.12.2.3

)

6.12.3.

)

6.12.2.4

• 6.12.2.5

(, .),

6.12.2.6

6.12.3

• 6.12.3.1

11.

1) . [39].

32601—2022

11—

			2)	-
			3л 4)	-
		5л		-
		21105,	18442®	-
			®	-
			®	-
1)	[40] [41].			
2)	54006—2010.	53687—2009,	53688—2009,	53690—2009,
3)	[40], [42] [43].			
4)		15609—2009 ()	
5)	[44].			
6)	[45].			
7)	[43], [45], [46].			
8)	[45], [46].			

6.12.3.2

6.12.3.1 8.2.2.1.

6.12.3.3

6.12.3.4):

d)

6.12.3.4

1) [45].

b)

)

• d)

•)

1)

2)

6.12.4

• 6.12.4.1

6.12.4.2

(). ASME BPVC ANSI,

40 °C (100 °F).

• 6.12.4.3

9454,

¹²Λ

6.12.4.4

)

)

1)

2)

3)

1)

148-1—2013.

2) . [45] [46].

32601—2022

) % (), , -

6.12.4.5 6.12.4.3
 [45], : -
) , -
 V- , 29 °C (20 °F), 1). -
) , 29 °C (20 °F) -
 38 °C (100 °F) :
 1) 25 (1)
 ;
 2) 25 (1) -
 , 2) , -
 , 3) , -
 V- , 4). -

6.13

6.13.1 () -

6.13.2 () -
) :
 () ;
) ;
) () ;
 d) ;
) ;
 f) ;
) ;
 h) () ;
 i) (MAWP);
 j) -

MAWP.

6.13.3

6.13.4 , , -

6.13.5 () ()). -

— (Monel™)

- 1) , [45, 11 -51].
- 2) . [45, UCS-66].
- 3) . [45, UCS-66.1].
- 4) . [45, UG-84],

« » (— 6),

7

7.1

7.1.1

—

6.9.3.1,

7.1.2

7.1.3

(500)

7.1.4

)

12

4 (5 . .),

12 —

		, %
22	30	125
22 55	30 75	115
. 55	. 75	110

• 7.1.5

-) ;
-) ();
-) ;
- d) ;
-)¹²⁾;
- f) ;
-) ;
- h) ;
- i) ();
- j) ;
-) ;
- l) IEC 60034^{2>>}

1) . [8] [47].

2) . [29], [48], [49] [50].

32601—2022

7.1.6


80 %

7.1.7

(

).

36



— 25 (0,001) TIR; b —
— 25 (0,001) TIR; —

— 125 (0,005) TIR.

36 —

7.1.8

25000

18855^;

16000

750 (1000 . .),

16000

125 (0,005);

d)

24810^1 . .

«N» (

1) . [32].

2) . [30].

)

f) , ;

6.7.4, 50 % -

7.1.9 , -

^ , -

110 %

7.1.10 , -

12 ^ , -

7.2

7.2.1 , ,

7.2.2 , , -

3), -

)

)

— , -

)

d) () , () , -

125 . , , , VS, -

(. L, 7. N). -

— ;

)

— 25 (1)) -

f) , 3800 / ., -

4).

1) . [51].
 2) . [52].
 3) . [53].
 4) . [54] [55],

32601—2022

• 7.2.3	,					
1940-1 G6.3.						
• 7.2.4						-
			1).			
7.2.5						-
7.2.6						-
			23360 ²³ \			
						-
7.2.7						-
7.2.8			60	(2,5)		-
				1:16 (60 /	0,75	-
), 1:10.						
						-
						-
						-
7.2.9						-
			10	(0,38)		
• 7.2.10						-
7.2.11						-
						-
						-
						-
						-
						-
						-
						-
						-
						-
7.2.12						-
						-
7.2.13						-
						-
)						-
)			12.2.003,	12.2.062^1		-
					() ,	
			900	(200 -) ,		-
)					() ,	-
						12.2.003,

1) , [54] [55].

2) . [56].

3) . [57], [58], [59].

12.2.062^,	10	(0,375)	-
d)			-
()			-
• 7.2.14			-
• 7.2.15	(. 6.10.2.6,)	-
	«	» ()	31441.1 ¹² \
7.3	()		-
• 7.3.1		()	-
)			-
)			-
)			-
		1:120	-
DN 50 (NPS 2).			-
7.3.2			-
			-
			-
7.3.3			-
	D		-
0,5 12.		«	»,
			-
7.			-
			-
• 7.3.5			-
			-
	150	1 (0,002)	-
			-
			-
			-
			-

1) . [57], [58], [59].

2) . [35].

32601—2022

				Λ.			-	
•	7.3.6						-	
		3	(0,12),	13	(0,5).	
							-	
		5					-	
			5	(1/4)		.	
							-	
							-	
					5	(0,2).	
							-	
	7.3.7						-	
							-	
	7.3.8						-	
							-	
	7.3.9						-	
							-	
	7.3.10						-	
		125	¹²	(19)	75	(3)
							-	
						13	(0,5).
							-	
						1,5	(0,06).
							-	
	7.3.11			13	(0,5).	-	
		50	(2)	[D.1	(D)].
	7.3.12						-	
							2Λ,	
							-	
							-	
				(7.3.9).		-	

1) . [60].

2) . [61], [62].

• 7.3.13

• 7.3.14

7.3.15

7.3.16

7.3.17

250 (500)

12 (1/2"—13).

7.3.18

7.3.19

7.3.20

13.

7.3.21.

250 (0,010) (. F).

• 7.3.21

7.3.20.

M_{zc}

(),

($A4_{zc}$),

32601—2022

13 —

	()	()	
	175 (0,007)	125 (0,005)	+Z
	75 (0,003)	50 (0,002)	-Y
) M_{zc} 5, . . : = (4) (+ () (); $M_{zc} = (M_z) () + (M_z) ()$.			

7.4

7.4.1

-

[63].

7.4.2

- 7.4.2.1

- 7.4.2.2

- 7.4.2.3

- 7.4.2.4

7.5

7.5.1

7.5.1.1

1) . [63] [64].

2) . [28].

3) . [63].

7.5.1.2
 ;
) ;
) ;
) ;
 d) (.9.2.6).
).

6.4.3.

7.5.1.3

• 7.5.1.4

7.5.1.5

• 7.5.1.6

• 7.5.1.7

6.1.30

(, 4543 7¹),
 ISO 10684²).

6.4.3.10.

7.5.1.8

7.5.2

7.5.2.1

7.5.2.2

(MAWP)

PN 40 PN 50³) (.6.3.5).

7.5.2.3

• 7.5.2.4

3 (0,12).

7.5.2.5

1) . [65].

2) . [66].

3) . [13] [14].

32601—2022

7.5.2.6

7.5.2.7

• 7.5.2.8

33259

2,5

03

04

(. 6.4.3.11).

90°

7.5.2.9

1-1 I-2

-1 ().

7.5.2.10

7.5.3

7.5.3.1

.2— .7 ().

7.5.3.2

6.1.20.

7.6

7.6.1

7.6.2

/)».

«

(

8

8.1

• 8.1.1

)

)

30

	-
	-
	-
)	-
	-
	-
8.1.2	-
8.1.3	-
8.1.4	-
• 8.1.5	-
	-
8.1.6	-
8.2	-
8.2.1	-
• 8.2.1.1	20
)	-
)	-
)	-
d)	-
)	-
f)	-
(. 10.3.1 10.3.2).	-
8.2.1.2	-
• 8.2.1.3	6.12.1.5
)	-
)	-
8.2.1.4	-
8.2.2	-
8.2.2.1	14.
	-
	-
	-

32601—2022

14 —

	1)		
	1 ^{2>}	II ³⁾	III ⁴⁾
5)	VI	VI,	VI, RT UT
5) .6)	VI	VI,	VI, UT
	VI, (100 %)	VI, (100 %)	VI, (100 %), RT (100 %)
7) -	VI	VI,	VI, (100 %)
	VI	VI	VI
:	VI	VI, (100 %)	VI, (100 %)
:	VI, RT (5%)	VI, (100 %), RT (5 %)	VI, (100 %), RT (10 %)
<p>1) : VI — ; RT — ; UT — ; —</p> <p>2) I — , ()</p> <p>3) II — II III ; 80 %</p> <p>4) III — 200 °C; 200 °C, 260 °C, 0,5 0,7, -</p> <p>5)) « , (.</p> <p>» —</p> <p>6)</p> <p>7) -</p>			

8.2.2.2

(. 8.2.2.1).

I

14.

8.2.2.3

14

a) VI/MT/PT

()

1 (0,040) 5 % -

b) RT/UT
) RT UT UT
 UT -

8.2.2.4 -

- 8.2.2.5 15, -
 -
 15. -
- 8.2.2.6 -
- 8.2.2.7 -

15 —

	/		
	7512^	7512 ²⁾	7512 ²⁾
	14782^	14782 ²⁾	14782^
	18442^	18442^	18442^
- -	21105^	21105^	21105 ³⁾
(-)	^>	,	- 3^

1) . [67].
 2) . [45].
 3) . [39].

- 8.2.2.8 -

(PMI) -
 -
 -

PML
 — PMI

32601—2022

8.3

8.3.1

- 8.3.1.1

(8.3.4).

8.3.1.2

6134^Λ.

8.3.1.3

) 8.3.3.3.

16.

1

8.3.2

8.3.2.1

8.3.2.2

(MAWP)

34233.

8.3.2.3

8.3.2.4

8.3.2.5

- 8.3.2.6

6.3.4

1 2^Λ

8.3.2.7

)

0,7

)

260 °C (500 °F);

)

d)

1) . [68], [69], [70].

2) . [43] [71].

8.3.2.8 , , 50 / (50 ppm). -

8.3.2.9 (). -
() 32600¹⁾

32600. — [3]

8.3.2.10 , , -
() (. 8.2.2.3). -

8.3.2.11 , , 30 , -

8.3.2.12 , , -

8.3.2.13 , , 2Λ, -

8.3.2.14 , , () 610 -
(24), ,

1) . [3].

2) . [43] [71].

32601—2022

8.3.2.15

1000 (10, 150 psig).

8.3.2.16

1,5

1050 (10,5, 150 psig),

8.3.3

8.3.3.1

• 8.3.3.2

)

()

)

1);

)

()

32600 (

.1.3)²³ |

d) 8.3.3.7.

32600^

(4000 (40, 600 psi)

[3]

32600;

d)

)

(,);

f)

)

h)

i)

55 °C (130 °F).

1) . 32600 (10.3.5) [3, . 10.3.5].

2) . [3, .1.3].

3) . [3].

• 8.3.3.3

),
 3) () ;
 4) () ;
 5) 95 % 99 % ;
 6) 105 % ;
 7) (5 %);
 8))
) (),
 () .
 16.
 (. 6.1.8),
) ;
) 3 % ;
 d) (. 10.2.4, 10.3.2.2) ;
) 10.3.2.2,
 (24)

16 —

	, %	, %
0 75 (0 250) .75 300 (. 250 1000) .300 (. 1000)	±3	± 1>
	±3	±8 ¹⁾
	±3	±5 ¹⁾
	4 ²⁾	—
	—3)	—
NPSH	0	—
¹⁾ « »		(. 6.1.11), -

32601—2022

	16				
2)					-
) 8.3.3.3			()	-
		104 %			
3)				3 %	
	6134 (6.3).			(. 8.3.3.4),	-
• 8.3.3.4			(1)		-
		16.			-
			()		-
• 8.3.3.5					-
:					
)					
		6.9.3.2.			-
6.9.3.6;					-
)					-
)					
6.10.2.4.					
d)					-
		16.			
• 8.3.3.6					
		(NPSHA),		110 %	
—					-
NPSHA					
• 8.3.3.7					
:					
)					-
				5 %	
)					-
				5 %	
)					-
		(NPSH3)			-

d) , , : , -

1) 172 (1,72 , 25 psi); , -

2) 5 , 5 30 -

(1 .) ;

3) 14 (0,14 , 2 psi). -

- 8.3.3.8 , 4 -

8.3.4

8.3.4.1

- 8.3.4.2—8.3.4.7. (-

8.3.4.2

- 8.3.4.2.1 , 6.10.2.4. , -

- 8.3.4.2.2 1 10 . -

8.3.4.3 (NPSH3)

- 8.3.4.3.1 (NPSH3) , (NPSH3) -

- 8.3.4.3.2 () 3 % -

NPSH3. -

- 8.3.4.3.3 NPSHA, 3 % , -

(NPSHA) — , -

NPSHA , 3 % , -

(NPSH3) NPSHA (. 8.3.4.3.2). , -

2 NPSHA, NPSH3, -

NPSHA , -

1 (3). NPSHA NPSH3 -

6134^, -

1) . [68], [69].

32601—2022

	()	
20 %.			
—			8.3.3.6, -
,			NPSHA. -
	NPSHA.		
8.3.4.3.4		(NPSH3)	
			16. -
	(8.3.3.5	8.4.3.1).
8.3.4.4			
• 8.3.4.4.1			-
,			-
,			-
,			-
8.3.4.4.2			-
	(-
)	-
8.3.4.5			
•			
—	31252 (3740)^	-
8.3.4.6			
•			-
,			-
,			-
8.3.4.7			
•			-
,			-
,			-
)			: 1,0; 2,0; ,0;
)			-
			: 1,0; 2,0.
			-
			-
8.4			
• 8.4.1			-
			-
	6		-
			-
8.4.2			
	8.4.2.1—8.4.2.9.		

1) [6] [7].

8.4.2.1					-
8.4.2.2					-
8.4.2.3					-
8.4.2.4					-
8.4.2.5				7.3.12.	-
8.4.2.6	5	(0,19)		-
8.4.2.7					-
8.4.2.8			6.4.3.11.		-
8.4.2.9					-
8.4.3					-
8.4.4					-
8.4.5					-
8.4.6				() ,	-
8.4.7				() .	-
8.4.8		—	31252 (3740) >		-

1) [6] [7].

32601—2022

				-
				-
8.4.9			200	-
(450)				-
				-
8.4.10				-
8.4.11				-
8.4.12				-
				-
9				-
9.1				-
9.1.1		(2)		-
9.1.1.1				-
			(-
80 °C)				-
9.1.1.2			(-
)	-
			,	-
• 9.1.1.3				-
	.1 ()			-
	.1 ()			-
				-
9.1.2			()	-
9.1.2.1				-
			3:1.	-
				-
9.1.2.2				-
				-
				-
9.1.2.3				-
	(),			-
	DN 15 (NPS 1/2).			-
9.1.2.4			/	-
				-
			(,)	-
				-
9.1.2.5				-
			(-
)	-
			,	-

- 9.1.2.6
- 9.1.2.7
- (6.11.4).
- 82 °C (180 °F) 43 °C (110 °F).
- 9.1.2.8
- 9.1.3** (6)
- 9.1.3.1
- 9.1.3.2
- 9.1.3.3
- 9.1.3.4
- 9.2.4.1.
- 6.
- 9.1.3.5 ()
- 9.1.3.6
- 50 (2)
- 9.1.3.7
- 7 (0,01 -), G2.5 1940-1,
- 8.
- 9.2** (1, 2, 5)
- 9.2.1**
- 9.2.1.1 « ».
- 9.2.1.2 150 °C (300 °F),
- 9.2.1.3
- (.10.2.2.1 L).
- 9.2.1.4
- 9.2.1.5

1) [63].

32601—2022

9.2.2

9.2.2.1

9.2.2.2

0,75 (0,030).

• 9.2.2.3

(0,030).

9.2.2.4

V-

17.

17 —

$F_f^{1>2>}, \quad ^2 (\quad ^2)$	(TIR), ()		(TIR) ^{3>} , ()
$> 1,9 \quad ^9$	40		90 (0,0035)
$(> 3,0 \quad ^6)$	(0,0015)		60 (0,0025)
$< 1,9 \quad ^9$	25		75 (0,0030)
$(< 3,0 \quad ^6)$	(0,0010)		50 (0,0020)
1) ; D —	F_f ()	$: F_f = L^4/D^2, \quad L —$	
2)	F_f		
3)			

9.2.3

9.2.3.1

9.2.3.2

6.7.4

9.2.4

9.2.4.1

9.2.4.1.1

« »

9.2.4.1.2

18.

18 —

1	
2	(. 3.1) (. 3.9) ? « », 5 « », 3
3	(. 3.14)? « », 5 « », 4
4	
5	

• 9.2.4.1.3

9.2.4.1.2,
1.1 (l).

9.2.4.2

9.2.4.2.1

19:

- ();

- ,

3800 / .

9.2.4.2.2

31320^.

19

G2.5

1940-1

3800 / .

- :

3800 /

G2.5

- , 10 % ;

- (. 17),

G1.

9.2.4.2.3

2,5 (0,00010)

G1,

3800 / .

- ; G2.5

(. 6.9.4.1),

;

-

9.2.4.2.4

9.2.4.2.5

J.

J.

1) . [72].

32601—2022

19 —

		$\frac{L^4 I D^2}{()^2}$	$2>$	
	3800 ¹⁾			—3)
	3800		+ D	G2.5 (8W/n) ⁴⁾
	3800	$1,9 \cdot 10^9$ $3,0 \cdot 10^6$	+ D	G1 (4W/n) ⁴⁾⁻⁵⁾
1)	5 %-			
2)	31320 [72].			
3)				-
4)	1940-1.			
5)	3800 /			-
				-
				17.

9.2.5

9.2.5.1

9.2.5.1.1—9.2.5.1.4.

9.2.5.1.1

9.2.5.1.2

9.2.5.1.3

9.2.5.1.4

1,0 %
20 / (65 /),

« »

9.2.5.2

9.2.5.2.1—9.2.5.2.5.

9.2.5.2.1

9.2.5.2.2

9.2.5.2.3

0,4 Ra (16

13 (0,0005 TIR).

9.2.5.2.4 (. 6.10.1.2). -
-

) : 8 (0,0003);
) (,): 3500 (35 ; 500 psi);
) : 130 °C (265 °F). -

• , 2 , -

(. 6.10.2.4): -
[.) 8.3.3.5]: 93 °C (200 °F);
: 115 °C (240 °F). -

9.2.5.2.5 , -

9.2.5.3 50 °C (120 °F), -

9.2.5.4 7.5. « -

» -

9.2.6
• 9.2.6.1 , -

9.2.6.2 ^ -

.8 .1 () , -

9.2.6.3 (, ,), -

— () , 32—68 17479.3. ,

• 9.2.6.4 1). -

9.2.7
9.2.7.1 , -

^ , -

1) . [63].

32601—2022

9.2.7.2

9.2.7.3

6134^.

(.6.9.3.6).

9.2.7.4

• 9.2.7.5

9.2.8

9.2.8.1

3

3 (0,12);

• 9.2.8.2

1,5

).

• 9.2.8.3

• 9.2.8.4

9.3

(VS1—VS7)

9.3.1

9.3.1.1

9.3.1.2


9.3.2

9.3.2.1

1) [28].

9.3.2.2									-
9.3.2.3									-
				(. 6.3.10).					-
9.3.3									
9.3.3.1									-
(0,0005),	80	(0,003	(TIR),		40			-
)	4500	(177)			-
(0,003),							80	-
9.3.3.2								(-
									-
9.3.4									
9.3.4.1									-
									-
9.3.4.2						6.7.4,			-
9.3.4.3									-
9.3.5									-
•									-
									-
									-
									-
5 %									-
									-
20 %.									-
9.3.6									
9.3.6.1									-
									-
		37,							-
9.3.6.2								7.1.8.	-
6.10.									-
9.3.6.3								VS4,	-

32601—2022



x — () ; — () ; —

37 —

9.3.7

9.3.8

9.3.8.1

9.3.8.1.1

9.3.8.1.2

(. .) .

36.

9.3.8.2

9.3.8.2.1

0,1 (0,0001) , 13 (0,0005)

(TIR),

9.3.8.2.2

9.3.8.2.3

9.3.8.3

- 9.3.8.3.1

38).

9.3.8.3.2

250 (500)

- 9.3.8.3.3


4 (. 38).

9.3.8.3.4

50

D.1 (-

D).



1 — ; 2 — ; 3 — ; 4 — ; 5 — ;
 6 — ; 7 — (; 8 — (;
 8 — (; 9 — (; 10 — (; 11 — (; 12 — (

38 —

(VS6 VS7)

9.3.8.4

9.3.9

9.3.9.1

[

(« »)]

32601—2022

· 9.3.9.2	/	:	-
-	;	;	-
-	;	;	-
-	;	;	-
90°	;	;	-
-	;	;	-
10 %	,	,	10 %
9.3.10			-
(VS1)	(VS2)		-
9.3.10.1		VS1 VS2	-
:	(« »),		-
—	(« »)	VS1	S-6
(.)	,		-
9.3.10.2	(,)		-
	,		-
	,		-
9.3.10.3			-
9.3.10.4			-
· 9.3.10.5			-
9.3.10.6	(« »)		-
9.3.10.7	(« »)		-
	« »		-
9.3.11		(VS3)	-
9.3.11.1		VS3	-
:	(« »),		-
9.3.11.2	(« »)		-
9.3.11.3	(« »)	« »	-
9.3.12		() (VS4)	-
(VS5)	VS4		-
9.3.12.1	VS5		-
9.3.12.2	VS5	:	-
)			-

b)					-
)	30 %	VS5	« »		
d)	(0,002)	VS5		(TIR),	50
9.3.12.3				VS4 VS5	-
9.3.12.4		VS4			-
			VS5		
			43 °C (110 °F).	82 °C (180 °F)	
9.3.12.5				VS4 VS5,	
9.3.12.6					
9.3.12.7					
6.3.3.					(.6.5).
9.3.12.8					
9.3.12.9					-
		VS4 VS5		()	
9.3.12.10		VS4 VS5			-
9.3.12.11		VS4 VS5			-
9.3.13					-
(VS6)			(VS7)		
9.3.13.1			VS7:	VS6 :	
			()	()	
9.3.13.2			(« »)		-
1,5					-
			8.3.2.		
9.3.13.3			(« »)		-

32601—2022

9.3.13.4

9.3.13.5

(« »)

9.3.13.6

(« »)

10

10.1

10.1.1

10.2 10.3.

10.1.2

)

)

)

d)

)

f)

10.1.3

)

)

)

d)

)

f)

)

h)

i)

j)

10—12

l)

)

)

)

)

10.2

10.2.1

10.2.1.1

10.2.2 —10.2.5,

10.1.2.

10.2.1.2

10.2.2

10.2.2.1

D (

10.2.2.2

10.2.3

d)

f)

h)

i)

j)

8.2.2 8.3.4;

: 6.1.12, 6.1.13, 6.1.14, 6.3.4,

32601—2022

6.4.3.10, 6.4.3.13, 6.9.3.1, 6.12.1.1, 6.12.1.2, 6.12.1.3, 7.1.4, 7.1.8, 9.2.1.1, 9.2.3.2, 9.2.7.4, 9.3.4.2, 9.3.9.1, 10.2.1.2, 10.2.2.1 10.3.4.2;

• л) ;
) ;
) ;
) ;
) ;
 (. 2.7.4);
) ;
 (. 6.2).

20 —

	:						
	1-3	4-6	>7	1-3	4-6	7-9	>10
2) ⁵⁾	—	—	—	1	1	1	1
2)-6)	—	—	—	1	1	1	1
3)-7)	—	—	—	1	1	1	1
1)	—	—	—	—	—	—	1
()	—	—	—	—	—	—	1
1)	—	—	—	—	—	—	1
()	—	—	—	1	1	2	/3
	—	—	—	1	1	2	/3
() ⁸⁾	1	1	1	1	1	2	/3
, (,) ¹⁾⁻⁹⁾	1	1	2	1	2	/3	/3
, (,) ¹⁾⁻⁹⁾	1	1	2	1	2	/3	/3
) ¹⁾⁻⁹⁾ , (, -	1	1	2	1	2	/3	/3
,) ¹⁾⁻⁹⁾ , (-	1	1	2	1	2	/3	/3
) ¹⁾⁻⁹⁾ , (, -	1	1	2	1	2	/3	/3
,) ¹⁾⁻⁹⁾ , (-	1	1	2	1	2	/3	/3
/) ⁴⁾⁻⁸⁾) ⁹⁾	1	2	/3	1	2	/3	/3
⁸⁾	1	2	/3	1	2	/3	/3
, () ⁸⁾ , -	1	2	/3	1	2	/3	/3
(« »)	—	—	—	—	—	/3	—
(« ») « » ()	—	—	1	1	1	/3	/3

	1-3	4-6	>7	1-3	4-6	7-9	>10
, ()	1	1	2	1	1	/3	/3
	—	1	1	1	1	1	/3
	1	1	1	1	1	1	/3
	1	1	1	1	1	1	/3
	—	—	—	1	1	1	/3
,	—	1	1	1	1	1	/3
,	—	1	1	1	1	1	/3
	1	2	/3	1	2	3	/3
^							
2)							
3)							
4)							
5)							
6)							
7)							
8)							
9)							

10.2.4

(NPSH3) , -
 , 120 % -
 (), -
 , -
 , -
 (). , (-
), -

10.2.5

• , -

32601—2022

10.3

10.3.1

10.3.1.1

(. L).

10.3.1.2

10.1.2.

10.3.1.3

10.3.1.4

L).

10.3.2

10.3.2.1

10.3.5,

N,

L,

8 .,

10.3.2.2

15

),

(NPSH3),

• 10.3.2.3

(.),

10.3.3

6.3.3 6.3.4.

10.3.4

10.3.4.1

(. L).

6.12.1.

/

10.3.4.2

10.3.5

10.3.5.1

10.3.5.2

10.3.5.3

10.1.2.

10.1.2,

10.2.2 10.2.3,

135 (300).

L.

2.601,

32601—2022

()

n_s

n_s

$$= \frac{VQ}{\Delta 0,75}$$

(.1)

— , / ;
 Q — , 3/ () ;
 — , ().

1 —

51,64,

USC.

2 —

3 —

3,65,

n_{ss}

n_{ss}

$$n_{ss} = \frac{n^1 \Delta_{75}}{NPSH3^{0,75}}$$

(.2)

— , / ;
 — , 3/ (),
 ;
 NPSH3 — , ().

1 —

51,64,

USC.

USC

n_{ss}




2 —

5,62,

()


.2— .8,

.1.




1 — ; 2 — (; 7 — (); 3 — ; 4 — ; 5 — (); 8 — ; 11 — (); 12 — ; 13 — (); 14 — (); 15 — (); 16 — ; 17 — ; 18 — ; 19 — , .1 — , .2— .8



32601—2022




1— ; 2— ; 3— ; 4—
 2— — :




1— ; 2— ; 3— ; 4—
 . — — :




32601—2022



1— ; 2— ; 3— ; 4—
 .6— : ,



1— ; 2— ; 3— ; 4—
 .7— : ,



II-P0-R1-H0-BP0-C1F2-C0-PV1-TV1-BB0

II-P0-R1-H0-BP1-C1F2-C0-PV1-TV1-BB0

« 1 » —
 [64] 2 — [63].
 .8 .1
 .1 —
 .8

.8	1)	
	2)	II — P0-R1-H0-BP0-C1F2-C0-PV1-TV1-BB0 II — P0-R1-H0-BP1-C1F2-C0-PV1-TV1-BB0

32601—2022

. 1

.8	/ 1>	
2 3 5	,	3) , DN 50 3) , 3)
6 7 8 9 10 12 13 14	/ -	
15 16 17		
21	- () ()	- (TV1) ⁴⁾
	⁵⁾	
PSLL, PSL, PI PDI TS TI	⁶⁾ 7) ⁹⁾	PSLL ⁴⁾⁸⁾ TS ⁴⁾⁸⁾ TI - - ⁴⁾⁸⁾
b d		- 1:50 (20 / ; 0,25) ³⁾
^{1>} . [63] [64]. ²⁾ ³⁾ ⁴⁾ ⁵⁾ . [63, . 5.2]. ⁶⁾ . [63, 6]. ^{7>} . [63, . 25]. ⁸⁾ . [63, . 6.2, 3]. ^{9>} . [63, . 32].		

()

.1

(—).

.2

« », « » « » « », « » « » « » « »

.3.1

.3.1.1

.3.1.2

()

.3.1.3

()

.3.2

.3.3

.3.3.1

().

115 % 120 %

.3.3.2

(,),

.3.3.3

.3.4

— .1,


.3.4.1

.3.4.2— .3.4.5.


.3.4.2

32601—2022


- .3.4.3 (. . . ,) , - ,
- .3.4.4 40 % , -
- .3.4.5 .
- .3.5** — . .1, . ,
- 20—30 % ,
- .3.6** , , .1.
- .3.7** , ,
- (. .1).
- .3.8** , -
- .1.
- .4**
- .4.1 , -
- .4.2 .2 , -
- .4.3 , , -
- .4.4 , -



a




b



- 1— ; 2— ; 3— ;
 4— ; 5— ; 6— ; 7— ;
 ; 8— ; 9— ; 10— ; 11—
 ; 12— ; 13—
 .1—

32601—2022




X — ; 1 — ; 3 — ; 4 — , %; 2 — ; 5 — , %; 1 — ; 2 — (95%);
6 — , (105%);
.2 —

D
()
()

D.1 — () ()

()		$\pm 13 (0,5)$	$\overset{\wedge}{2}$ $\pm 25 (1,0)$	$\overset{\wedge}{3}$ $\pm 3(0,12)$	>4 $\pm 3(0,12)$	$\pm 3(0,12)$
0,5	3	760 (30)	1230 (48,5)	465 (18,25)	465 (18,25)	685 (27)
1	3	760 (30)	1535 (60,5)	615(24,25)	615 (24,25)	685 (27)
1,5	3	760 (30)	1840 (72,5)	770 (30,25)	770 (30,25)	685 (27)
2	4	760 (30)	2145 (84,5)	920 (36,25)	615 (24,16)	685 (27)
2,5	3	915(36)	1535 (60,5)	615 (24,25)	615 (24,25)	840 (33)
3	3	915(36)	1840 (72,5)	770 (30,25)	770 (30,25)	840 (33)
3,5	4	915(36)	2145 (84,5)	920 (36,25)	615 (24,16)	840 (33)
4	4	915(36)	2450 (96,5)	1075 (42,25)	715 (28,16)	840 (33)
5	3	1065 (42)	1840 (72,5)	770 (30,25)	770 (30,25)	990 (39)
5,5	4	1065 (42)	2145 (84,5)	920 (36,25)	615 (24,16)	990(39)
6	4	1065 (42)	2450 (96,5)	1075 (42,25)	715 (28,16)	990 (39)
6,5	5	1065 (42)	2755 (108,5)	1225 (48,25)	615 (24,12)	990 (39)
7	4	1245 (49)	2145 (84,5)	920 (36,25)	615 (24,16)	1170 (46)
7,5	4	1245 (49)	2450 (96,5)	1075 (42,25)	715 (28,16)	1170 (46)
8	5	1245 (49)	2755 (108,5)	1225 (48,25)	615 (24,12)	1170 (46)
9	4	1395 (55)	2145 (84,5)	920 (36,25)	615 (24,16)	1320 (52)
9,5	4	1395 (55)	2450 (96,5)	1075 (42,25)	715 (28,16)	1320 (52)
10	5	1395 (55)	2755 (108,5)	1225 (48,25)	615 (24,12)	1320 (52)
11	4	1550 (61)	2145 (84,5)	920 (36,25)	615 (24,16)	1475 (58)
11,5	4	1550 (61)	2450 (96,5)	1075 (42,25)	715 (28,16)	1475 (58)
12	5	1550 (61)	2755 (108,5)	1225 (48,25)	615 (24,12)	1475 (58)
—		D.1.				

32601—2022



a) Для анкерных болтов размером 20 мм (3/4 дюйма).

D.1 — ()

()

- 1 ;
 - 2 ;
 - 3 ;
 - : ;
 - : ;
 - W: .
- .1 —

W				
	1 —			
	()	6.13.3		
	— -	6.1.22		
		6.3.13		
	DN, PN 1)	6.4.1.1,6.4.2		
	()	7.3		
		8.3.2		
	— -	8.3.3.3)		
	—	8.3.4.3.4		
	— -	8.3.3.5)		
		6.13.4		
	, 1)			
	1)			
	(P&ID)			
		7.5		
		6.13.2		
		6.10.2.4		
		8.4.2.1		
		8.4.7		

32601—2022

. 1

		8.4.2.2, 8.4.2.3, 8.4.2.5, 8.4.27, 8.4.2.9, 8.4.12				
		8.4.2.4				
		8.4.1, 8.4.2.6, 8.4.2.8				
		8.4.3, 8.4.5, 8.4.6				
2—		(1)			
		6.12.1.8				
	()	6.12.1.5, 8.2.2.1			
	()	8.3.2			
	(,)	6.6.7, 6.6.9, 6.6.10, 6.6.13, 6.7.4, 9.2.2.4, 9.2.3, 9.3.3.1, 9.3.4.2, 9.3.8.2.1, - d) 9.3.12.2		
)	(-	8.3.3, 8.3.4.3	
3—		(1 2)			
			6.12.3.1			
			6.12.3.2			
		/	6.9.4, 9.2.4.2			
		-	9.27.5			
		,	7.3.21			
			8.3.4.2			
			8.3.4.4			
			8.3.4.5			
			8.3.4.6			
		()	8.3.47, 9.3.9.2		
1)						

(F)

F.1

F.1.1

F.1.2

(. 6.3.3),

)

(M_{RCA}),

(F.3)—(F.5).

21—25,

$$^{\wedge}RCA < 1^{15} (^{\wedge}RST5 + ^{\wedge}RDTs)'$$

$$|^{\wedge}YCA| < 2 > 0 (^{\wedge}YST5 + ^{\wedge}YDTs)' \tag{^{\wedge}.4}$$

$$^{\wedge}RCA < 1^{15} (MRST5 + MRDT5)- \tag{F.5}$$

$$F_{RCA} = [(F_{XCA})^2 + (F_{YCA})^2 + (F_{ZCA})^2]^{0.5},$$

$$F_{XCA} = F_{XSA} + F_{XDA};$$

$$^{\wedge}YCA = ^{\wedge}YSA + ^{\wedge}YDA;$$

$$^{\wedge}ZCA = ^{\wedge}ZSA + ^{\wedge}ZDA;$$

$$MRCA = \llcorner AW + (MYCA)^2 + (^{\wedge}ZCA)^2 \gg^{0.5},$$

$$M_{XCA} = A4_{XSA} + A4_{XDA} - [(FYSA)(z^8) + (FYDA)(zD) - (F^{\wedge} 8) - ^{\wedge}$$

$$^{\wedge}YCA = ^{\wedge}YSA + ^{\wedge}YDA - XSAx^z^8 + XDAX^2^{\wedge} \sim (FzSA)(x^8) - ZDAX^XD)V1000$$

$$MZCA = MZSA + MZDA - [(W)(yS) + (^{\wedge}ZDA)(yD) \llcorner (W^{\wedge}8) \llcorner (W(xD)V1000$$

xS, yS, zS —

X, Y Z ;

xD, yD, zD —

Y Z X,

USC 1000

12.

F.1.3

F.1.2,

[60].

32601—2022

F.2

() 6), -
 , , -
 , 5,
 41 (5950 psi). 40^{1\}
 (F.8) (F.6), (F.7)

$$= (/2) + (^2/4 + ^2)^{0.5} < 41, \tag{F.6}$$

$$\sigma_L = [1,27 F_y/(D_o^2 - D_i^2)] + [10200 D_o \cdot (M^2 + M^2)^{0.5}/(D_o^4 - D_i^4)], \tag{F.7}$$

$$= [1,27 (F^2 + F_f)^{0.5}/(D_o^2 - D_i^2) + \pi D_o (IM_y)]/(D_o^4 - D_i^4). \tag{F.8}$$

USC

$$= (/2) + (^2/4 + ^2)^{0.5} < 5950, \tag{F.9}$$

$$\sigma_L = [1,27 F_y/(D_o^2 - D_i^2)] + [122 D_o (M^2 + M^2)^{0.5}/(D_o^4 - D_i^4)], \tag{F.10}$$

$$\tau = [1,27(F^2 + F^2)^{0.5}/(D_o^2 - D_i^2) + [61D_o(IM_y)]/(D_o^4 - D_i^4)]. \tag{F.11}$$

Op — (- .);
 oL — (- .);
 — (- .);
 Fx — X;
 Fy — Y;
 Fz — Z;
 — X;
 — Y;
 Mz — Z;
 Dj, D_o — ()
 Fx, Fy, Fz, Mz, SA, DA, Fy
 21. (F.8) (F.11)

F.3

F.4,
 — 2, 2 5
 (. 24 25). 1, 5
 (. 23);
 D — ;
 Dt — 40^{1\} -
 D_o — 40^{1\} -
 F — (-);
 FR — ; FRSAH FRDA -
 5 ; FRST5 FRDT5 -
 — / (-);
 MR — ; MRSA MRDA -
 5 ; MRST5 MRDT5 -

1) . Schedule 40 noASME/ANSI.

Q_p — , (-);
 Q_L — , ();
 — , ();
 S — :
 , , Z — , ();
 X, Y, Z — (. 21—25);
 — ;
 5 — 5.

F.4

F.4.1 1 —

F.4.1.1

(2) —
 F.1. — F.2. — , —
 —) F.1.2.

F.4.1.2

F.4.1.2.1

a) F.1.2, —

:
 DN 250 :

$I^{FXSA}/I^{FXSTS} = 1+12 \cdot 900/66701 = 1,93 < 2,00$

$I^{FYSA}/I^{FYST5} = 10/5340 = 0 < 2,00$

$I^{FZSA}/I^{FZSTS} = |-8852/4450| = 1,99 < 2,00$

$I^{MXSA}/I^{MXSTS} = |-1356/5020| = 0,27 < 2,00$

$I^{MYSA}/I^{MYST5} = 1-5017/2440 = 2,06 > 2,00$

$I^{MZSA}/I^{MZSTS} = |-7458/3800| = 1,96 < 2,00$

M_{YSA} , 5 (M_{YSA}),

-4879. :

$I^{MYSA}/I^{MYST5} = |-4879/2440| = 1,999 < 2,00$

DN 200 :

$I^{FXDA}/I^{FXDT5} = |1+7117/37801| = 1,88 < 2,00$

$F_{YDA}/I^{FYDT5} = 1-445/31101 = 0,14 < 2,00$

$I^{FZDA}/I^{FZDT5} = |1+8674/48901| = 1,77 < 2,00$

$I^{MXDA}/I^{wXDT5} = |1+678/35301| = 0,19 < 2,00$

$I^{MYDA}/I^{MYDT5} = 1-3390/17601 = 1,93 < 2,00$

$I^{MZDA}/I^{MZDT5} = 1-4882/25801 = 1,89 < 2,00$

M_{YSA} , -4879, a) F.1.2.

F.1 — , 1

	, DN	X,	,	Z,
	250	+267	0	0
	200	0	-311	+381

F.2 — 1

	,	,	,
F_{XSA}	+12900	M_{XSA}	-1356
F_{YSA}	0	M_{YSA}	-5017 ¹⁾
F_{ZSA}	-8852	M_{ZSA}	-7458

32601—2022

F.2

	,H		
F _{XDA}	+7117	M _{XDA}	+678
F _{YDA}	-445	M _{YDA}	-3390
F _{ZDA}	+8674	M _{ZDA}	-4882
1)См. E.4.1.2.1.			

F.4.1.2.2 , b) F.1.2,

$$F_{RSA} = \sqrt{<F_XSA>^2 + <F_YSA>^2 + (F_{ZCA})^2}^{0.5} = [(+12900)^2 + ()^2 + (-8852)^2]^{0.5} = 15645.$$

$$M_{RSA} = \sqrt{K^M XSA)^2 + <M_YSA>^2 + (M_{ZSA})^2}^{0.5} = (356)^2 + (-487)^2 + (-7458)^2]^{0.5} = 9015.$$
 (F.1):

$$\sqrt{RSA^{1.5} \cdot FRST5} + \sqrt{RSA^{1.5} \cdot WRST5} < 2$$

$$15645/(1,5 \cdot 9630) + 9015/(1,5 \cdot 6750) < 2,$$

$$1,96 < 2.$$

$$F_{RDA} = \sqrt{W + <F_YDA>^2 + (F_{ZDA})^2}^{0.5} = [(+7117)^2 + (-445)^2 + (+8674)^2]^{0.5} = 11229.$$

$$M_{RDA} = \sqrt{(4<DA>)^2 + (M_YDA)^2 + (M_{ZDA})^2}^{0.5} = [(+678)^2 + (-3390)^2 + K882)^2]^{0.5} = 5982.$$
 (F.2):

$$\sqrt{RDA^{1.5} \cdot FRDT5} + \sqrt{RDA^{1.5} \cdot ARDT5} < 2$$

$$11229/(1,5 \cdot 6920) + 5982/(1,5 \cdot 4710) < 2,$$

$$1,93 < 2.$$

F.4.1.2.3 b) F.1.2) F.1.2 :

$$F_{RCA} = \sqrt{<F_XCA>^2 + <F_YCA>^2 + (F_{ZCA})^2}^{0.5}$$

$$F_{XCA} = (+12900) + (+7117) = +20017,$$

$$F_{YCA} = () + (445) = -445.$$

$$F_{ZCA} = (-8852) + (+8674) = -178,$$

$$F_{RCA} = [(+20017)^2 + (-445)^2 + (-178)^2]^{0.5} = 20023.$$
 (F.3):

$$F_{RCA} < 1,5 \cdot (FRST5 + FRDTS)$$

$$20023 < 1,5 \cdot (9630 + 6920),$$

$$20023 < 24825.$$

$$M_{YCA} = M_YSA + M_YDA + [(F_XSA) \cdot (Z^S) + (F_XDA) \cdot (Z^D) + (F_ZSA) \cdot (X^S) + (F_ZDA) \cdot (X^D)]/1000 = K879 + (-3390) + [(+12900) \cdot (0,00) + \dots + (+7117) \cdot (+381) - (-8852) \cdot (+267) - (+8674) \cdot (0,00)]/1000 = -3194.$$
 (F.4) :

$$|M_{YCA}| < 2,9 \cdot (M_YST5 + M_YDT5)$$

$$|-3194| < 2,0 \cdot (2440 + 1760),$$

$$3194 < 8400.$$

$$M_{RCA} = \sqrt{<M_XSA>^2 + <M_XDA>^2 + [(F_YSA) \cdot (Z^S) + (F_YDA) \cdot (Z^D) + (F_ZSA) \cdot (X^S) + (F_ZDA) \cdot (X^D)]/1000}$$
) F.1.2):

$$\begin{aligned}
 & \text{"MysA} + \text{^YDA} + \text{XSA} \text{' (z\$) + (\text{^~XDA}) \text{' (zD) ZSA} \text{' (x\$) ZDA} \text{' (xD)]/1000} \\
 \text{WZCA} &= \text{^MZSA} + \text{^MZDA} - \text{^FXSA} \text{' (< \text{^}) + (\text{'W} \text{' (> \text{' (FYSA) \text{' (<^S) \text{' (FYDA) \text{' (<xD)]/1000} \\
 \text{^MRCA} &= [(\text{^MXCA})^2 + (\text{^WYCA})^2 + (\text{^ZCA})^2]^{0.5} \\
 \text{M}_{\text{XCA}} &= (\text{"1356}) + (+678) - [(0) \cdot (0,00) + (-445) \cdot (+381) - (-8852) \cdot (0,00) - (+8674) \cdot (-311)]/1000 = -3206, \\
 \text{M}_{\text{YCA}} &= \text{"3194 (.)}. \\
 \text{M}_{\text{ZCA}} &= (-7458) + (-4882) - [(+12900) \cdot (0,00) + (+7117) \cdot (-311) - (0) \cdot (+267) - (-445) \cdot (0,00)]/1000 = -10127, \\
 \text{M}_{\text{RCA}} &= [(-3206)^2 + (-3194)^2 + (-10127)^2]^{0.5} = 11092. \\
 & \text{(F.5) :}
 \end{aligned}$$

$$\begin{aligned}
 \text{^WRCA} &< 1.5 \cdot (\text{M}_{\text{RST5}} + \text{^WRDT5}) \\
 11092 &< 1.5 \cdot (6750 + 4710), \\
 11092 &< 17190.
 \end{aligned}$$

) F.1.2,

F.4.2 2 —
F.4.2.1

DN80 DN100 178 , F.3. -
F_{ZSA}, M_{ZSA} M_{XDA} , 5 ().
F.2, , -
41 .

F.3 —

2

	,H		,
—	—	DN 100	—
F _{XSA}	-2224	W _{XSA}	+136
F _{YSA}	-5338	M _{YSA}	-2034
F _{ZSA}	+1334	M _{ZSA}	+1356
—	—	DN 80	—
F _{XDA}	+1334	M _{XDA}	+2712
F _{YDA}	-2224	M _{YDA}	+271
F _{ZDA}	+445	W _{ZDA}	+136

F.4.2.2

F.4.2.2.1

$$\begin{aligned}
 & 40 \quad \text{DN 100, } D_o = 114 \quad D_i = 102 \quad : \\
 D^2 - \text{' }^2 &= (114)^2 - (102)^2 = 2592, \\
 D^* - \text{' }^4 &= (114)^4 - (102)^4 = 6,065 \cdot 10^7, \\
 K^{\text{^FXSA} >^2 + (\text{^FZSA})^2]^{0.5}} &= [(-2224)^2 + (+1334)^2]^{0.5} = 2593, \\
 K^{\text{^MXSA}^2 + \text{^MZSA}^2]^{0.5}} &= (+136)^2 + (+1356)^2]^{0.5} = 1363. \\
 & \text{(F.7)}
 \end{aligned}$$

, O_s.

$$\begin{aligned}
 & \text{F}_{\text{YSA}} \text{' ; } \text{F}_{\text{YSA}} \\
 \text{°s} &= [1,27 \text{ F}_{\text{YSA}} / (D^2 - \text{' }^2)] + [10200 \text{ D}_o (\text{M}_{\text{XSA}}^2 + \text{M}_{\text{ZSA}}^2) \text{' (D}_o^4 - \text{' }^4)] = \\
 &= [1,27 \cdot (-5338) / 2592] + [10200 \cdot 114 \cdot 1363 / (6,065 \cdot 10^7)] = 23,52 \\
 & \text{(F.8)} \quad \text{T}_s:
 \end{aligned}$$

$$\begin{aligned}
 t_s &= [1,27 \cdot (\text{F}_{\text{XSA}})^2 + (\text{F}_{\text{ZSA}})^2]^{0.5} / (Dg \text{' }^2)] + [0,51 \cdot 10^4 \text{ D}_o (|\text{M}_{\text{YSA}}|) / (D^4 - D^4)] = \\
 &= (1,27 \cdot 2593 / 2592) + [5100 \cdot 114 \cdot (|-2034|) / (6,065 \cdot 10^7)] = 20,77
 \end{aligned}$$

(F.6):

$$s = (o_s/2) + (o_s^{2/4} + T_s^2)^{0.5} < 41 = (+23,52/2) + [(+23,52)^2/4 + (+20,77)^2]^{0.5} < 41 = +35,63 < 41.$$

32601—2022

F.4.2.2.2

$$D_S - D = (89)^2 - (78)^2 = 1837,$$

$$-D = (89)^4 - (78)^4 = 2,573 \cdot 10^7,$$

$$[(F/DA)^2 + (FZDA)^{2 \cdot 10^5} = +1334)^2 + (+445)^{2 \cdot 10^5} = 1406,$$

$$K^{MXDA} >^2 + <^M ZDA)^{2 \cdot 10^5} = [(+2712)^2 + (+136)^{2 \cdot 10^5} = 2715.$$

(F.7)

$$+D = 1,27 \cdot F_{YDA} / (D^2 - D^2) + [10200 \cdot D_0 \cdot (M_{XDA}^2 + M_{ZDA}^2) < > .5] / (D^4 - D^4) =$$

$$= [1,27 \cdot (+2224) / 1837] + [10200 \cdot (89) \cdot (2715)] / (2,573 \cdot 10^7) = 97,33.$$

(F.8)

$$T_D = 11,27 \cdot (F_{XDA})^2 + (F_{ZDA})^{2 \cdot 10^5} / (D_0 - D_i^2) + 15100 \cdot D_0 \cdot (K_{MH} - D_i^4) =$$

$$= [1,27 \cdot 1406 / 1837] + [5100 \cdot 89 \cdot (1 + 2711) / (2,573 \cdot 10^7)] = 5,75.$$

$$OPD = (Q_D / 2) + (O_{D2} / 4 + T_D) 0,5 < 41 = (+97,33 / 2) + [(+97,33) / 4 + (+5,75)^{2 \cdot 10^5}]^{0,5} = +97,67 > 41.$$

50 % 1356 • M_{XDA} 41 M_{XDA} M_{XDT5} 1900 •

F.4.3 1 — USC

F.4.3.1

(2) F.4. F.5. — F.1.2. F.4 — 1

		X	Y	Z
	10	+10,50	0	0
	8	0	-12,25	+15

F.5 — 1

F _{XSA}	+2900	M _{XSA}	-1000
F _{YSA}	0	M _{YSA}	-3700 ¹⁾
F _{ZSA}	-1990	M _{ZSA}	-5500
F _{XDA}	+ 1600	M _{XDA}	+500
F _{YDA}	-100	W _{YDA}	-2500
F _{ZDA}	+ 1950	M _{ZDA}	-3600
1)См. F.4.1.2.1.			

F.4.3.2

F.4.3.2.1 a) F.1.2, -

:

10 :

$$|F_{XSA} / F_{XST5}| = 1 + 2900 / 15001 = 1,93 < 2,00;$$

$$|F_{YSA} / F_{YST5}| = 10 / 1200 = 0 < 2,00;$$

$$|F_{ZSA} / F_{ZST5}| = 1 - 1990 / 10001 = 1,99 < 2,00;$$

$$|M_{XSA} / M_{XST5}| = 1 - 1000 / 37001 = 0,27 < 2,00;$$

$$|M_{YSA}/M_{YST5I}| = 1-3700/18001 = 2,06 > 2,00;$$

$$|M_{ZSA}/M_{ZST5I}| = 1-5500/28001 = 1,96 < 2,00.$$

$$M_{YSA} \quad , \quad 5 (\quad USC)$$

$$-3599. \quad :$$

$$|M_{YSA}/M_{YST5I}| = 1-3599/18001 = 1,999 < 2,00.$$

$$8 \quad :$$

$$|XDA/XDT5I| = 1+1600/8501 = 1,88 < 2,00;$$

$$|YDA/YDT5I| = 1-100/7001 = 0,14 < 2,00;$$

$$|ZDA/ZDT5I| = 1+1950/11001 = 1,77 < 2,00;$$

$$|MXDA/MXDT5I| = |1+500/2600| = 0,19 < 2,00;$$

$$|MYDA/MYDT5I| = |-2500/1300| = 1,93 < 2,00;$$

$$|MZDA/MZDT5I| = 1-3600/19001 = 1,89 < 2,00.$$

$$M_{YSA} \quad -3599,$$

a) F.1.2.

F.4.3.2.2

b) F.1.2,

:

$$F_{RSA} \quad M_{RSA}$$

$$F_{RSA} = |FXSA|^2 + |FYSA|^2 + (ZCA)^{2 \cdot 0,5} = [(+2900)^2 + (0)^2 + (-1990)^2]^{0,5} = 3517;$$

$$M_{RSA} = |MXSA|^2 + |MYSA|^2 + (MZSA)^{2 \cdot 0,5} = [(-500)^2 + (-2500)^2 + (-3600)^2]^{0,5} = 4411;$$

(F.1):

$$|RSA|^{1,5} \cdot |RST5| + |RSA|^{1,5} \cdot |RST5|^2$$

$$3517/(1,5 \cdot 2200) + 4411/(1,5 \cdot 5000) < 2,$$

$$1,95 < 2.$$

$$F_{RDA} \quad M_{RDA}$$

$$F_{RDA} \quad M_{RDA}:$$

$$F_{RDA} = (W + |FYDA|)^2 + |FZDA|^{2 \cdot 0,5} = [(+1600)^2 + (|-100|)^2 + (|+1950|)^2]^{0,5} = 2524,$$

$$M_{RDA} = [|MXDA|^2 + |MYDA|^2 + (MZDA)^{2 \cdot 0,5}]^{0,5} = [(+500)^2 + (-2500)^2 + (-3600)^2]^{0,5} = 4411.$$

(F.2):

$$|RDA|^{1,5} \cdot |RDT5| + |RDA|^{1,5} \cdot |RDT5|^2$$

$$11229/(1,5 \cdot 1560) + 4411/(1,5 \cdot 3500) < 2,$$

$$1,92 < 2.$$

b) F.1.2,

F.4.3.2.3

) F.1.2,

:

$$; F_{RCA}$$

) F.1.2:

$$XCA = FXSA + XDA;$$

$$YCA = FYSA + FYDA;$$

$$ZCA = ZSA + ZDA;$$

$$F_{RCA} = \sqrt{W + (FYCA)^2 + (ZCA)^2}^{0,5};$$

$$F_{XCA} = (+2900) + (+1600) = +4500;$$

$$F_{YCA} = (0) + (-100) = -100;$$

$$F_{ZCA} = (-1990) + (+1950) = -40;$$

$$F_{RCA} = [(+4500)^2 + (-100)^2 + (-40)^2]^{0,5} = 4501.$$

(F.3):

$$|RCA| < 1,5 \cdot (RSTS + RDT5)$$

$$4501 < 1,5 \cdot (2200 + 1560),$$

$$4501 < 5640.$$

32601—2022

) F.1.2:

$$M_{YCA} = M_{YSA} + M_{YDA} + K^{\wedge}XSA)^{\wedge}z^S + (W^{\wedge}z^D)^{\wedge}ZSA)^{\wedge}x^S)^{\wedge}ZDA)^{\wedge}W^{12} =$$

$$= (-3599) + (-2500) + [(+2900) \cdot (0,00) + \dots + (+1600) \cdot (+15) - (-1990) \cdot (+10,5) - (+1950) \cdot (0,00)]/12 = -2358.$$

(F.4) :

$$|M_{YCA}| < 2 \cdot 0^{\wedge}(\wedge YST5 + \wedge YDTs)^{\wedge}$$

$$|-2358| < 2,0 - (1800 + 1300),$$

$$2358 < 6200.$$

M_{RCA} (.) F.1.2):

$$= 4 < SA + 4 < DA + K^{\wedge}FYSA)^{\wedge}z^S + (FYDA)^{\wedge}z^D)^{\wedge}FZSA)^{\wedge}z^S)^{\wedge}FZDA)^{\wedge}x^S)^{\wedge}1/12 =$$

$$\wedge YCA = \wedge YSA + \wedge YDA + ((FXSA)^{\wedge}z^S + (FXDA)^{\wedge}z^A)^{\wedge}FZSA)^{\wedge}x^S)^{\wedge}FZDA)^{\wedge}x^D)]/12;$$

$$M_{ZCA} = M_{ZSA} + M_{ZDA} - K^{\wedge}XSA)^{\wedge}z^S + (FXDA)^{\wedge}z^A)^{\wedge}FYSA)^{\wedge}z^S)^{\wedge}FYDA)^{\wedge}z^D)]/12 =$$

$$M_{RCA} = [(W_{XCA})^2 + (M_{YCA})^2 + (W_{ZCA})^2]^{0,5};$$

$$M_{XCA} = [(100^{\circ}) + (+50^{\circ}) + K^{\circ} (z^{\circ}) + (1^{\circ})] \cdot (+15,00) - (-1990) \cdot (0,00) - (+1950) \cdot (-12,25)]/12 = -2366.$$

$$M_{YCA} \sim -2358 (.);$$

$$M_{ZCA} = (-550^{\circ}) + ("3600) - [(+2900) \cdot (0,00) + (+1600) \cdot (-12,25) - (0) \cdot (+10,50) - (-100) \cdot (0,00)]/12 = -7467;$$

$$M_{RCA} = [(-2366)^2 + (-2358)^2 + (-7467)^2]^{0,5} = 8180.$$

(F.5) :

$$M_{RCA} < 1,5^{\wedge}(M_{RST5} + M_{RDT5})^{\wedge}$$

$$8180 < 1,5 \cdot (5000 + 3500),$$

$$8180 < 12750.$$

) F.1.2,

F.4.4 2 — USC

F.4.4.1

NPS 3 NPS 4x7 (6), F.6.
 F_{ZSA}, M_{ZSA}, M_{XDA} 5 ()
 USC). F.2, 5950 psi.

F.6 —

2

		NPS 4	
F _{XSA}	-500	W _{XSA}	+100
F _{YSA}	-1200	M _{YSA}	-1500
F _{ZSA}	+300	M _{ZSA}	+1000
		NPS 3	
F _{XDA}	+300	M _{XDA}	+2000
F _{YDA}	-500	A _{4_{YD}A}	+200
F _{ZDA}	+100	^ZDA	+100

F.4.4.2

F.4.4.2.1

$$D_0^2 - 2 = (4,500)^2 - (4,026)^2 = 4,04,$$

$$D_0^4 - 4 = (4,500)^4 - (4,026)^4 = 147,34,$$

$$[(\wedge XSA)^2 + (FZSA)^2]^{0,5} = [(-500)^2 + (+300)^2]^{0,5} = 583,$$

$$[(M_{XSA})^2 + (M_{ZSA})^2]^{0,5} = [(+100)^2 + (-1500)^2]^{0,5} = 1005.$$

(F.10)

O_{LS}.

Y

F_{ys}^A

;

F_{YSA}

$$c_{L,s} = [1,27 \cdot F_{YSAW} \cdot (D^2 - 2)] + [122 \cdot D_o \cdot (M_{XSA}^2 + M_{ZSA}^2) \cdot 0,5 / (D^4 - D_{J4})] =$$

$$= [1,27 \cdot (-1200) / 4,04] + [122 \cdot 4,500 \cdot 1005] / 147,34 = 3367.$$

(F.11)

$$T_s = [1,27 \cdot (F_{XSA})^2 + (F_{ZSA})^2] \cdot 0,5 / (D^2 - 2) + [61 \cdot D_q \cdot (|M_{YSA}|)] / (\epsilon > 4 - D^4) =$$

$$= (1,27 \cdot 583 / 4,04) + [61 \cdot 4,500 \cdot (|-1500|)] / 147,34 = 2978.$$

T_s :

(F.9):

$$Op_s = (o_s/2) + (o_s/4 + T_s/2) \cdot 0,5 < 5950 = (+3367/2) + [(+3367)^2/4 + (+2978)^2]^{0,5} < 41 = +5105 < 5950.$$

F.4.4.2.2

40

3

$D_o = 3,500$

$= 3,068$

:

$$- D^2 = (3,500)^2 - (3,068)^2 = 2,84$$

$$D^4 - D^2 = (3,500)^4 - (3,068)^4 = 61,47,$$

$$K^{FXDA} \cdot D^2 + (F_{ZDA})^2]^{0,5} = (+300)^2 + (+1) \cdot 2]^{0,5} = 316,$$

$$K^{MXDA} \cdot D^2 + (M_{ZDA})^2]^{0,5} = (+2000)^2 + (+1) \cdot 2]^{0,5} = 2002.$$

(F.10)

F_{YDA}

;

F_{YDA}

$$\%D = [1,27 \cdot F_{YDA} / (D^2 - 2)] + [122 \cdot D_o \cdot (M_{XDA}^2 + M_{ZDA}^2) \cdot 0,5] / (D^4 - D_{J4}) =$$

$$= [1,27 \cdot (+500) / 2,84] + [122 \cdot (3,5) \cdot (2002)] / 61,47 = 14131.$$

(F.11)

$$T_D = [1,27 \cdot (F_{XDA})^2 + (F_{ZDA})^2] \cdot 0,5 / (D^2 - 2) + [61 \cdot D_q \cdot (|M_{YDA}|)] / (D^4 - D_{J4}) =$$

$$= [1,27 \cdot 316 / 2,84] + [61 \cdot 3500 \cdot (|+200|)] / 61,47 = 836.$$

< D

(F.9):

$$°P,D = (°D^2) + (°D^{2/4} + T_D^2)^{0,5} < 5950 = (+14131/2) + [(+14131)^2/4 + (+836)^2]^{0,5} = +14181 > 5950.$$

O_{LD}

T_D :

M_{XDA}

5950 psi.

50 % 1000

M_{XDA}

M_{XDT5}

1400

32601—2022

(G)

G.1

G.1 —

	°C	°F			
	< 100	<212		1-1 I-2	—
	< 120	<250		1-1 I-2	1)
	120—175	250—350		S-5	1)
	> 175	>350		S-6, -6	1)
	> 95	>200		-6	—
	>95	>200		S-6	—
	> 95	>200		-6	—
	< 175	<350		S-3 S-6	2)
	> 175	>350		-6	—
	<230	<450		S-1	—
	>-46	>-50		S-1 (LCB)	8)
	>-73	>-100		S-1 (LC2)	8)
	>-100	>-150		S-1 (LC3)	8), 9)
	>-196	>-320		-7 -8	8), 9)
	<230	<450		S-1	—
	230—370	450—700		S-6	2), 3)
	> 370	>700		-6	2)
	230—370	450—700		S-4	3)
	<230	<450		S-1	—
	< 175	<350		1-1	—
< 20 %	< 100	<212		S-1	4)
	> 100	>212		—	5)
	<95	<200		—	6)
	<260	<470		D-1	—

G. 1

	°C	°F			
				D-1 D-2	6)
()				S-1	—
-	<370	< 700		-6	—
	< 175 <370	< 350 < 700		-6 -8	—
(DEA), (), (TEA), -	< 120	<250		S-1	—
DEA TEA	< 120	<250		S-1 S-8	4), 7)
() ₂	80—150	175—300		S-9	4)
() ₂ H ₂ S)	8—150	175—300		S-8	4), 7)
, DEA, TEA	<80	< 175		S-1 S-8	4)
- 85 %	<38	< 100		S-1	2)
- 85 %	<230	<450		-8	2)
96 %	<38	< 100		S-9	2)

1)
2) 230 °C (450 °F),
S-8
95 °C (200 °F).
3) 231 °C 370 °C (451 °F 700 °F). S-4
4)
5) Ni-Cu UNS N08007.
6)
7) 95 °C (200 °F),
8) LCB, LC2, LC3 6.12.1.6 6.12.4.
C23-45BL, C43E2al C43L LCB, LC2, LC3
ISO 4991. LCB, LC2, LC3
ASTM 352/ 352 LCB, LC2, LC3
9) 196 °C (320 °F).
1 —
2 —
3 — (. 6.2.1.6),

32601—2022

()

.1
(. 6.12.1.2). -
.2, .4
.2
-
-
-

.1 () —

		2)													
		1-1	I-2	S-1	S-3	S-4	S-5	S-6	S-8 ¹²⁾	S-9 ¹²⁾	C-6	A-7	A-8	D-1 ^{1°)}	D-2 ^{1°)}
		CI	CI	STL	STL	STL	STL	STL	STL	STL	12 %Cr	AUS	316AUS		-
		CI	BRZ	CI	-	STL	STL 12 %	12 %	316 AUS	Ni-Cu	12 %Cr	AUS ³⁾ 4)	316 AUS ⁴⁾		-
,		CI	CI	STL	STL	STL	STL	STL	STL	STL	12 %Cr	AUS	316AUS		-
(. .)	-	CI	BRZ	CI	-	CI	STL	12 %	316AUS	Ni-Cu	12 %Cr	AUS	316AUS		-
		CI	BRZ	CI	-	STL	STL	12 %	316AUS	Ni-Cu	12 %Cr	AUS	316AUS		-
11) -		CI	BRZ	CI	-	CI	12 % , .	12 % , .	316AUS . .5)	Ni-Cu	12 %Cr, ynp.	AUS ynp. .5)	316AUS ynp. .5)	, . .5)	- . .5)
11) -		CI	BRZ	CI	-	CI	12 % , .	12 % , .	316AUS . .5)	Ni-Cu	12 %Cr, ynp.	AUS ynp. .5)	316AUS ynp. .5)	, . .5)	- . .5)
4)		STL	STL	STL	STL	STL	4140	4140 ⁶⁾	316AUS	Ni-Cu	12 %Cr	AUS	316AUS		-
11) -		CI	BRZ	CI	-	CI	12 % , .	12 % , .	316AUS	Ni-Cu	12 %Cr, ynp-	AUS	316AUS		-
11)		CI	BRZ	CI	-	CI	12% , .	12 % , .	316AUS . .5)	Ni-Cu	12 %Cr, ynp.	AUS ynp. .5)	316AUS ynp. .5)	, . .5)	- . .5)
11)		CI	BRZ	CI	-	CI	12% , .	12 % , .	316AUS . .5)	Ni-Cu	12 %Cr, ynp.	AUS ynp. .5)	316AUS ynp. .5)	, . .5)	- . .5)
-		4140	4140	4140	4140	4140	4140	4140	4140	Ni-Cu ynp. ⁹⁾	4140	4140	4140	- 9)	- 9)

32601—2022

		2)													
		1-1	I-2	S-1	S-3	S-4	S-5	S-6	S-8 ¹²⁾	S-9 ¹²⁾	-6	-7	-8	D-1 ^{1°)}	D-2 ^{1°)}
		CI	CI	STL	STL	STL	STL	STL	STL	STL	STL	12 %	AUS	316AUS	
CI	BRZ	CI	- -	STL	STL	12 %	12 %	316 AUS	Ni-Cu	12 %	AUS ³⁾ 4*)	316 AUS ⁴⁾		-	
		AUS ⁷⁾	AUS ⁷⁾	AUS ⁷⁾	AUS ⁷⁾	AUS ⁷⁾	AUS ⁷⁾	AUS ⁷⁾	316 AUS ⁷⁾	Ni-Cu - - 7)	AUS ⁷⁾	AUS ⁷⁾	316 AUS ⁷⁾	- 7)	- 7)
		STL	STL	STL	STL	STL	STL	STL	STL	STL	AUS	AUS	316AUS		-
/	-	8****)	BRZ	BRZ	8)	-				-					
, - -		STL	STL	STL	STL	STL	316 AUS ¹³⁾	316 AUS ¹³⁾	316AUS	Ni-Cu	316 AUS ¹³⁾	316AUS	316AUS		-

1) 6.12.1.4.

2)

: CI — ; BRZ — ; - —
 ; STL — ; 12 % —
 12 %; 12 % ; AUS — ; AUS —
 ; 316 AUS — 2,0 % ; 316 AUS —
 ; — 40:60 60:40; —
 25 %, 6 %, 3 %, 0,2 %; ()
 ; 4140 — (AISI 4140), 0,40 %
 1 % 0,2 % ; Ni — (Monel), 70 % NI 30 % ;
 ; (NBR) —

- . 1
- 3) 316, 321 347 : 12 18 10 , 2 18 12 . 977; : AISI 302, 303, 304,
- 4) — (12 %- VS5) 4140 S-9, -7, -8 D-1.
- 5) (. G.1).
- (. 6.7.4)
- 6) S-6 175 °C (350 °F) 12 %- (. G.1).
- 7>
- 8) 45 °C (110 °F) (. 6.3.10).
- 9) 4140
- 10) .2 (PRE) 40. PRE
- PRE = $W_{Cr} + 3,3 \cdot W_{Mo} + 16 \cdot W_{N}$ W—
- 11) >) 6.7.4.
- 12) 95 °C (200 °F).
- 13) 12 % 17 %,

.2 () —

				ISO	ASTM	UNS ¹⁾	EN ²⁾			JIS			
	, - -	25	1412	185/Gr250	278/ 278 Class 30	F12401	EN 1561	EN-GJL-250	JL 1040	G 5501, FC 250			
	,	25	1412, 1412	185/Gr300	48/ 48 Class 25/30/40	F11701/ F12101	EN 1561	EN-GJL-250 EN-GJL-300	JL 1040 JL 1050	G 5501, FC 250/300			
	, - -	25	977	4991 23-45	216/ 216 Gr WCB	J03002	EN 10213	GP 240 GH	1.0619	G5151, CI SCPH 2			
				/	25	1050 8479	683-18- 25	A266 Class 4	K03506	EN 10222-2	P280 GH	1.0426	G3202, CI SFVC 2A
				, - -	25	1050	683-18- 25	A696 Gr B40	G10200	EN 10273	P295 GH	1.0481	G4051, CI S25C
				, 3)	45	1050	683-18- 45	A576 Gr1045	G10450	EN 10083-2	C45	1.0503	G4051, CI S45C
				4) -	38 , 40 4543	2604-2-F31	A193/A193M Gr B7	G41400	EN 10269	42 Cr Mo 4	1.7225	G4107, Class 2, SNB7	
				4)	45	1050	683-1- 45	A194/A194M Gr2H	K04002	EN 10269	C 35 E	1.1181	G4051, CIS45C
				-	17 , 14 2 19281	9328-4, P/PL 355 TN	A516/A516 Gr 65/70	02403/ K02700	EN 10028-3	P355 N P355 NL1	1.0562 1.0566	G3108, Gr SM400B	
					20	1050	9329-2 26	A106/A106M Gr	K03006	EN 10208-1	L 245 GA	1.0459	G3456, Gr. STPT370/410
					25, 30	1050	—	A105/A105M	K03504	—	—	—	G4051.CI S25C, G3202, CI SFVC 2A, SFVC2B

			ISO	ASTM	UNS ¹⁾				JIS
						EN ²⁾			
4140	-	38 , 40 4543, 30X13, 40X13 5632	—	434 Class	G41400)	EN 10083-1	42 Cr Mo 4	1.7225	G4105, CI SCM 440
	-	38 , 40 4543	2604-2-F31	193/ 193 Gr 7	G41400	EN 10269	42 Cr Mo 4	1.7225	G4107, Class 2, SNB7
		45 1050	683-1- 45	194/ 194 Gr2H	K04002	EN 10269	C45 E	1.1191	G4051, CI S45C
12 %	, - -	15 14 , 30X1 977	—	487/ 487 Gr CA6NM	J91540	EN 10213	GX4CrNi 13-4	1.4317	G5121, CI SCS6, SCS 6X
		15 14 , 30X1 977	—	743/ 743 Gr 15	J91150	EN 10283	GX 12 Cr 12	1.4011	G5121, CI SCS 1, SCS 1X1
		—	—	743/ 743 Gr CA6NM	J91540	EN 10283	GX4 CrNi 13-4	1.4317	G5121, CI SCS 6, SCS 1X1
	/ ,	20X13, 30X13, 40X13 5632	683-13-3	A182/A182MGr F6a CI 1 GrF6NM	S41000 S41500	EN 10250-4 EN 10222-5	X12 Cr13 X3 Cr Ni Mo 13-4-1	1.4006 1.4313	G3214, Gr. SUS410-A, CI SUS F6 NM
	/ ,	20X13, 30X13, 40X13 5632	683-13-2	A473 Type 410	S41000	EN 10088-3	X 12Cr13	1.4006	G3214, Gr. SUS410-A
	, - -	20X13, 30X13, 40X13 5632	683-13-3	A479/A479M Type 410	S41000	EN 10272	X12 Cr13	1.4006	G4303, Gr. SUS 410 403
	,	20X13, 30X13, 40X13 5632	683-13-3	A276 Type 410	S41400	EN 10088-3	X12 Cr 13	1.4006	G4303, Gr. SUS 410 403

			ISO	ASTM	UNS ¹⁾	EN ²⁾			JIS	
12%	,	³⁾	20X13, 30X13, 40X13 5632	683-13-4	276 Type 420 A473 Type 416 A582/A582M Type 416	S42000 S41600	EN 10088-3	X20 Cr 13 X20 CrS 13	1.4021 1.4005	G4303, Gr. SUS 420J1 420J2
		⁴⁾	20X13, 30X13, 40X13 5632	3506-1 4-70	A193/A193M Gr B6	S41000	EN 10269	X22CrMo V 12-1	1.4923	G4303, Gr. SUS 410 403
		⁴⁾	20X13, 30X13, 40X13 5632	3506-2 4-70	A194/A194M Gr6	S41000	EN 10269	X22CrMo V 12-1	1.4923	G4303, Gr. SUS 410 403
		-	08X13, 20X13, 30X13, 40X13 5632	683-13-3	A240/A240M Type 410	S41000	EN 10088-2	X12 Cr13	1.4006	G4304/4305, Gr. SUS 410 403
-	,	-	12 18 9 - 977	683-13-10	A351/A351M GrCF3	J92500	EN 10213-4	GX2 Cr Ni 19-11	1.4309	G5121, CI SCS 19A
			12 18 12 977	683-13-19	A351/A351M GrCF3M	J92800	EN 10213-4	GX2 CrNi Mo 19-11-2	1.4409	G5121, CI SCS 16A, 16AX
		-	12 18 9 977	—	A743/A743M GrCF3	J92500	EN 10283	GX2 Cr Ni 19-11	1.4309	G5121, CI SCS 19A
			12 18 12 977	—	A743/A743M GrCF3M	J92800	EN 10283	GX2 CrNi Mo 19-11-2	1.4409	G5121, CI SCS16A, 16AX
		/	12 18 10 - 5632	9327-5 XCrNi 18-10	A182A/A182M Gr F 304L	S30403	EN 10222-5	X2 Cr Ni 19-11	1.4306	G3214, Gr. SUS F 304L
			10 17 13 2 - 5632	9327-5 XCrNiMo17-12	A182A/A182M Gr F316L	S31603	EN 10222-5 EN 10250-4	X2 Cr Ni Mo 17-12-2	1.4404	G4304/4305, Gr. SUS 304L/ 316L

.2

			ISO	ASTM	UNS ¹⁾	EN ²⁾			JIS
-	5)	12 18 10 5632	9327-5 X2CrNi18-10	A479/A479M Type 304L, Type 316L, A276 Gr.316L	S30403 S31603	EN 10222-5	X2 Or Ni 19-11	1.4306 1.4404	G3214, Gr. SUS F 304L
		10 17 13 2 5632	9327-5 X2CrNi- 17-12	A479/A479M Type XM19	S20910	—	—	—	—
	-	12 18 10 10 17 13 2 5632	9328-5 X2CrNi- 17-12-2	A240/A240M Gr304L/316L	S30403 S31603	EN 10028-7	X2 Or Ni 19-11 X2 Cr Ni Mo 17-12-2	1.4306 1.4404	G4304/4305, Gr. SUS 304L/ 316L
		12 18 10 10 17 13 2 9940 9941	683-13-10 683-13-19	A312/A312M Type 304L, 316L	S30403 S31603	—	—	—	G3459, Gr. SUS 304LT- P/316LTP
		12 18 10 10 17 13 2 5632	9327-5 X2CrNi 18-10 X2CrNi- Mo17-12	A182/A182M Gr F304L Gr316L	S30403 S31603	EN 10222-5	X2 Cr Ni 19-11 X2 Cr Ni Mo 17-12-2	1.4306 1.4404	G3214, Gr. SUS F304L/F316L
		12 18 10 10 17 13 2 5632	3506-1 A4-70	A193/A193M GrB 8 M	S31600	EN 10250-4	X6 Cr Ni Mo Ti 17-12-2	1.4571	G4303, Gr. SUS 316
		12 18 10 10 17 13 2 5632	3506-2 A4-70	A194/A194M GrB 8 M	S31600	EN 10250-4	X6 Cr Ni Mo Ti 17-12-2	1.4571	G4303, Gr. SUS 316
6)	-	—	—	A890/A890M Gr 1 A995/A995M Gr 1	J93372	EN 10213-4	GX2 CrNiMoCuN- 25-6-3-3	1.4517	—

			ISO	ASTM	UNS ¹⁾	EN ²⁾			JIS	
6)	-			A890/A890M Gr3A A995/A995M Gr3A	J93371	—	—	—	G 5121, Gr. SOS 11	
				A890/A890M Gr4A A995/A995M Gr4A	J92205	EN 10213-4	GX2 CrNiMoCuN- 25-6-3-3	1.4517	G 5121, Gr. SOS 10	
	/			9327-5 X2CrNiMoN 22-5-3	A182/A182M GrF51	S31803	EN 10250-4 EN 10222-5	X2CrNiMoN 22-5-3	1.4462	—
				—	A479/A479M	S32550	EN 10088-3	X2CrNiMoCuN 25-6-3	1.4507	—
		—		9327-5 X2CrNiMoN 22-5-3	A276-S31803	S31803	EN 10088-3	X2CrNiMoN 22-5-3	1.4462	2312/B 2316, G 4303, Gr. SUS 329 J3L
	-	—	—	—	A240/A240M- S31803	S31803	EN 10028-7	X2CrNiMoN 22-5-3	1.4462	G 4304/G 4305, Gr. SUS 329 J3L
		—	—	—	A790/A790M- S31803	S31803	—	—	—	G 3459, Gr. SUS 329 J3LTP
		—		9327-5 X2CrNiMoN 22-5-3	A182/A182M GrF51	S31803	EN 10250-4 EN 10222-5	X2CrNiMoN 22-5-3	1.4462	2312/B 2316, Gr. SUS 329 J3L
		—	—	—	A276-S31803	S31803	EN 10088-3	X2CrNiMoN 22-5-3	1.4462	G 4303, Gr. SUS 329 J3L
		—	—	—	A276-S31803	S31803	EN 10088-3	X2CrNiMoN 22-5-3	1.4462	G 4303, Gr. SUS 329 J3L

			ISO	ASTM	UNS ¹⁾	EN ^{2,3,4,5)}			JIS
7)	-	-	-	890/ 890 Gr5A	J93404	EN 10213-4	GX2CrNiMoN 26-7-4	1.4469	—
				890/ 890 Gr6A	J93380	—	—	—	—
	/	—	—	182/ 182 Gr55	S32750 S32760	EN 10250-4 EN 10088-3	X2CrNiMoCu- WN 25-7-4	1.4501	G 4303, Gr. SUS 329 J4L
		—	—	A276-S32760 479/ 479 S32760	S32750 S32760	EN 10088-3	X2CrNiMoCu- WN 25-7-4	1.4501	G 4304/G 4305, Gr. SUS 329 J4L
	-	—	—	240/ 240 S32760	S32750 S32760	EN 10028-7	X2CrNiMoCu- WN 25-7-4	1.4501	—
		—	—	790/ 790 S32760	S32750 S32760	—	—	—	G 3459, Gr. SUS 329 4LTP
		—	—	182/ 182 GrF55	S32750 S32760	EN 10250-4 EN 10088-3	X2CrNiMoCu- WN 25-7-4	1.4501	2312/B 2316, Gr. SUS 329 J4L
		—	—	A 276 S32760	S32750 S32760	EN 10088-3	X2CrNiMoCu- WN 25-7-4	1.4501	G 4303, Gr. SUS 329 J4L
		—	—	A 276 S32760	S32750 S32760	EN 10088-3	X2CrNiMoCu- WN 25-7-4	1.4501	G 4303, Gr. SUS 329 J4L

1) UNS ()
 2) EN , AFNOR, BS, DIN, -
 3) (302).
 4) (4140).
 5) («1_»)
 ^ (PRE) 28. PRE = / + 3,3 w_{Mo} +
 + 16w_N, w—
 7) (PRE) 40.

140

. ()—

32601—2022

	, °C (°F)		25 (1), (; psi)	
()	-30 (-20)	+ 135 (+275)	2000(20; 300)	
()	-30 (-20)	+230 (+450)	3500 (35; 500) 14000 (140; 2000)	-
, 20 %-	-46 (-50)	+230 (+450)	2000 (20; 300)	
	-50 (-55) -100(-150) -195(-320) -100(-450)	+285 (+550) + 150 (+300) +400 (+750)	2000 (20; 300) 2750 (27,5; 400) 3500 (35; 500)	
1 —	(.) 6.7.4.			-
2 —	(, 12 %			-
3 —				-

.4 () —

	()					
			, (; psi)			
	1-1	1-2	< 500 (5; 75)	> 500 (5; 75)	< DN 25 (1 NPS)	< DN 40 (1/2 NPS)
(pipes)	1)		1)		—	(ISO 10684 ASTM 153/ 153)
(tubes) ²⁾	(AISI 316 -)		(AISI 316 -)		(AISI 316),	—
	800		800		200	
-	-		-		—	—
	, 3000		, 3000		(ISO 10684 ASTM 153/ 153)	
						—
(1 NPS) < DN 25						—
(1 1/2 NPS) < DN 40	—	—	—	—	—	—
-	—	(AISI 304, 316) ;	—	(AISI 304, 316) ;	—	—
	—	(AISI 4140)	—	(AISI 4140)	—	—

¹⁾ : DN 15 DN 20 (NPS 14 NPS %) — 4 , DN 25 (NPS 1) — 4,5 , DN 32, DN 40, DN 50 DN 65 (NPS 114, NPS 114, NPS 2, NPS 214) — 5 80 (Schedule 80) ANSI/ASME
DN 15 DN 40 (NPS 14 NPS 114) 40 (Schedule 40) DN 50 (NPS 2) .
²⁾ [* ()]: 12,7x1,66 (1/2 0,065); 19 2,6 (3/4 0,095); 25
2,9 (1 0,109) [73] 9567.

32601—2022

(I)

1.1

1.1.1

(. 9.2.4.1),
1.1.2—1.1.5.

1.1

-
-
-

1.1 —

1		-
2	(. 6.9.1.2)	
3	1 2	

1.1.2

) , « » : (. 6.9.1.2).

1 — « » ()

2 —

20 %

-
-

),

)

, 2,2

-

25 % 125 %

1)

-

-

-

2

2)

3)

4)

5)

—

)

1.1.3

()

f_{ni}

1.1.

f_{run}

1.1.4.

-
-
-

0,4, S § (1.1):

$$\delta = (2 - \epsilon)/(1 - i;^2)^{0,5}. \quad (1.1)$$

(1.2), 8

$$\epsilon = 5/2 \cdot = 1/(2 \cdot F_a). \quad (1.2)$$

:
 > 0,15,
 8 > 0,95,
 F_a < 3,33.

1 — API

2 — $\epsilon > 0,08$ f_{nj}/f_{run} 0,8 0,4

1.1.4

1.1, :


() ,

(4) (. 9.2.4.2.1),

1.1.5

(« 35 % ») /

32601—2022




X—

, 1—

; 2—

, f_n/f_{un} , Y—

1.1—



X — ; Y — ; 1 — ; 2 — ; 3 — ; 4 — ; 5 — ; 6, 8 — ; 7, 9 — ; b — ; 10 — ; 1 — ; 2 — ; 3 — ; 4 — ; 5 — ; 6, 8 — ; 7, 9 — ; b — ; 10 —

1.2 —

1.2

1.2.1

75 %

(. 1.1.4),

1.2.2

32601—2022

1 - ,

) ;

) , 90 °

[.)].

(, 8 9,), -

150 % 200 %

8 .

I.2.3 , 1 - , -

I.2.4 , -

:) () -

) - 10 % ; 35 %

) -

I.2.5 , I.2.4, -

, , -

$L/D < 0,15,$ $UD > 0,15,$ -

, -

, -

I.2.6 , -

I.3 :

) (. 9.2.4.1.1);

) ;

) (. 1.2);

d) ;

) () ,

f) (. 1.1.4); (. 1.2.3);

) (. 1.2.5).

)—g) I.3

(J)

J.1

J.2

J.2.1

).

J.3

J.3.1

19.

J.3.2

(3000).

2700 (6000)

1350

J.4

J.4.1

J.4.1.1

J.4.1.2

6 (12,

J.4.2.

J.4.2

J.4.2.1

1440 • t_{max} 2880 • (2 oz • in 4 oz • in), 1440 • (2 oz • in),

J.4.2.2

60° 30°.

(6 12)

J.4.2.3

J.4.2.4

J.4.2.5

(J.1 J.2).

« » ;

(J.3 J.4).

32601—2022

() :
 :
 (, . ,) :
 : / ,
 : /
 (W) — (): (lb)
 $U_{max} = 6350 / (4W/n)$
 $6350 \cdot / / . (4 \cdot lb / /) : * (oz \cdot in)$
 $(2 U_{max}) : * (oz \cdot in)$
 $R - : (in)$
 — //?
 / (oz*in/in): (oz)
 — 1 (oz) = 28,350 .

1			
2			
3			
4			
5			
6			
7			

1: (. J.2). ,
 2: , (),
 3: , 1, :
 4: : (oz»in)
 5: , 4 ((oz»in)
 6: 5 3:.....

1,
 6. ,
 : (oz»in)
 : (oz*in)
 ()

J.1 —




Рисунок J.2 — Форма для определения остаточного дисбаланса. Полярная диаграмма

32601—2022

() : -101


 (, ,) :
 : 800 / ,
 : 10000 /
 (I/V) — () : 908 lb
 Umax — = 6350 / (4W/n)
 4 * 908 lb / 10000 / : 0,36 oz*in
 (2*) : 0,72 oz*in
 R— : 6,875 in
 — //?
 0,72 oz*in / 6,875 in : 0,1 oz
 — 1 (oz) = 28,350 .

1	0°	14
2	60°	12
3	120°	14
4	180°	23,5
5	240°	23
6	300°	15,5
7	0°	13,5

1: (. J.2).
 2: () ,
 3: 1, : 35
 4: : 0,72 oz*in
 5: 4 () : 1,44 oz*in
 6: 5 3: 0,041

1,
 6.
 : 6,5*0,041=0,27 oz*in
 : 0,36 oz*in
 -101 ()

J.3 —



J.4 —

J.4.2.6

J.4.2.1—J.4.2.5,

J.4.2.7

32601—2022

()

.1

2

.1

(. 9.1.1.3),

: D_1 —

», SFI

I_{SF} ,

(.1):

$$I_{SF} = L_3/D_4 + L_1 \cdot L_2/D_4 \quad (.1)$$

(.1)

L_1 —

(

);

L_2 —

(.1)


20 %

I_{SF} ,

$D_2 > L_2 <$

$$I_{SF} = I/D^* \quad (.2)$$

(.2)



1 —

; 2 —

; 3 —

; 4 —

;

5 —

(

); 6 —

;

—

.1 —

$\frac{1}{D^2} \frac{1}{D^2}$
($D^4 D^2$)

Z_{SF}

(.2)

1970-

80-

(

1,2)

(MTBR),

1990-

(VOC).

I_{SF}

I_{SF}

« »
 >120 %
 (. 6.9.1.2).
) (. 6.9.1.3).
 « »

$$K_t = (H)/N, \quad (.)$$
 Q — (), ;
 — ;
 N —


$$K_t = 25 \cdot 35000 \cdot (35 \cdot . .)$$

$$500000 \cdot /_{SF} \cdot)$$
 .).
 (. 4) (. 5)
 USC.

$${}^{SF-SI} = 32 \cdot {}^{-0,76}, \quad (. 4)$$


$${}^{snusc} = 6200 \cdot {}^{-0,76}. \quad (. 5)$$
 (. 4) (. 5)
 3600 / . 100 (4)
 3000 / .
 .2 (. 4) (. 5)
 /_{SF}
 1,2,
 .2 2, , 1, 2
 .2
 (. 6.10.1.6).
 25000
 16000
 20-
 3
 3
 « »,

32601—2022



.2 —

()



. —

(USC)

25000

16000

L_{10h}

$L_{10h\text{sys}}$

(.6):

$$L_{10h\text{sys}} = [(1/L_{10hA})^{3/2} + (1/L_{10hB})^{3/2}]^{2/3} + (1/L_{10h})^{3/2} \quad (-6)$$

L_{10hA} —

L_{10h}

18855 (281)\|

L_{10hB} —

L_{10h}

18855 (281)';

$Z_{iOh/y}$ —

L_{10h}

N

18855 (281).

1 —

L_{10h}
(.6)

$L_{Oh\text{sys}}$

25000

L_{10h}

37500

L_{10h}

37500

2 —

100000 (

)

L_{10h}

$L_{10h\text{sys}} = 25000$
25700

L_{10}

2,

1, 2

«

», . . .

«

», . . .

()

«

»,

98 %

10

3—4

(. . . « »)

(.7),

(4) (L_{10h} 18855—2013):

$$L_{10} = (C_r/P_r)^x, \quad (.7)$$

X—

3

10/3

32601—2022

Итого		в том числе		в том числе	
по	на	по	на	по	на
(.6),	,			16 %	-
				37 %.	,
					-
					,
					-
					,
					-
					,
(L _{10h} = 25000)				-
	L _{10h sys} 25000				,
					-
					,
					-
					,
(3000 3600 /)				-
				7315 7316	-
				75 80	,
					-
					-
					-
					-
«	»				-

(L)

L.1

L.1


,
)

(, , .),

L.2.1 ()

L.2.2 (-


32601—2022



-)
-)
-)
- d)
-)
- f)
-)
- h)
- i)
- j)
-)
- l)
-)
-)
-)
-)
- q)
-)

L.1 — , 1 2

- 1) / /
- 2) -
-) , ()
- 4) («X» « »,)
(« + «F» — : « + «S» —
« + « » —) .
- 5) () ,
- 6) () , , ,



			()											
			()											
			5)											
			5)											
V	V	W	1 ! W											
		s)												
		t)												
)												
		v)												
		w)												
)												
)												
		z)	: (),											
)												
		bb)												
)												
		dd)												
)												
		ff)												
)												
)												
)	: (),											
		d)												
)												
		f)												
)												
		h)												
		i)												

L.1, 2 2

1 —
 2 —
 () 3 —
 (,).

32601—2022

L.2

L.2.1

-)
 - 1) DN, PN ;
 - 2) ;
 - 3) , ;
 - 4) ;
 - 5) (;) () ;
 - 6) ;
 - 7) ;
 - 8) ;
 - 9) ;
 - 10) ;
 - 11) ; -
-)
-)
- d) ; -
-) ; -
- f) ; -
-) ;
- 1) ;
- 2) ; (
-);
- 3) ;
- 4) ;
- 5) ;
- 6) ;
- h) ; -
- i) ;
- 1) ;
- 2) ;
- 3) ;
- 4) ;
- j) ;
- : 1) ;
- 2) ;
- 3) ;
- 4) ;
- 5) () ;
- 6) ;
- () ;
- l) ;
-) ;
-) ;
-) ;
-) 3 1.1.2 1.1.3;
-) 3 6.9.2.10;
- q) ;

- s) () ;
- t)) ;
- v) (NPSH3), ;
- w)) ;
- z) () ;
- bb)) ;
- 1) 1. ;
 - I) ;
 - II) ;
 - III) ;
 - IV) ;
 - V) ;
 - VI) ;
 - VII) ;
 - VIII) ;
- 2) 2. ;
 - I) ;
 - II) ;
 - III) ;
- 3) 3. / ;
 - I) ;
 - II) ;
 - III) () ;
 - IV) ;
 - V) () ;
 - VI) ;
 - VII) ;
 - VIII) ;
- 4) 4. (NPSH3), — ;
- 5) 5. ;
 - I) ;
 - II) ;
 - III) ;
- 6) 6. () :
 - I) — ;
 - II) ;
 - III) () ;

20

32601—2022

- IV) ;
- V) .
- 7) 7. :
- I) ;
- II) ;
- III) ;
- IV) ;
- V) ;
- VI) ;
- VII) ;
- VIII) ;
- IX) (
- X) . .) ;
- XI) ;
- XII) ;
- dd) ;
-) ;
- ff) .
- L.2.2**
-) -
- 1) , ;
- 2) PN ;
- 3) ;
- 4) (-
-) ;
- 5) / ;
- 6) ;
- 7) ;
- 8) ;
-) ;
-) () , ;
- d) ;
-) ;
- 1) 150 ;
- I) 50 %- , 75 %- 100 %- ;
- II) ;
- 2) 150 -
- I) ;
- II) ;
- 70 %, 80 %, 90 % 100 % ;
- III) -
- IV) -
- V) 0 % 100 % ;
- f) ;

- g)
 - 1) 1. ;
 - I) ;
 - II) , ;
 - III) , ;
 - IV) , ;
 - 2) 2. ;
 - I) , ;
 - II) ;
 - III) ;
 - IV) ;
 - 3) 3. / ;
 - I) ;
 - II) ;
 - III) ;
 - IV) ;
 - 4) 4.) L.2.2.
 - 5) 5. ;
 - I) ;
 - II) ;
 - 6) 6. ;
 - I) ;
 - II) ;
- h) ;
- i) .

32601—2022

()

.2, .4 .1

USC,

:					
()					
:					
()					
(16)					
				+/- %	+/- %
NPSH3					
, /					
		()			
				()	
(6.1.15)		%		(6.1.15) %	

.1 —

, 1 2



32601—2022

						(. 6.9.3)					
-		/		:							
-		/		:							
-		/		:							
-		/		:							
						, (F) (. 6.10.2.4, 9.2.5.2.4(c) 9.2.5.3)					
()		-									
1 —											
());		() —		/ (/) RMS		— °C (°F).	

.1, 2 2

32601—2022


: : 3 : 1485 : D2 , : 332,0	, / ³ : 999,23 , °C: 20 , / ² : 1,0 -06 , ² : 28000 , : 332,0 D2 , : 315,4	:- (rated point): , / ³ : 650 , : 95 NPSH3, : 6,3 , : 214,3 , %: 78,5



(rated point), (normal point), NPSH3,)
 .2 — ()

32601—2022

		USgal/min <u>900.0</u>
		°F <u>325</u>
		NPSH3, <u>17.1</u>
		, ... <u>72.4</u>
		, % <u>88,3</u>



X — , US / ; 1 — , ; 2 — , %; 3 — ; 4 — NPSH3, ;
 ; b — ; 1 — ; 2 — ; 3 — ; 4 — NPSH3
 (, , NPSH3,)
 .4 — (USC)

(N)

N.1

N.2

(EDE)

)

- 1)
- 2)
- 3)
- 4)

)

- 1)
- 2)
- 3)

(EDE),

<http://www.pumps.org/ede>.

raulic Institute),
 ().
www.fiatech.org/aex.html.

FIATECH API
EDE

(Hyd-

XML

2 —

www.fiatech.org/aex.html.

XML,

[74], www.pumps.org/ede

FIATECH

1) , . [74].

32601—2022

()

()

: _____ : _____ : _____ : _____ : _____ : _____ : _____																																																													
: _____																																																													
<table border="1" style="margin: auto; border-collapse: collapse;"> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </table>																																																													

1													
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13		(6.1.2):											
14													
15		NPSHA											
16													
17													
18													
19													
20													
21													
22		NPSHA:											
23													
24													
25													
26													
27													
28													
29													
30													
31													
32													
33													
34													
35													
36													
37													
38													
39													
40													
41								(7.1.5):					
42													
43													
44													
45													
46													
47													
48													
49													
50													
51													
52													
53													
54		NPSHa	NPSH3										
55													
56													
57													
58													
59													
60													
61													

32601—2022

1			
2	(32601):	:
3			(6.3.10):
4		(6.5.5):	(9.1.2.6)
5		DN . . PN	:
6	:		(6.3.6) °C
7	:		°C
8		(6.4.3.2):	
9		DN . . PN	:
10	:		MAWP
11	:		()
12	:		
13	:		/ 4/ 5
14	:		/ 4/ 5
15	:		
16			(9.1.1.3):
17	:		1- « » ():
18	:		G1.0 1940-1:
19	:		(9.2.2.3):
20	:		
21	:	< 50 °C (6.4.3.2):	(7.2.3, 7.2.13(e)):
22	:	(6.4.3.3):	:
23	:	(6.4.3.8):	:
24	:	:	(/100):
25	:	(6.4.3.12):	:
26	:	VS6:	:
27	:	:	:
28			(7.2.10):
29		(6.12.1.1):	G6.3 ISO1940-1 (7.2.3):
30			(7.2.11):
31		(6.12.4.1): °C	(7.2.4):
32		(6.12.1.12.1):	(7.2.13):
33		(6.12.1.12.3):	:
34		():	:
35	:		:
36	:		:
37	:		:
38	:		(7.3.14):
39	:		(7.3.1):
40	:		:
41		(« »), VS:	(7.3.13):
42	:		:
43		(6.10.1.1):	:
44		(/): (6.11.4)	:
45			:
46			(7.3.5):
47		(9.2.5.2.4):	(7.3.6):
48			:
49		(6.10.2.2,6.11.3,9.6.1):	:
50		ISO 10438: (.2.6.5)	:
51		ISO 10438:	:
52		:	:
53		:	:
54		:	:
55		:	:
56		:	:
57		ISO: VG	:
58		:	:
.2			

1	-	:	/	:
2	API 670:		/	
3	(7.4.2.1):		(7.5.1.4):	
4	:		:	
5				
6				
7	(6.10.2.10):			
8	:		(6.8.1):	
9	:		API682/ISO21049:	
10			(6.8.9):	
11	(6.10.2.11):		(6.8.11):	
12	:			
13	:		(6.1.17):	
14			:	
15	(7.4.2.2):		:	
16	:		-	
17	-		:	
18	-			
19	(7.4.2.4):			
20				
21	(7.4.2.3):			
22	:			
23	:			
24	-			
25	:			
26	-			
27	-			
28	() (9.1.3.6):			
29	:			
30	:			
31				
32			(7.5.2.4):	
33				
34			(7.5.2.8):	
35				
36				
37				
38				
39				
40				
41				
42				
43				
44				
45				
46				
47				
48				
49				
50				
51				
52				
53				
54				
55				
56				
57				
58				
59				
60				

32601—2022

1		:	:
2		:	(8.1.1):
3	(.):	:	:
4	:	:	:
5	:	:	(8.3.3.26):
6	:	:	(6.12.1.8):
7	:	:	:
8	:	:	:
9	:	:	:
10	:	:	(6.12.2.5,6.12.3.1):
11	:	:	(6.12.3.4 ,):
12	:	:	:
13	:	:	:
14	:	:	:
15	(8.4.1):	:	:
16	:	:	:
17	6 :	:	(8.2.2.7):
18	:	:	(6.12.1.5, 8.2.1.3):
19	- (9.2.8.2):	- :	:
20	- (9.2.8.3):	- :	:
21			(8.2.2.8):
22	- (.2.8.4):	- :	:
23	:	:	:
24	:	:	(.4.1.2):
25	:	:	:
26			(8.1.1 , 8.3.3.5):
27			(7.3.21):
28			:
29			« » (9.3.13.2):
30			:
31			(8.3.3.2):
32			(8.3.3.3):
33	(10.1.3):		(8.3.3.4):
34	:	NPSH	(8.3.4.3.1, 8.3.4.3.4):
35	- :	NPSH	1- (8.3.4.3.2):
36	- , (3.33 3.34):	NPSH	.6 ISO9906 (8.3.4.3.3):
37	- , / - :	NPSH	110% . NPSHa (8.3.3.6):
38	(9.2.1.4):		(8.3.3.2):
39	(6.9.2.10):		(8.3.3.76):
40	:		(8.3.4.4.1):
41	(10.2.5):		(8.3.4.5):
42	20 (8.2.1.1):		(8.2.2.6):
43	(9.1.3.4, 9.2.4.1.3):		:
44	(9.3.9.2):		:
45	(6. .4.4):		:
46	[)10.2.3]:		:
47		4 . .	(8.3.4.2.1):
48	(6.9.2.3):	4 . .	(8.3.4.2.2):
49			(8.3.4.7):
50	(6.9.2.4)		(9.3.9.2):
51	(6.10.1.6):		:
52	(10.3.2.3):		(9.2.7.5):
53	(7.5.2.8):		(8.3.4.6):
54	(6.9.3.3):		:
55	(7.5.1.7):		:
56	:		:
57			:
58	(8.2.1.1B)		(6.12.4.3): EN 13445:
59	(8.3.1.1):		ASME Section VIII:
60	(8.1.5):		:
61			:

1		(1.1): _____	
2		: _____	
3			
4			
5		:	
6		: «+» «-»	:
7		:	: _____
8		:	: _____
9		:	:
10		:	: _____
11		:	:
12		: _____	: _____
13		: _____	: _____
14		: _____	:
15		: _____	(9.3.10.5): _____
16		:	:
17		: _____	(9.3.5): _____
18		: _____	:
19		: _____	:
20		: _____	:
21		: _____	: _____
22		:	: _____
23		:	: _____
24		: _____	(9.3.8.3.1): _____
25		: _____	(9.3.8.3.3): _____
26		: _____	(9.3.13.5): _____
27		:	: _____
28		(): _____	
29		/ « »: _____	: _____
30		: _____	: _____
31		: _____	: _____
32		: _____	: _____
33		: _____	: MAWP
34		: _____	:
35		« »: _____	: _____
36		: _____	(« »): _____
37		:	:
38		:	:
39		1 _____	12 _____ 3 _____
40		2 _____	/ / / V.
41		3 _____	/ / /
42		1 _____	/ / /
43		L ₂ _____	/ / /
44		L ₃ _____	/ / /
45		4 _____	/ / /
46		1-5 _____	/ / /
47		L _α _____	/ / /
48		Od _____	/ / /
49		:	/ / /
50		:	/ / /
51		:	/ / /
52		:	/ / /
53		:	/ / /
54		:	/ / /
55		:	/ / /
56		:	/ / /
57		:	/ / /
		: _____	.5 _____

32601—2022

1			
2		:	
3		(3):	
4		:	
5			
6			
7		(. 10,):	
8		:	
9		():	
10		:	
11		:	
12		(, .):	
13		:	
14		:	
15		:	
16			
17		:	
18		:	
19		14, :	
20		(. 14) (8.2.2.5):	
21		:	:
22		:	:
23		:	:
24		:	:
25		:	:
26		()	
27			
28		:	
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			
44			
45			
46			
47			
48			
49			
50			
51			
52			
53			
54			
55			
56			
57			
58			
59			
60			
		:	. 6

()

,

.1

		()
8724—2002 (261—98)	MOD	ISO 261:98 « . » .
18855—94 (281—89)	MOD	ISO 281:89 « (-)» (-
24705—2004 (724:1993)	MOD	ISO 724:1993 « . » .
16093—2004 (965-1:1998, 965-3:1998)	MOD	ISO 965-1:1998, ISO 965-3:1998 « - - » . . .
1940-1—2007	IDT	ISO 1940-1:2007 « . . . 1. - - » .
24069—97 (3117—77)	MOD	ISO 3117:77 « . » .
6134—2007 (9906:1999)	MOD	ISO 9906:1999 « . - 1 2» . -
31320—2006 (11342:1998)	MOD	ISO 11342:1998 « . » . -
32600 (130 21049:2009)	MOD	ISO 21049:2009 « . » .
31252—2004 (3740:2000)	MOD	ISO 3740:2000 « . » . -
22247—96 (2858—75)	MOD	ISO 2858—75 « . » . -
<p>— : ;</p> <p>- IDT — ;</p> <p>- MOD — .</p>		

32601—2022

- [1] API Std 685 Sealless Centrifugal Pumps for Petroleum, Petrochemical and Gas Industry Process Services
()
- [2] ISO 9905 Technical specifications for centrifugal pumps — Class 1 ()
- [3] ANSI/API Std 682 Shaft Sealing Systems for Centrifugal and Rotary pumps ()
- [4] ISO/TR 17766 Centrifugal Pumps Handling Viscous Liquids — Performance Corrections
()
- [5] ANSI/HI 9.6.7 Effects of Liquid Viscosity on Rotodynamic (Centrifugal and Vertical) Pump Performance
()
- [6] ISO 3744 Acoustics — Determination of sound power levels of noise sources using sound pressure Engineering method in an essentially free field over a reflecting plane
()
- [7] ISO 3746 Acoustic — Determination of sound power levels of noise sources using sound pressure — Survey method using an enveloping measurement surface over a reflecting plane
()
- [8] IEC 60079 () Explosive atmospheres. Equipment — all parts
()
- [9] NFPA 70:2008 National Electrical Code
()
- [] ISO 262 ISO general purpose metric screw threads — Selected sizes for screws bolts and nuts
()
- [11] ANSI/ASME B1.1 Unified Inch Screw Threads, UN and UNR Thread Form
(UN UNR)
- [12] ANSI/ASME B18.18.2M Inspection and Quality Assurance for High-Volume Machine Assembly Fasteners
()
- [13] ISO 7005-2 Metallic flanges — Part 2: Cast iron flanges
(2.)
- [14] ISO 7005-1 Metallic flanges — Part 1: Steel flanges for industrial and general service piping systems
(1.)
- [15] ANSI/ASME B16.1 Gray Iron Pipe Flanges and Flanged Fittings: Classes 25, 125 and 250
(: 25, 125 250)
- [16] ANSI/ASME B16.5 Pipe Flanges and Flanged Fittings: NPS 1/2 through NPS 24 Metric/Inch Standard
(: NPS 1/2 NPS 24 /)
- [17] EN 1759-1 Flanges and their joints — Circular flanges for pipes, valves, fittings and accessories, Class designated — Part 1: Steel flanges, NPS 1/2 to 24
(1. NPS 1/2 to 24)
- [18] ANSI/API Std 610 Centrifugal Pumps for Petroleum, Petrochemical and Natural Gas Industries
()

- [19] ANSI/ASME 16.42 Ductile Iron Pipe Flanges Fittings, Classes 150 and 300
() 150 300)
- [20] ANSI/ASME B16.47 Larger Diameter Steel Flanges: NPS 26 Through NPS 60
(: NPS 26 NPS 60)
- [21] ISO 7-1 Pipe threads where pressure-tight joints are made on the threads — Part 1: Dimensions, tolerances
(. 1. -)
- [22] ANSI/ASME B1.20.1 Pipe Threads, General Purpose (Inch)
(())
- [23] ISO 228-1 Pipe threads where pressure-tight joints are not made on the threads — Part 1: Dimensions
(. 1. -)
- [24] ANSI/ASME B16.11 Forged Steel Fittings, Socket-Welding and Threaded
()
- [25] DIN 910 Heavy-duty hexagon head screw plugs
()
- [26] ISO 3117 Tangential Keys and Keyways
()
- [27] ANSI/ASME B17.1 Keys and Keyseats
()
- [28] ANSI/API Std 670 Machinery Protection Systems
()
- [29] ANSI/API Std 541 Form-Wound Squirrel-Cage Induction Motors — 375 kW (500 Horsepower) and Larger
(375 (500 . .)) -
- [30] ISO 5753 () Rolling bearings — Internal clearance
(—)
- [31] ANSI/ABMA 20 Radial Bearings of Ball, Cylindrical Roller and Spherical Roller Types — Metric Design
(. -)
- [32] ISO 281 Rolling bearings — Dynamic load ratings and rating life
(.)
- [33] ANSI/ABMA 9 Load Ratings and Fatigue Life for Ball Bearings
(. -)
- [34] ANSI/ABMA 7 Shaft and Housing Fits for Metric Radial Ball and Roller Bearings (Except Tapered Roller Bearings) Conforming to Basic Boundary Plan
(. -)
- [35] EN 13463-1 Non-electrical equipment for use in potentially explosive atmospheres. Basic method and requirements
(. 1.) -
- [36] NACE MR0103 Materials Resistant to Sulfide Stress Cracking in Corrosive Petroleum Refining Environments
(. -)
- [37] ISO 15156/ANSI/NACE MR0175 () Petroleum and natural gas industries — Materials for use in H₂S-containing environments in oil and gas production.
Part 1: General principles for selection of cracking-resistant materials.
Part 2: Cracking-resistant carbon and low alloy steels, and the use of cast irons.
Part 3: Cracking-resistant CRAs (corrosion-resistant alloys) and other alloys

32601—2022

- (
1.
2.
3. (),
))
- [38] NACE Corrosion Engineer's Reference Book NACE Corrosion Engineer's Reference Book ([])
- [39] MSS SP-55 Quality Standard for Steel Castings for Valves, Flanges and Fittings and Other Piping Components — Visual Method for Evaluation of Surface Irregularities (—)
- [40] ASME Boiler and pressure vessel code (BPVC) Section IX ASME Boiler and pressure vessel code (BPVC). Section IX — Welding, Brazing and Fusing Qualifications (IX —)
- [41] ISO 9606 () Qualification testing of welders — Fusion welding ()
- [42] ISO 15609 () Specification and qualification of welding procedures for metallic materials — Welding procedure specification ()
- [43] ANSI/ASME B31.3 Process Piping Guide (/)
- [44] ISO 10721-2 Steel structures — Part 2: Fabrication and erection (2.)
- [45] ASME Boiler and pressure vessel code (BPVC) Section VIII Division 1 ASME Boiler and pressure vessel code (BPVC). Section VIII. Division 1 — Rules for Construction of Pressure Vessels (VIII. 1 —)
- [46] EN 13445 () Unfired pressure vessels ()
- [47] API RP 500 Recommended Practice for Classification of Locations for Electrical Installations at Petroleum Facilities Classified as Class 1, Division 1 and Division 2 (1, 1 2)
- [48] IEC 60034 () Rotating Electrical Machines ()
- [49] API Std 547 General-Purpose Form-Wound Squirrel Cage Induction Motors — 250 Horsepower and Larger (250)
- [50] IEEE 841 IEEE Standard for Petroleum and Chemical Industry — Severe Duty Totally Enclosed Fan-Cooled (TEFC) Squirrel Cage Induction Motors — Up to and Including 500 hp (IEEE (TEFC), 500 . .)
- [51] ANSI/API Std 611 General-Purpose Steam Turbines for Petroleum, Chemical, and Gas Industry Services ()

- [52] ANSI/API Std 677 General-Purpose Gear Units for Petroleum, Chemical and Gas Industry Services
()
- [53] ANSI/AGMA 9000 Flexible Couplings — Potential Unbalance Classification
()
- [54] ISO 14691 Petroleum, petrochemical and natural gas industries — Flexible couplings for mechanical power transmission—General purpose applications ()
- [55] ANSI/API Std 671/
ISO 10441 Petroleum, petrochemical and natural gas industries — Flexible couplings for mechanical power transmission — Special-purpose applications ()
- [56] ANSI/AGMA 9002 Bores and Keyways for Flexible Couplings (Inch Series)
()
- [57] ISO 14120 Safety of machinery—Guards — General requirements for the design and construction of fixed and movable guards
()
- [58] EN 953 Safety of machinery. Guards. General requirements for the design and construction of fixed and movable guards
()
- [59] ANSI/AMT B15.1 Safety Standard for Mechanical Power Transmission Apparatus
()
- [60] API RP 686 Recommended Practice for Machinery Installation and Installation Design
()
- [61] ISO 8501 () Preparation of steel substrates before application of paints and related products — Visual assessment of surface cleanliness
()
- [62] SSPC SP6 Commercial Blast Cleaning ()
- [63] ISO 10438 () Petroleum, petrochemical and natural gas industries — Lubrication, shaft-sealing and control-oil systems and auxiliaries
()
- [64] ANSI/API Std 614 Lubrication, Shaft-sealing and Oil-control Systems and Auxiliaries
()
- [65] ASME SA-193/SA-193M Specification for alloy-steel and stainless steel bolting materials for high-temperature or high pressure service and other special purpose applications
()
- [66] ASTM A153/A153M Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware
()
- [67] ASME Boiler and pressure vessel code (BPVC) Section V ASME Boiler and pressure vessel code (BPVC). Section VI. Nondestructive Examination
()
- [68] ISO 9906 Rotodynamic pumps — Hydraulic performance acceptance tests — Grades 1,2 and 3
(1,2 3)
- [69] ANSI/HI 1.6 Centrifugal Pump Tests
()

32601—2022

- [70] ANSI/HI 2.6 Vertical Pump Tests
()
- [71] ISO 15649 Petroleum and natural gas industries — Piping
()
- [72] ISO 11342 Mechanical vibration — Methods and criteria for the mechanical balancing of flexible rotors
()
- [73] ISO 4200 Plain end steel tubes, welded and seamless; general tables of dimensions and masses per unit length
()
- [74] BSR/HI 50.7 Electronic Data Exchange for Pump Data
()

62-762.6:006.354

23.080

: , , ,

11.07.2022. 01.08.2022. 60x84%.
. . . 21,86. .- . . 19,67.

« »
117418 , - , . 31, . 2.
www.gostinfo.ru info@gostinfo.ru